

CONTENTS

| | Page |
|--|---------------|
| ACKNOWLEDGEMENTS | iii |
| ABSTRACT (ENGLISH) | iv |
| ABSTRACT (THAI) | v |
| LIST OF TABLES | xi |
| LIST OF FIGURES | xiv |
| ABBREVIATIONS | xix |
| CHAPTER 1 INTRODUCTION | 1 |
| 1.1 Flow Injection Analysis (FIA) | 1 |
| 1.1.1 General and Principle | 1 |
| 1.1.2 Basic Components of an FIA System | 3 |
| 1.2 Phosphorus/Phosphate | 4 |
| 1.2.1 Spectrophotometry | 5 |
| 1.2.2 FIA Method | 6 |
| 1.3 Nitrates and Nitrites | 6 |
| 1.3.1 Colorimetric Method | 8 |
| 1.3.2 Ion Chromatography Method | 9 |
| 1.3.3 FIA Method | 9 |
| 1.4 Chromium | 9 |
| 1.4.1 Diphenylcarbazide Method | 10 |
| 1.4.2 Chromate Method | 10 |
| 1.4.3 Atomic Absorption Method-Chelation Extraction | 11 |
| 1.4.4 FIA Method | 11 |
| 1.5 Calcium | 12 |
| 1.5.1 Complexometric Method | 13 |
| 1.5.2 Atomic Absorption Method-Direct | 14 |
| 1.5.3 FIA Method | 14 |
| 1.6 Aims of the Thesis | 14 |
| CHAPTER 2 EXPERIMENTAL, RESULTS AND DISCUSSION | 15 |
| 2.1 Instruments, Apparatus and Chemicals | 15 |
| 2.1.1 Instruments and Apparatus | 15 |
| 2.1.2 Chemicals | 15 |
| 2.2 Solutions | 16 |
| 2.3 Determination of Phosphate by Flow Injection Fluorometric Method | 20 |
| 2.3.1 Preliminary Studies of the Fluorescence Spectra Scanning | 20 |
| 2.3.2 Manifold | 21 |
| 2.3.3 Optimization of Flow Injection Determination of Phosphate | 21 |
| 2.3.3.1 Effect of H ₂ SO ₄ Concentration | 22 |
| 2.3.3.2 Effect of Ammonium Molybdate Concentration | 23 |
| 2.3.3.3 Effect of Rhodamine B Concentration | 24 |
| 2.3.3.4 Effect of PVA Concentration | 25 |

| | Page |
|---|------|
| 2.3.3.5 Effect of Flow Rate of the two Streams (CS and RS) | 26 |
| 2.3.3.6 Effect of Reaction Coil Length | 27 |
| 2.3.3.7 Effect of Sample Volume | 28 |
| 2.3.3.8 Summary of Condition Used | 29 |
| 2.3.3.9 Calibration Curve and Detection Limit | 29 |
| 2.3.3.10 Precision | 31 |
| 2.3.3.11 Interference Studies | 31 |
| 2.3.3.12 The Effect of Suspended Solids (SS) | 36 |
| 2.3.3.13 Determination of Phosphate in Natural Water Sample | 37 |
| 2.3.3.14 Standard Addition FIA | 39 |
| 2.4 Flow Injection Determination of Nitrite and Nitrate | 41 |
| 2.4.1 Absorption Spectrum | 41 |
| 2.4.2 Manifold | 41 |
| 2.4.3 Optimization of Flow Injection Determination of Nitrite | 43 |
| 2.4.3.1 Effect of NED Concentration | 43 |
| 2.4.3.2 Effect of Sulfanilamide Concentration | 43 |
| 2.4.3.3 Effect of H_3PO_4 Acid Solution Concentration | 44 |
| 2.4.3.4 Effect of Flow Rate of Reagent Stream | 44 |
| 2.4.3.5 Effect of GBC Length | 45 |
| 2.4.3.6 Effect of Sample Volume | 45 |
| 2.4.3.7 Summary of Condition Used | 46 |
| 2.4.3.8 Calibration Curve and Detection Limit | 46 |
| 2.4.3.9 Precision | 48 |
| 2.4.3.10 Interference Studies | 48 |
| 2.4.4 Sequential Flow Injection Determination of Nitrite and Nitrate | 49 |
| 2.4.4.1 Effect of Cd-Column Length | 49 |
| 2.4.4.2 Effect of Cadmium Granule Size | 50 |
| 2.4.4.3 Effect of Flow Rate Passing Through Cd-Column | 51 |
| 2.4.4.4 Regenerating the Cd-Column | 52 |
| 2.4.4.5 Summary of Conditions Used | 53 |
| 2.4.4.6 Calibration Curve and Detection Limit | 54 |
| 2.4.4.7 Interference Studies | 55 |
| 2.4.4.8 Effect of Cd-Column for Nitrite Determination | 57 |
| 2.4.4.9 A study for Nitrite and Nitrate Mixture | 58 |
| 2.4.4.10 Determination of Nitrite and Nitrate in a Water Sample | 59 |
| 2.5 Determination of Chromium | 60 |
| 2.5.1 Absorption spectra of Metal-DPC Complexes | 60 |
| 2.5.2 Manifold | 64 |
| 2.5.3 Optimization of FI Determination of Chromium(VI) | 65 |
| 2.5.3.1 Effect of Flow Rates of Methanol, Sample and R1 Streams | 65 |
| 2.5.3.2 Effect of DPC Concentration | 66 |
| 2.5.3.3 Effect of Acid Concentration of DPC Solution | 67 |

| | Page |
|---|-------------|
| 2.5.3.4 Effect of the GBC Length | 68 |
| 2.5.3.5 Effect of the RC Length | 69 |
| 2.5.3.6 Summary of Conditions Used for Cr(VI) Determination | 70 |
| 2.5.3.7 Calibration Curve and Detection Limit | 70 |
| 2.5.3.8 Precision | 72 |
| 2.5.3.9 Interference Studies | 73 |
| 2.5.4 Optimization of Sequential Determination of Chromium(VI) and Chromium(III) | 75 |
| 2.5.4.1 Effect of Cerium(IV) Concentration | 75 |
| 2.5.4.2 Effect of H ₂ SO ₄ Acid Concentration in the Reagent R2 | 76 |
| 2.5.4.3 Effect of DPC Concentration | 77 |
| 2.5.4.4 Effect of the RC1 Length | 78 |
| 2.5.4.5 Effect of the Aqueous Methanol Concentration | 79 |
| 2.5.4.6 Effect of pH in a Mixture of Chromium(VI) and Chromium(III) | 80 |
| 2.5.4.7 Effect of Loading Time on Calibration Curve | 81 |
| 2.5.4.8 Summary of the Conditions Used | 83 |
| 2.5.4.9 Calibration Curve and Detection Limit | 84 |
| 2.5.4.10 Precision | 86 |
| 2.5.4.11 Determination of Chromium(VI) and Chromium(III) in Sample Drinking Water | 86 |
| 2.6 Determination of Calcium: | 87 |
| 2.6.1 Determination of Calcium by Using Murexide | 87 |
| 2.6.1.1 Absorption Spectra | 87 |
| 2.6.1.2 Manifold | 87 |
| 2.6.1.3 Effect of Murexide Concentration | 88 |
| 2.6.1.4 Effect of Sample Volume | 89 |
| 2.6.1.5 Effect of Flow Rates of Murexide and Ethylenediamine Buffer Streams | 90 |
| 2.6.1.6 Effect of LED Color | 91 |
| 2.6.1.7 Effect of pH | 92 |
| 2.6.2 Determination of Calcium by Using Calmagite | 97 |
| 2.6.2.1 Absorption Spectra | 97 |
| 2.6.2.2 Manifold | 98 |
| 2.6.2.3 Effect of the Amount of EDTA | 98 |
| 2.6.2.4 Effect of Calmagite Concentration | 99 |
| 2.6.2.5 Effect of MgCl ₂ Concentration | 100 |
| 2.6.2.6 Effect of Sample Volume | 101 |
| 2.6.2.7 Effect of the RC Length | 102 |
| 2.6.2.8 Effect of Flow Rate | 103 |
| 2.6.2.9 Summary of the Conditions Used | 105 |
| 2.6.2.10 Calibration Curve and Detection Limit | 105 |
| 2.6.2.11 Precision | 107 |
| 2.6.2.12 Application of the Procedure for the Determination of Hardness Water Samples | 107 |

| | Page |
|------------------------------|------|
| CHAPTER 3 CONCLUSIONS | 109 |
| REFERENCES | 110 |
| APPENDICES | 113 |
| APPENDIX A | 114 |
| APPENDIX B | 115 |
| APPENDIX C | 116 |
| APPENDIX D | 119 |
| APPENDIX E | 120 |
| APPENDIX F | 122 |
| APPENDIX G | 123 |
| APPENDIX H | 125 |
| APPENDIX I | 126 |
| APPENDIX J | 127 |
| VITA | 129 |

LIST OF TABLE

| Table | Page |
|--|------|
| 1.1 Some industrially important chromium compounds | 10 |
| 1.2 Classification of water by hardness content | 12 |
| 1.3 Maximum hardness levels accepted by industry as a raw water source | 13 |
| 2.1 Effect of H_2SO_4 concentration on peak height ; mean of triplicate injections. | 22 |
| 2.2 Effect of ammonium molybdate concentration on peak height ; mean of triplicate injections. | 23 |
| 2.3 Effect of RB concentration on peak height ; mean of triplicate injections. | 24 |
| 2.4 Effect of PVA concentration on peak height ; mean of triplicate injections. | 25 |
| 2.5 Effect of flow rates of CS and RS on peak height ; mean of triplicate injections. | 26 |
| 2.6 Effect of reaction coil length on peak height ; mean of triplicate injections. | 27 |
| 2.7 Effect of sample volume on peak height ; mean of triplicate injections. | 28 |
| 2.8 Conditions used for the determination of phosphate | 29 |
| 2.9 Calibration curve for phosphate. | 29 |
| 2.10 Precision study using $80 \mu\text{g PO}_4^{3-}/\text{l}$, $n = 12$ | 31 |
| 2.11 Effect of interference for phosphate concentration of $50 \mu\text{g/l}$; mean of triplicate injections. | 31 |
| 2.12 Summary of the interference effect for phosphate determination. | 35 |
| 2.13 Effect of SS (kaolin) on peak height ; mean of triplicate injections. | 36 |
| 2.14 Determination of phosphate in natural water. | 38 |
| 2.15 The phosphate contents found by using FIA standard addition method ; mean of triplicate injections. | 40 |
| 2.16 Effect of NED concentration on peak height ; mean of triplicate injections. | 43 |
| 2.17 Effect of sulfanilamide concentration on peak height ; mean of triplicate injections. | 43 |
| 2.18 Effect of H_3PO_4 acid solution concentration on peak height ; mean of triplicate injections. | 44 |
| 2.19 Effect of flow rate reagent stream on peak height ; mean of triplicate injections. | 44 |
| 2.20 Effect of GBC length on peak height ; mean of triplicate injections. | 45 |
| 2.21 Effect of sample volume on peak height ; mean of triplicate injections. | 46 |
| 2.22 Conditions used for the determination of nitrite. | 46 |
| 2.23 Calibration curve of nitrite ; mean of triplicate injections. | 46 |
| 2.24 Precision study of $50 \mu\text{g NO}_2^-/\text{l}$, $n = 15$. | 48 |
| 2.25 Effect of interfering ions for nitrite concentration of 0.05 mg/l ; mean of triplicate injections. | 48 |
| 2.26 Effect of Cd-column length on peak height ; mean of triplicate injections. | 50 |

| Table | Page |
|--|------|
| 2.27 Effect of cadmium granule size on peak height ; mean of triplicate injections. | 50 |
| 2.28 Effect of flow rate passing through Cd-column on peak height ; mean of triplicate injections. | 51 |
| 2.29 Effect of regenerating time and precision of the Cd-column on peak height ; mean of the first 30 replicate injections. | 52 |
| 2.30 Effect of regenerating efficiency and precision of the Cd-column on peak height ; mean of the first 30 replicate injections of nitrate. | 53 |
| 2.31 Condition used for the determination of nitrite and nitrate. | 53 |
| 2.32 Calibration curve for nitrite ; mean of triplicate injections. | 54 |
| 2.33(a) Effect of interference cations for nitrate concentration of 200 µg/l. | 55 |
| 2.33(b) Effect of interfering anions for nitrate concentration of 100 µg/l. | 56 |
| 2.34 Summary of the interference effect for nitrate determination. | 57 |
| 2.35 Effect of Cd-column for nitrite determination peak height ; mean of triplicate injections. | 57 |
| 2.36 A study for nitrite mixture on peak height ; mean of triplicate injections. | 58 |
| 2.37 FIA determination of nitrite and nitrate in spiked water samples. | 59 |
| 2.38 Molar absorptivity study of chromium(VI)-DPC complex. | 61 |
| 2.39 Effect of flow rates of methanol , sample and R1 stream on peak height, mean of duplicate injections. | 65 |
| 2.40 Effect of DPC concentration on peak height ; mean of triplicate injections. | 66 |
| 2.41 Effect of H ₂ SO ₄ concentration in DPC solution on peak height ; mean of triplicate injections. | 67 |
| 2.42 Effect of HNO ₃ concentration in DPC solution on peak height ; mean of triplicate injections. | 68 |
| 2.43 Effect of the GBC length on peak height ;mean of triplicate injections. | 69 |
| 2.44 Effect of RC length on peak height ; mean of duplicate injections. | 69 |
| 2.45 Condition used for the determination of chromium(VI). | 70 |
| 2.46 Calibration curve for chromium(VI) ; mean of triplicate injections. | 71 |
| 2.47 Precision study using 0.1 mg Cr ⁶⁺ /l, n = 20. | 72 |
| 2.48 Effect of interference study for chromium(VI) concentration of 0.10 mg/l ; mean of triplicate injections. | 73 |
| 2.49 Summary of the interference effect for the 0.1 mg Cr ⁶⁺ /l. | 74 |
| 2.50 Effect of cerium(IV) concentration on peak height ; mean of triplicate injections. | 75 |
| 2.51 Effect of H ₂ SO ₄ acid concentration in the reagent R2 on peak height ; mean of triplicate injections. | 76 |
| 2.52 Effect of DPC concentration on peak height ; mean of triplicate injections. | 77 |
| 2.53 Effect of the RC1 length on peak height ; mean of triplicate injections. | 78 |

| Table | Page |
|---|------|
| 2.54 Effect of the aqueous methanol concentration on peak height ; mean of triplicate injections. | 79 |
| 2.55 Effect of pH in a mixture of 0.3 mg Cr^{6+}/l and 0.3 mg Cr^{3+}/l solution; mean of triplicate injections. | 80 |
| 2.56 Different loading time ; mean of triplicate injections | 81 |
| 2.57 Two sets of experiments ; a single standard solution and a constant loading time | 82 |
| 2.58 Condition for the sequential determination of chromium(VI) and chromium(III). | 83 |
| 2.59 Calibration curve Cr(VI) and Cr(III) standard solution ; mean of triplicate injections. | 84 |
| 2.60 Precision study using 0.1 mg Cr^{6+}/l , (n= 20) and 0.4 mg Cr^{3+}/l (n=20) | 86 |
| 2.61 Determination of Cr(VI) and Cr(III) in drinking water samples ; mean of triplicate injections. | 86 |
| 2.62 Effect of murexide concentration on peak height ; mean of triplicate injections. | 89 |
| 2.63 Effect of sample volume on peak height ; mean of triplicate injections. | 90 |
| 2.64 Effects of flow rates of murexide and ethylenediamine buffer streams on peak height ; mean of triplicate injections. | 91 |
| 2.65 Effect of LED color on peak height ; mean of triplicate injections. | 92 |
| 2.66 Effect of pH on absorption maxima (λ) and absorbance (A). | 93 |
| 2.67 Calibration curves : (a) Ca(II) -murexide and (b) Mg(II) -murexide complexes of various pHs ; mean of triplicate injections. | 94 |
| 2.68 Effect of the amount of EDTA on peak height ; mean of triplicate injections. | 99 |
| 2.69 Effect of calmagite concentration on peak height ; mean of triplicate injections. | 100 |
| 2.70 Effect of MgCl_2 concentration on peak height ; mean of triplicate injections. | 101 |
| 2.71 Effect of sample volume on peak height ; mean of triplicate injections. | 102 |
| 2.72 Effect of the RC length on peak height ; mean of triplicate injections. | 103 |
| 2.73 Effect of flow rate on peak height ; mean of triplicate injections. | 104 |
| 2.74 Conditions used for the determination of calcium by using calmagite. | 105 |
| 2.75 The calibration curve for Ca ; mean of triplicate injections. | 105 |
| 2.76 Precision study of 250 mg/l as CaCO_3 ; n = 12. | 107 |
| 2.77 Application of the procedure for the determination of hardness of water samples. | 107 |
| E.1 The determination of injection valve dead volume, ($H^0 = 6.20 \text{ mV}$). | 121 |

LIST OF FIGURES

| Figure | | Page |
|--------|---|------|
| 1.1 | (a) The simplest single-line FIA manifold utilizing a carrier stream of reagent ; S : the injection port , D : the flow cell and W : waste. (b) The analog output has the form of a peak, the recording starting at S (time of injection to) ; H : the peak height, W : the peak width at a selected level, A : the peak area, T : the residence time corresponding to the peak height measurement, and t_b : the peak width at the baseline. | 1 |
| 1.2 | Dispersion, D in the system defined as the ratio between the original concentration, C^0 and the concentration of the dispersed species, C^{max} . | 2 |
| 1.3 | Response curve upon dispersion as function of (a) injection sample volume, with sample volumes of 60, 110, 200, 400 and 800 μ l, (b) the tube length ; L is given in centimeters and (c) flow rate at various reactor lengths with a constant tube diameter. | 2 |
| 1.4 | General arrangement of an FIA system, showing its essential components ; propelling unit (peristaltic pump or gas-pressure unit), injection system, reaction zone (A: straight open tube, B : coiled tube, C : mixing chamber, D : single-bead string reactor and E: knitted reactor). Adopted from Vancarcial and luque de Castro and Ruzicka and Hansen | 3 |
| 1.5 | Representation of the operationally defined components of total dissolved phosphorus. | 4 |
| 1.6 | Chemical structure of Rhodamine B . | 6 |
| 1.7 | Nitrogen speciation in natural waters. Concentrations are expressed as mg nitrogen per litter. Values are quoted as ranges typically encountered in a variety of waters. The values in brackets represent indicative values at or above which problems have been known to occur , depending on a range of other factors. | 7 |
| 1.8 | Main biological process involving nitrogen. | 7 |
| 1.9 | Absorption spectra of (1) dichromate (in M H_2SO_4) and (2) chromate (in ammonical medium). | 11 |
| 1.10 | Chemical structure of (a) Murexide, (b) Eriochrome black T and (c) Calmagite. | 13 |
| 1.11 | Manifold for the simultaneous determination of calcium and sum of calcium and magnesium (hardness) ; ebt = Eriochrome black T, buffer = NH_4Cl/NH_3 buffer solution, Vi = injection valve, p = pump, L = reaction length, D = detector, W = waste, S1 and S2 = selecting valves. | 14 |
| 2.1 | Fluorescence spectra of RB and ion associate formed between molybdophosphate and RB. Spectra : (a) absorption and (b) emission : (1) the RB solution (0.8×10^{-4} % (w/v) RB + 0.1 M H_2SO_4 + 8×10^{-3} % (w/v) PVA), (2) 0.25 % (w/v) molybdate in the RB solution and (3) 20 μ g PO_4^{3-} /l together with molybdate (0.25 % (w/v)) in the RB solution. | 20 |

| Figure | Page |
|---|------|
| 2.2 Flow diagram of phosphate fluorimetric determination ; CS : carrier solution (H_2O), RS : reagent solution (ammonium molybdate + H_2SO_4 + RB + PVA), P : peristaltic pump, I : injection valve, S : sample, RC : reaction coil, FC : flow cell cassette (quartz cell), SF : spectrofluorometric detector (Jasco 821-FP) and W : waste. | 21 |
| 2.3 Effect of H_2SO_4 concentration on peak height ; (1) 0.4, (2) 0.6, (3) 0.8 and (4) 1.0 M H_2SO_4 . | 22 |
| 2.4 Effect of ammonium molybdate concentration on peak height ; Ammonium molybdate concentrations : (1) 0.5, (2) 1, (3) 2 and (4) 4% (w/v). | 23 |
| 2.5 Effect of RB concentration on peak height ; RB concentrations : (1) 0.5×10^{-4} , (2) 1×10^{-4} , (3) 3×10^{-4} , (4) 5×10^{-4} and (5) 7×10^{-4} % (w/v). | 24 |
| 2.6 Effect of PVA concentration on peak height ; PVA concentrations : (1) 0, (2) 0.005, (3) 0.01, (4) 0.03, (5) 0.05 and (6) 0.07 % (w/v). | 25 |
| 2.7 Effect of flow rate of the two streams on peak height ; Flow rates : (1) 0.5, (2) 0.7, (3) 1.0 and (4) 1.5 ml/min. | 26 |
| 2.8 Effect of reaction coil length on peak height ; Reaction coil lengths : (1) 50, (2) 100, (3) 150 and (4) 200 cm. | 27 |
| 2.9 Effect of sample volume on peak height ; Sample volumes : (1) 123, (2) 223, (3) 323, (4) 423, (5) 523 and (6) 623 μl . | 28 |
| 2.10 FIA signals for the determination of phosphate. S1, S2 and S3 : real samples 1, 2 and 3 respectively. | 30 |
| 2.11 Calibration curve for phosphate ($n = 3$). | 30 |
| 2.12 Effect of SS on peak height ; Kaolin concentrations : (1) 0, (2) 5, (3) 10, (4) 50, (5) 100, (6) 150 and (7) 200 mg/l. | 37 |
| 2.13 Comparison of phosphate concentrations in natural water samples determining by the normal-colorimetric FIA method and fluorimetric-FIA methods. | 39 |
| 2.14 Standard addition curve of the FIA phosphate determination (data of the sample No.4 in Table 2.15). | 40 |
| 2.15 Absorption spectrum of the azo dye product nitrite with reagent (versus reagent blank). | 41 |
| 2.16 Flow diagram ; R : coloring reagent (sulfanilamide and NED in phosphoric acid solution), S : sample, I : injection valve, P1 : peristaltic pump, P2 : aquarium pump, GBC : glass bead column, V : three way valve, W : waste , and Cd-column (Copperized cadmium column or cadmium reduction column). | 42 |
| 2.17 Effect of flow rate of reagent stream on peak height. | 45 |
| 2.18 FIA signals of nitrite standards. | 47 |
| 2.19 Calibration curve for nitrite standards ($n = 3$). | 47 |
| 2.20 Effect of cadmium granule size on peak height ; Cadmium granule sizes : (1) small (<16 mesh), (2) medium (16 - 9 mesh) and (3) large (<9 mesh). | 51 |
| 2.21 Effect of flow rate passing through Cd-column on peak height ; (1) blank and (2) 300 NO_3^- $\mu\text{g/l}$. | 52 |

| Figure | Page |
|---|------|
| 2.22 FIA signals of nitrate standards. | 54 |
| 2.23 Calibration curve of nitrate standards ($n = 3$). | 55 |
| 2.24 Effect of Cd-column for nitrite determination ; The nitrite calibration curves : (1) without Cd-column (2) with Cd-column. | 58 |
| 2.25 Absorption spectra of Cr(VI)-DPC-complex : (a) versus aqueous reagent solution (0.2 %w/v DPC + 0.2 M H ₂ SO ₄) and (b) versus methanol (see text for detail). | 61 |
| 2.26 Curve of a molar absorptivity study of chromium complex : (versus aqueous reagent solution ((0.2 %w/v DPC + 0.2 M H ₂ SO ₄) as a reference). | 62 |
| 2.27 Absorption spectra (versus H ₂ O as a reference) of : (1) the color reagent blank (0.1 % w/v DPC + 0.5 M HNO ₃ + 0.15 M H ₂ SO ₄), (2) Ce(IV) solution (0.6 %w/v Ce(NH ₄) ₄ (SO ₄) ₄ + 0.15 M H ₂ SO ₄), (3) 0.6 % w/v Ce(IV) in the color reagent, (4) 0.1 mg/l of Cr(VI) in the color reagent, (5) 1.0 mg/l of Cr(VI) and 0.6 % w/v Ce(IV) in the color reagent, (6) 1.0 mg/l Cr(VI) and 0.6 % w/v Ce(IV) in color reagent and (7) 1.0 mg/l Cr(III) in the color reagent | 63 |
| 2.28 Flow diagrams of the system designed for ; (a) determination of Cr(VI) (b) sequential determination of Cr(VI) and Cr(III) ; P : peristaltic pump, RC : reaction coil, R1 : reagent solution (DPC in acid solution), R2 : oxidizing reagent solution (Ce(IV) in sulfuric solution), GBC : glass bead column, V1 : three way valve (in Appendix A), V2 : rotary injection valve, C18 SPE column (see in Appendix C) on V2 and W : waste. | 64 |
| 2.29 Effect of flow rate on peak height for ; (1) blank (deionized water), (2) 0.1 and (3) 1.0 mg Cr ⁶⁺ /l. | 66 |
| 2.30 Effect of DPC concentration on peak height ; DPC concentrations : (1) 0.005, (2) 0.01, (3) 0.05, (4) 0.10 and (5) 0.15 % (w/v). | 67 |
| 2.31 Effect of acid concentration on peak height for (1) blank, H ₂ SO ₄ media , (2) 0.1 mg Cr ⁶⁺ /l, H ₂ SO ₄ media , (3) blank, HNO ₃ media and (4) 0.1 mg Cr ⁶⁺ /l, HNO ₃ media. | 68 |
| 2.32 Effect of the GBC length on peak height for ; (1) blank and (2) 1.0 mg Cr ⁶⁺ /l. | 69 |
| 2.33 Effect of the RC length on peak height ; (1) blank, (2) 0.1 and (3) 1.0 mg Cr ⁶⁺ /l. | 70 |
| 2.34 FIA signals for the determination of chromium(VI) using 60 sec loading time | 71 |
| 2.35 Effect of loading time on the calibration curve ; Loading time : (1) 40 sec [$y = 1396.56(x) - 29.24$, $r^2 = 0.993$] and (2) 60 sec [$y = 1610.02(x) - 26.36$, $r^2 = 0.998$] | 72 |
| 2.36 Effect of cerium (IV) concentration on peak height ; Cerium(IV) concentration : (1) 0.1, (2) 0.3, (3) 0.6, (4) 0.8, (5) 1.0, (6) 1.2 and (7) 2.0 % (w/v). | 76 |
| 2.37 Effect of H ₂ SO ₄ acid concentration in reagent R2 on peak height ; H ₂ SO ₄ concentration : (1) 0.3, (2) 0.5, (3) 1.0 and (4) 1.5 M. | 77 |
| 2.38 Effect of DPC concentration on peak height ; DPC concentrations : (1) 0.05, (2) 0.10, (3) 0.13, (4) 0.15 and (5) 0.20 % (w/v). | 78 |

| Figure | Page |
|--|------|
| 2.39 Effect of RC1 length on peak height ; RC1 lengths : (1) 50, (2) 120 and (3) 200 cm. | 79 |
| 2.40 Effect of the aqueous methanol concentration on peak height ; Methanol concentrations : (1) 30, (2) 50, (3) 70, (4) 80, (5) 90 and (6) absolute (99.8) % (v/v). | 80 |
| 2.41 Effect of pH in a mixture of 0.3 mg Cr^{6+}/l and 0.3 mg Cr^{3+}/l solution ; (1) blank, H_2O stream, (2) the mixture, H_2O stream, (3) blank, the Ce(IV) reagent stream (R2) and (4) the mixture, the Ce(IV) reagent stream. | 81 |
| 2.42 Calibration curve : Different loading time ; (1),(2),(3) 15, 30 and 60 sec, respectively using H_2O stream and (4),(5),(6) 15, 30 and 60 sec, respectively using the Ce(IV) reagent stream (R2). | 82 |
| 2.43 (1) a single standard and (2) conventional calibration. | 83 |
| 2.44 FIA signals for the chromium determination ; (a) Cr(VI), H_2O stream, (b) Cr(VI), R2 reagent stream, (c) Cr(III), R2 reagent stream. | 85 |
| 2.45 Calibration curve for chromium standards ($n = 3$) : (1) Cr(VI), H_2O stream, (2) Cr(VI), R2 reagent stream and (3) Cr(II), R2 reagent stream (see text). | 85 |
| 2.46 Absorption spectra of : (a) murexide (using water as a reference) and (b) its calcium(II) complex (using the reagent blank as a reference), buffer pH 11. | 87 |
| 2.47 Flow diagram of the system ; P1 : peristaltic pump, P2 : aquarium pump, GBC1 and GBC2 : glass bead column, S : sample, I : rotary injection valve and W : waste. | 88 |
| 2.48 Effect of murexide concentration on peak height ; Murexide concentrations : (1) 0.005, (2) 0.01, (3) 0.02, (4) 0.03 and (5) 0.04 % (w/v). | 89 |
| 2.49 Effect of sample volume on peak height ; Sample volumes : (1) 100, (2) 200, (3) 250 and (4) 300 μl . | 90 |
| 2.50 Effects of flow rates of murexide and ethylenediamine buffer streams on peak height for (1) 80 and (2) 160 mg Ca^{2+}/l . | 91 |
| 2.51 Effect of LED color on peak height (1) green, calcium, (2) yellow, calcium, (3) green, magnesium and (4) yellow, magnesium. | 92 |
| 2.52 Effect of pH : (a) Ca(II)-murexide and (b) Mg(II)-murexide complexes. | 93 |
| 2.53 FIA signals of Ca(II)- and Mg(II)-murexide complexes using of buffer pH being 9.5. | 95 |
| 2.54 Calibration curves for Ca(II)-murexide and Mg(II)-murexide complex in different pH values ; (1) pH = 9.0, (2) pH = 9.5, (3) pH = 10.5, (4) pH = 11.5 and (5) pH = 12.0. | 96 |
| 2.55 Absorption spectra : (a) versus H_2O ; (1) Calmagite (pH=10) (2) Ca-Calmagite (3) Mg-Calmagite complexes ; (b) : (1) the reagent in boric/borate buffer (pH=10) (Calmagite(0.001 % (w/v)), MgCl_2 (2×10^{-5} % (w/v)) and an amount of EDTA which just turned the red to blue), (2) Ca (40 mg/l) in the reagent, both using water as a reference and (3) the Casolution versus the reagent as reference). | 97 |

| Figure | Page |
|--|------|
| 2.56 Flow diagram of the system ; R : reagent (calmagite + MgCl_2 + EDTA + borate buffer), S : sample, P1 : peristaltic pump, P2 : aquarium pump, I : rotary injection valve, RC : reaction coil and W : waste. | 98 |
| 2.57 Effect of amounts of EDTA on peak height for ; (1)blank, (2) 100 and (3) 300 mg/l as CaCO_3 (blank subtraction). | 99 |
| 2.58 Effect of calmagite concentration on peak height ; Calmagite concentrations : (1) 0.003, (2) 0.006, (3) 0.009, (4) 0.012, (5) 0.015 and (6) 0.018 % (w/v). | 100 |
| 2.59 Effect of MgCl_2 concentration on peak height ; MgCl_2 concentrations : (1) blank ($\times 10$), (2) 100 and (3) 400 mg/l as CaCO_3 . | 101 |
| 2.60 Effect of sample volume on peak height ; Sample volumes : (1) 100, (2) 200 and (3) 300 μl . | 102 |
| 2.61 Effect of the RC length on peak height ; The RC lengths : (1) 20, (2) 50 and (3) 100 cm. | 103 |
| 2.62 Effect of flow rate on peak height ; Flow rates : (1) 1.2, (2) 3.3 and (3) 7.0 ml/min. | 104 |
| 2.63 FIA signals of Ca standard. | 106 |
| 2.64 Calibration curve of Ca. | 106 |
| 2.65 Correlation between the results obtained by the proposed method (FIA) and (a) the titrimetric method or (b) the calculation method. | 108 |
| E.1 Single line FIA system for determination of injection valve dead volume. | 120 |
| E.2 The plot for determination of injection value dead volume. | 121 |

ABBREVIATIONS AND SYMBOLS

| | |
|------|-------------------------|
| °C | degree Celsius |
| cm | centimeter |
| FIA | Flow injection analysis |
| g | gram |
| µg | microgram |
| mg | milligram |
| l | liter |
| ml | milliliter |
| mV | millivolt |
| min | minute |
| nm | nanometer |
| µm | micrometer |
| mm | millimeter |
| sec | second |
| No | number |
| h | hour |
| i.d. | inner diameter |
| φ | diameter |
| M | molarity |
| v/v | volume by volume |
| w/v | weight by volume |