## **CONTENTS**

|  | Page         |
|--|--------------|
| ACKNOWLEDGMENT                                 | iii          |
| ABSTRACT                                       | iv           |
| LIST OF TABLES                                 | $\mathbf{x}$ |
| LIST OF FIGURES                                | xiii         |
| ABREVIATIONS                                   | xvii         |
| CHAPTER 1 INTRODUCTION                         |              |
| 1.1 Uranium                                    | 1            |
| 1.1.1 General                                  | 1            |
| 1.1.2 Applications of uranium                  | 2            |
| 1.1.3 Determination of uranium                 | 3            |
| 1.2 Yttrium                                    | 7            |
| 1.2.1 General                                  | 7            |
| 1.2.2 Applications of yttrium                  | 9            |
| 1.2.3 Determination of yttrium                 | 10           |
| 1.3 Flow Injection Analysis                    | 15           |
| 1.4 Aims of the Thesis                         | 16           |
| CHAPTER 2 EXPERIMENTAL, RESULTS AND DISCUSSION |              |
| 2.1 Apparatus and Chemicals                    | 17           |
| 2.1.1 Apparatus                                | 17           |
| 2.1.2 Chemicals                                | 17           |

| 2.1.3 Stock solutions                                 | 18           |
|---|--------------|
| 2.2 Determination of Uranium by Flow Injection Fluori | metry 20     |
| 2.2.1 Preliminary study on fluorescence spectra       | of           |
| uranium in aqueous solution                           | 20           |
| 2.2.2 Preliminary study on fluorescence spectra       | of           |
| uranium in buffer solutions of pH 8                   | 23           |
| 2.2.2.1 Buffer solutions with phosphate               | e species 23 |
| 2.2.2.2 Other buffers                                 | 28           |
| 2.2.2.3 Summary                                       | 33           |
| 2.2.3 Preliminary study on fluorescence spectra       | a of         |
| uranium in phosphoric and sulfuric acid s             | solutions 34 |
| 2.2.3.1 The efect of pH of acid solution              | ns 37        |
| 2.2.3.2 Buffer solutions of pH 3-4                    | 38           |
| 2.2.4 Development of flow injection analysis sy       | ystems 43    |
| 2.2.4.1 Single line manifold                          | 43           |
| 2.2.4.2 Two line manifold                             | 56           |
| 2.3 Determination of Yttrium by Flow Injection Analy  | ysis 61      |
| 2.3.1 Molar absorptivity study                        | 61           |
| 2.3.2 FIA manifold design                             | 62           |
| 2.3.2.1 Three line manifold                           | 62           |
| 2.3.2.2 Two line manifold                             | 64           |
| 2.3.3 Resin for yttrium preconcentration              | 67           |
| 2.3.4 Optimisation                                    | 72           |

| 2.3.4.1 Conventional method                              | 72  |
|--|-----|
| 2.3.4.2 Simplex optimisation                             | 82  |
| 2.3.5 pH of sample                                       | 89  |
| 2.3.6 Effect of water washing time                       | 90  |
| 2.3.7 Calibration curve                                  | 91  |
| 2.3.8 Effect of preconcentration time                    | 93  |
| 2.3.9 Adsorption onto glass                              | 95  |
| 2.3.10 Interferences                                     | 97  |
| 2.3.11 Determination of yttrium in tin tailing leachates | 98  |
| CHAPTER 3 CONCLUSION                                     | 99  |
| REFERENCES   | 102 |
| APPENDIX A   | 107 |
| APPENDIX B   | 112 |
| APPENDIX C   | 115 |
| APPENDIX D   | 116 |

## LIST OF TABLES

| TABLE  |   | Page |
|--------|---|------|
| 1.1    | Some fluorimetric methods for the determination of uranium  | 6    |
| 1.2    | Review of yttrium determination by spectrophotometry  | 12   |
| 1.3    | FIA techniques for the determination of yttrium   | 14   |
| 2.2.1  | Emission intensity of uranium in aqueous media at pH 8  | 23   |
| 2.2.2  | Emission intensity of uranium in citric acid - Na <sub>2</sub> HPO <sub>4</sub>                             | 24   |
| 2.2.3  | Emission intensity of uranium in KH <sub>2</sub> PO <sub>4</sub> - NaOH                                     | 26   |
| 2.2.4  | Emission intensity of uranium in Na <sub>2</sub> HPO <sub>4</sub> - KH <sub>2</sub> PO <sub>4</sub>         | 28   |
| 2.2.5  | Emission intensity of uranium in NH <sub>4</sub> Cl - NH <sub>3</sub>                                       | 29   |
| 2.2.6  | Emission intensity of uranium in Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub>                              | 32   |
| 2.2.7  | Maximum excitation and emission wavelengths of uranyl ion at pH   | 833  |
| 2.2.8  | Fluorescence intensity of uranium in acid solutions   | 36   |
| 2.2.9  | Fluorescence of uranium in KH <sub>2</sub> PO <sub>4</sub> - Na <sub>2</sub> HPO <sub>4</sub> at various pH | 37   |
| 2.2.10 | Fluorescence of uranium in K <sub>2</sub> HPO <sub>4</sub> - H <sub>3</sub> PO <sub>4</sub>                 | 42   |
| 2.2.11 | Summary of maximum excitation and emission wavelengths of   |      |
|        | uranyl ion at pH 3.5.   | 42   |
| 2.2.12 | Emission intensity of uranium when using GG as an emission filter.  | 45   |
| 2.2.13 | Emission intensity of uranium when using PP as an emission filter   | 47   |
| 2.2.14 | Effect of carrier flow rates on peak height   | 48   |
| 2.2.15 | Effect of Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> concetrations on peak height                        | 49   |

| 2.2.16 | Effect of mixing coil lengths on peak height                            | 50 |
|--------|---|----|
| 2.2.17 | Effect of sample volumes on peak height                                 | 51 |
| 2.2.18 | Effect of initial pH on that of final solution                          | 53 |
| 2.2.19 | The emission efficiency of a normal glass filter compared               |    |
|        | with that of 4 PP filters   | 54 |
| 2.2.20 | Peak height obtained with uranium standard solutions from               |    |
|        | 1 to 5 mg/l   | 55 |
| 2.2.21 | Peak heights obtained from single and two line manifolds                | 57 |
| 2.2.22 | Effect of NaOH concentrations on peak height                            | 58 |
| 2.2.23 | Effect of K <sub>2</sub> HPO <sub>4</sub> concentrations on peak height | 59 |
| 2.3.1  | Peak height obtained for yttrium standard solution using                |    |
|        | a three line manifold   | 64 |
| 2.3.2  | Peak height obtained for yttrium standard solution using                |    |
|        | a two line manifold   | 66 |
| 2.3.3  | Peak height of yttrium standard solution 0.01 mg/l with                 |    |
|        | preconcentration time of 5 minutes from various types of resin          | 70 |
| 2.3.4  | Peak height of yttrium standard solution 0.05 mg/l with                 |    |
|        | preconcentration time of 3 minutes from various types of resin          | 70 |
| 2.3.5  | Effect of HCl concentrations on peak height                             | 72 |
| 2.3.6  | Effect of buffer concentrations on peak height                          | 73 |
| 2.3.7  | Effect of Arsenazo III concentrations on peak height                    | 74 |
| 2.3.8  | Effect of flow rates of eluent on peak height                           | 75 |
| 2.3.9  | Effect of flow rates of reagent on peak height                          | 76 |

| 2.3.10 | Effect of mixing coil 1 lengths on peak height                   | 77  |
|--------|--|-----|
| 2.3.11 | Effect of mixing coil 2 lengths on peak height.                  | 78  |
| 2.3.12 | Effect of loading flow rates on peak height                      | 79  |
| 2.3.13 | Effect of resin column lengths on peak height.                   | 80  |
| 2.3.14 | The initial vertices of simplex method for yttrium determination | 84  |
| 2.3.15 | All of vertices in simplex method for yttrium determination      | 86  |
| 2.3.16 | The comparison of FIA optimum conditions obtained                |     |
|        | between conventional and simplex methods                         | 88  |
| 2.3.17 | Effect of pH sample solutions on peak height                     | 90  |
| 2.3.18 | Effect of water washing times on peak height                     | 90  |
| 2.3.19 | The absorbance obtained from varying either yttrium standard     |     |
|        | solutions or preconcentration times.                             | 91  |
| 2.3.20 | Effect of preconcentration times on peak height                  | 94  |
| 2.3.21 | Effect of adsorbed ions onto glass surface                       | 96  |
| 2.3.22 | Summary of interferences   | 97  |
| 2.3.23 | Determination of yttrium in tin tailing leachates                | 98  |
| B.1    | Effect of interfering ions in flow injection analysis for        |     |
|        | yttrium determination  | 112 |

## LIST OF FIGURES

| FIGURE | Page   |
|--------|--|
| 1.1.1  | Some reactions of uranium. 2   |
| 1.2.1  | Some reactions of yttrium9   |
| 2.2.1  | Fluorescence spectra of uranyl ion in aqueous solution20   |
| 2.2.2  | Effect of pH on fluorescence spectra of uranyl solution  |
| 2.2.3  | Fluorescence spectra of uranium in aqueous media   |
| 2.2.4  | Calibration curve of uranium in aqueous media  |
| 2.2.5  | Excitation and fluorescence spectra of uranium in phosphate buffer23                                     |
| 2.2.6  | Fluorescence spectra of uranium in citric acid - Na <sub>2</sub> HPO <sub>4</sub>                        |
| 2.2.7  | Emission intensity of uranium in citric acid - Na <sub>2</sub> HPO <sub>4</sub>                          |
| 2.2.8  | Fluorescence spectra of uranium in KH <sub>2</sub> PO <sub>4</sub> NaOH25                                |
| 2.2.9  | Emission intensity of uranium in KH <sub>2</sub> PO <sub>4</sub> . NaOH26                                |
| 2.2.10 | Fluorescence spectra of uranium in Na <sub>2</sub> HPO <sub>4</sub> _ KH <sub>2</sub> PO <sub>4</sub> 27 |
| 2.2.11 | Emission intensity of uranium in Na <sub>2</sub> HPO <sub>4</sub> _ KH <sub>2</sub> PO <sub>4</sub>      |
| 2.2.12 | Fluorescence spectra of uranium in NH <sub>4</sub> Cl - NH <sub>3</sub>                                  |
| 2.2.13 | Emission intensity of uranium in NH <sub>4</sub> Cl - NH <sub>3</sub>                                    |
| 2.2.14 | Fluorescence spectrum of uranium in NH <sub>4</sub> NO <sub>3</sub> - NH <sub>3</sub>                    |
| 2.2.15 | Fluorescence spectrum of uranium in triethanolamine  |
| 2.2.16 | Fluorescence spectra of uranium in glycine - NaOH31  |
| 2.2.17 | Fluorescence spectra of uranium in Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub>                         |

| 2.2.18 | Emission intensity of uranium in Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> 32                      |     |
|--------|--|-----|
| 2.2.19 | Fluorescence spectra of uranium in H <sub>2</sub> SO <sub>4</sub> 34                                   |     |
| 2.2.20 | Fluorescence spectra of uranium in H <sub>3</sub> PO <sub>4</sub>                                      |     |
| 2.2.21 | Fluorescence spectra of uranium in H <sub>2</sub> SO <sub>4</sub> _H <sub>3</sub> PO <sub>4</sub> 35   |     |
| 2.2.22 | Calibration of uranium in acid solutions   |     |
| 2.2.23 | Fluorescence intensity of uranium at various pH values38   |     |
| 2.2.24 | Fluorescence spectrum of uranium in sodium acetate - acetic acid39                                     |     |
| 2.2.25 | Fluorescence spectrum of uranium in potassium hydrogen tartate39                                       |     |
| 2.2.26 | Fluorescence spectrum of uranium in sodium formate - formic acid40                                     |     |
| 2.2.27 | Fluorescence spectrum of uranium in glycine - HCl40  |     |
| 2.2.28 | Fluorescence spectra of uranium in KH <sub>2</sub> PO <sub>4</sub> - H <sub>3</sub> PO <sub>4</sub> 41 |     |
| 2.2.29 | Calibration for uranium in KH <sub>2</sub> PO <sub>4</sub> - H <sub>3</sub> PO <sub>4</sub> buffer     |     |
| 2.2.30 | Single line manifold for the fluorimetric determination of uranium44                                   |     |
| 2.2.31 | Calibration with GG emission filters46   | 5   |
| 2.2.32 | Calibration with PP emission filters47   | 7   |
| 2.2.33 | Effect of carrier flow rates on peak height4   | 7   |
| 2.2.34 | Effect of Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> concentrations on peak height                  | 8   |
| 2.2.35 | Effect of mixing coil lengths on peak height50   | 0   |
| 2.2.36 | Effect of sample volumes on peak height5   | 1   |
| 2.2.37 | Effect of initial pH on peak height5   | ; 3 |
| 2.2.38 | Calibrations using a normal glass filter compared with   |     |
|        | that of 4 PP filters5  | 4   |

| Response of uranium standard solutions from 1 to 5 mg/l                 | 55  |
|---|---|
| Two line manifold for the fluorimetric determination for uranium5       | 6   |
| Calibrations from single and two line manifolds                         | 7   |
| Effect of NaOH concentrations on peak height5                           | 8   |
| Effect of K <sub>2</sub> HPO <sub>4</sub> concentrations on peak height | 0   |
| Absorption spectra of yttrium - Arsenazo III complex                    | 51  |
| Three line FIA manifold   | 52  |
| Calibrations for yttrium standard solution with a three line manifold6  | 53  |
| Two line FIA manifold.  | 54  |
| Calibrations for yttrium standard solutions with a two line manifold    | 65  |
| FIA manifold for preconcentration study                                 | 68  |
| Peak heights obtained from various types of resin using yttrium         |   |
| standard 0.01 mg/l with preconcentration time 5 minutes                 | 69  |
| Peak heights obtained from various types of resin using yttrium         |   |
| standard 0.05 mg/l with preconcentration time 3 minutes                 | .71   |
| Effect of HCl concentrations on peak height.                            | .73   |
| Effect of buffer concentrations on peak height.                         | .74   |
| Effect of Arsenazo III concentrations on peak height                    | .75   |
| Effect of flow rates of eluent on peak height.                          | .76   |
| Effect of flow rates of reagent on peak height                          | .77   |
| Effect of mixing coil 1 lengths on peak height                          | .78   |
| Effect of mixing coil 2 lengths on peak height                          | .79   |
|   | Calibrations from single and two line manifolds |

| 2.3.16      | Effect of loading flow rates on peak height                   | 80   |
|-------------|---|------|
| 2.3.17      | Effect of resin column lengths on peak height                 | 81   |
| 2.3.18      | Effect of pH sample solutions on peak height.                 | 89   |
| 2.3.19      | Signals from yttrium standard solutions loaded for a          |      |
| ,           | preconcentration time of 6 minutes                            | 92   |
| 2.3.19      | Calibration for yttrium standard solutions loaded for a       |      |
|             | preconcentration time of 6 minutes                            | 92   |
| 2.3.20      | Calibration for yttrium standard solutions loaded for various |      |
|             | preconcentration times  | 93   |
| 2.3.21      | Effect of preconcentration time on peak height                | 95   |
| 2.3.22      | Effect of adsorbed ions onto glass surface.                   | 96   |
| <b>A</b> .1 | The simplex in two dimensions                                 | .108 |
| A.2         | The moving in normal progression of two dimension simplex     | 108  |
| A.3         | Failure of simplex on ridge                                   | 109  |
| A.4         | Progress of simplex on ridge                                  | 110  |

## **ABBREVIATIONS AND UNITS**

 $\lambda \qquad \quad wavelength$ 

λex excitation wavelength

λem emission wavelength

E molar absorptivity

V volt

mV millivolt

MeV mega electron volt

Fig. figure

M molarity

N normality

sens. sensitivity

ref. reference

v/v volume by volume

w/v weigth by volume