

TABLE OF CONTENTS

	Page
ACKNOWLEDGEMENT	iii
ABSTRACT (ENGLISH)	v
ABSTRACT (THAI)	viii
LIST OF TABLES	xv
LIST OF ILLUSTRATIONS	xvi
ABBREVIATIONS AND SYMBOLS	xxii
CHAPTER 1: INTRODUCTION	1
1.1 Introduction	1
1.2 Crystal structure of PZT	3
1.2.1 Piezoelectricity in ferroelectric ceramics	3
1.2.2 Perovskite structure	9
1.3 Dielectric properties of PZT	15
1.3.1 Relative permittivity	15
1.3.2 Impedance spectroscopy	16
1.4 Modified PZT	20
1.4.1 Phase diagram of the PZT-PLZT solid-solution system	22
1.5 Powder processing route	25
1.5.1 Solid state Reaction	25
1.5.1.1 One-stage solid-state reaction process	26
1.5.1.2 Two-stage solid-state reaction process	28
1.5.2 Chemical Synthesis	30
1.5.2.1 Coprecipitation from solution	30

	Page
1.5.2.2 Molten salt synthesis	33
1.5.2.3 Spray pyrolysis	33
1.5.2.4 Sol-gel	34
1.5.2.5 Emulsion synthesis	36
1.5.2.6 Hydrothermal synthesis	37
1.5.2.6.1 Formation mechanism for PZT powders synthesized from hydrothermal process	42
1.6 Shape forming of PZT and PLZT ceramics	50
1.5.1 Uniaxial pressing	51
1.5.2 Isostatic pressing	51
1.7 Literature review	53
1.8 Objective of this work	57
 CHAPTER 2: EXPERIMENTAL	 58
2.1 Chemicals	60
2.2 Apparatus and instruments	61
2.3 Experimental procedure	62
2.3.1 Preparation of PZT powders	62
2.3.2 Preparation of PLZT powders	64
2.4 Powders characterization	65
2.4.1 Thermal Analysis (TG-DTA)	65
2.4.2 X-ray Diffraction (XRD)	66

	Page
2.4.3 Scanning Electron Microscopy (SEM)	66
2.5 Ceramics characterization	67
2.5.1 Ceramics preparation	67
2.5.2 X-ray Diffraction (XRD)	67
2.5.3 Scanning Electron Microscopy (SEM)	67
2.5.4 Measurement of shrinkage	68
2.5.5 Measurement of density	68
2.5.6 Measurement of dielectric constant	69
2.5.7 Measurement of impedance spectroscopy	70
CHAPTER 3: RESULTS AND DISCUSSION	71
3.1 Powders characterization	71
3.1.1 Investigation of thermal decomposition	71
3.1.1.1 PZT powders from hydrothermal process	71
3.1.2 Crystalline structure determination	73
3.1.2.1 PZT powders from hydrothermal process	73
3.1.2.1.1 Effect of mineralizer concentration	73
3.1.2.1.2 Effect of pH value	74
3.1.2.1.3 Effect of synthesis time	75
3.1.2.2 PLZT powders from hydrothermal process	77
3.1.3 Microstructure analysis	79
3.1.3.1 PZT powders from hydrothermal process	79
3.1.3.1.1 Effect of mineralizer concentration	79

	Page
3.1.3.1.2 Effect of pH value	81
3.1.3.1.3 Effect of synthesis time	82
3.1.3.2 PLZT powders from hydrothermal process	84
3.2 Ceramics characterization	85
3.2.1 Densification of PZT ceramics	85
3.2.2 XRD patterns of PZT and PLZT ceramics	89
3.2.3 Microstructure of PZT and PLZT ceramics	92
3.2.5 Dielectric Properties	95
3.2.4.1 Impedance spectra of PZT and PLZT ceramics	95
CHAPTER 4: CONCLUSIONS	107
4.1 Conclusions	105
4.2 Suggestions for future work	108
REFERENCES	111
VITA	126

LIST OF TABLES

Table		page
1.1	Typical additives for PZT and their major effects on piezoelectric properties	17
1.2	The comparison of powders synthesis route	39
3.1	Trace impurities in the PZT powders	112
3.2	Lead to zirconium to titanium ratio in PZT powders	113
3.3	The measured density, % theoretical density, % porosity and % linear shrinkage of PZT powders obtained from nitrate solutions and hydrothermal process	115

LIST OF ILLUSTRATIONS

Figure	Page
1.1 Interrelationship of piezoelectric and subgroups on the basis of symmetry	5
1.2 Schematic illustration of the poling process	7
1.3 Direct and indirect piezoelectric effect	8
1.4 Basic structural unit of perovskite PZT	9
1.5 Octahedral framework with an A atom lie at the center of the unit cell	10
1.6 Phase diagram of the PbTiO_3 - PbZrO_3 solid solution	12
1.7 Dielectric and piezoelectric properties of the PbTiO_3 - PbZrO_3 solid solution	12
1.8 Lattice parameter change at room temperature for the PbTiO_3 - PbZrO_3 solid solution	13
1.9 A portion of the PbTiO_3 - PbZrO_3 phase diagram	14
1.10 Equivalent circuit of a piezoelectric element (non-resonance operation)	15
1.11 The general principles of impedance spectroscopy	17
1.12 Typical impedance diagram	19
1.13 Phase diagram of $\text{Pb}_{1-3y/2}\text{La}_y(\text{Ti}_{1-z}\text{Zr}_z)\text{O}_3$	23
1.14 Phase diagram of $\text{Pb}_{1-3y/2}\text{La}_y(\text{Ti}_{1-z}\text{Zr}_z)\text{O}_3$	24
1.15 Four regions of solid-state reaction appear as the calcination temperature increases	27
1.16 Schematic representation of the perovskite PZT powder formation process via two-stage solid-state reaction and associated morphological change	29

Figure	Page
1.17 Flow diagram for preparing PLZT nitrate solutions	32
1.18 The overall sol-gel process	35
1.19 Flow chart of emulsion process	36
1.20 Flow chart of hydrothermal synthesis	38
1.21 Schematic representation of the perovskite PZT particle formation process	47
1.22 Four steps involved in typical powder processing for advanced ceramics	50
1.23 Isostatic pressing	52
2.1 Schematic diagram for the preparation of PZT powders by hydrothermal process	63
3.1 Thermogravimetric and differential thermal analysis of PZT powders synthesized by hydrothermal process	72
3.2 Thermogravimetric and differential thermal analysis of PLZT powders synthesized by hydrothermal process	72
3.3 XRD patterns of PZT powders synthesized by hydrothermal process at different KOH concentrations	73
3.4 XRD patterns of PZT powders synthesized by hydrothermal process using 4.0 M KOH as a mineralizer at different pH values	75
3.5 XRD patterns of PZT powders synthesized by hydrothermal process using 4.0 M KOH as a mineralizer at different synthesis times	76
3.6 XRD patterns of PLZT powders synthesized by hydrothermal process using 4.0 M KOH as a mineralizer at different %La	77

Figure	Page
3.7 SEM micrographs of PZT powders obtained from hydrothermal process at 200 °C for 6 hours using KOH as a mineralizer at different concentrations	79
3.8 SEM micrographs of PZT powders obtained from hydrothermal process at 200 °C for 6 hours using 4.0 M KOH as a mineralizer at different pH values	81
3.9 SEM micrographs of PZT powders obtained from hydrothermal process using 4.0 M KOH as a mineralizer at different synthesis temperatures and synthesis times	83
3.10 SEM micrograph of PLZT powders obtained from hydrothermal process at 200 °C for 6 hours using 4.0 M KOH as a mineralizer	84
3.11 % Theoretical density versus sintering temperature curves at sintering time of 3 and 5 hours for both nitrate solutions and hydrothermal process	87
3.12 % Linear shrinkage versus sintering temperature at sintering time of 3 and 5 hours for nitrate solutions and hydrothermal process	88
3.13 XRD patterns of sintered PZT ceramics obtained from hydrothermal process for 5 hours at different sintering temperatures between 1000 °C to 1250 °C	89
3.14 Fine structure in XRD pattern of PZT ceramics obtained from hydrothermal process sinter at 1250 °C at 2θ from 43 to 47 degrees	90
3.15 XRD patterns of PLZT ceramics sintered at 1300 °C for 3 h prepared from powders with different reaction times	91

Figure	Page
3.16 SEM micrographs of PZT from hydrothermal process sintered for 5 hours at 1150 °C to 1250 °C	93
3.17 SEM micrographs of PLZT ceramics obtained from hydrothermal process sintered for 5 hours at 1100°C to 1300 °C	94
3.18 The complex impedance plot of PZT measured at 350 to 650 °C with increasing 50 °C by step.	96
3.19 The complex impedance plot of PLZT measured at 400 to 650 °C with increasing 50 °C by step.	97
3.20 (a) A complex impedance plot of PLZT at 400 °C (b) The simulated curve fitted to an equivalent to simple parallel circuit.	98
3.21 Arrhenius plot for R_G and R_{GB} in PLZT ceramic.	99
3.22 The variation of the real part of impedance (Z') of PLZT ceramic with frequency at different temperatures	100
3.23 The variation of the imaginary part of impedance (Z'') of PLZT ceramic with frequency at different temperatures.	101
3.24 The a.c conductivity plots of PLZT ceramics as function of frequency at different measured time.	102
3.25 The a.c conductivity plots of PZT ceramics as a function of frequency at different measuring time.	104
3.26 Arrhenius plot of PZT ceramic, as a function of frequency at different measuring temperature	104

R

ABBREVIATIONS AND SYMBOLS

A	Area of disc face
A _T	Antiferroelectric tetragonal Phase
A _O	Antiferroelectric octahedral phase
AC	Alternating current
AFE	Antiferroelectric
AFE _{ortho}	Antiferroelectric and orthorhombic phase
D	Thickness
DTA	Differential Thermal Analysis
ε _r	Relative permittivity or dielectric constant
FE	Ferroelectric
FE _{tet} (F _T)	Ferroelectric and tetragonal phase
FE _{rhom} (F _R)	Ferroelectric and rhombohedral phase
FRA	Frequency response analyzer
HP	Hydrothermal Process
JCPDS	Joint Committee for Powder Diffraction Standards
K _p	Electromechanical Coupling Coefficient
MPB	Morphotropic Phase Boundary
P _c	Paraelectric cubic Phase
PE	Paraelectric
PLZT	Lead Lanthanum Zirconate Titanate
PMN	Lead Magnesium Niobate

PT	Lead Titanate
PZ	Lead Zirconate
PZT	Lead Zirconate Titanate
Q_m	Resonance Frequency
S_d	Linear shrinkage
SEM	Scanning Electron Microscope
T_c	Curie Temperature
TEM	Transmission Electron Microscope
TGA	Thermogravimetric Analysis
XRD	X-ray Diffraction
$\tan \delta$	Dielectric loss factor
ω	Angular frequency
ϕ	Phase angle

ลิขสิทธิ์มหาวิทยาลัยเชียงใหม่
Copyright© by Chiang Mai University
All rights reserved