

TABLE OF CONTENTS

	Page
Acknowledgements	iii
Abstract in Thai	iv
Abstract in English	vi
List of illustrations	x
Chapter 1 Introduction	1
Chapter 2 Preliminaries	3
2.1 Stability.	3
2.1.1 Definition.	3
2.1.2 Algebraic Criteria for Linear Systems.	4
2.1.3 Lyapunov Theory.	5
2.1.4 Application of Lyapunov Theory to Linear Systems.	6
2.2 Routh-Hurwitz Theorem.	6
2.3 Fourth-Order Runge-Kutta Method.	8
2.4 Matrix Types.	8
2.4.1 Symmetry Matrix.	8
2.4.2 Positive Definite Matrix.	8
2.4.3 Positive Semidefinite Matrix.	9
2.4.4 Negative Definite Matrix.	9
2.4.5 Negative Semidefinite Matrix.	9
2.5 Synchronization.	9
2.6 Terminology.	11

Chapter 3 Main results	12
3.1 Chua's Cirruit System.	12
3.1.1 Numerical Simulations.	13
3.2 The Perturbed Chua's Cirruit System.	15
3.2.1 Numerical Simulations.	19
3.3 Controlling Chaos of Perturbed Chua's Cirruit System to	
3.3.1 Feedback Control Method.	21
3.3.2 Adaptive Control Method.	25
3.4 Synchronization of Perturbed Chua's Cirruit system.	31
3.4.1 Synchronization of Perturbed Chua's Cirruit System	
Using Active Control.	31
3.4.2 Adaptive Synchronization of Perturbed Chua's Cirruit	
System	37
Chapter 4 Conclusion	43
Bibliography	46
Vita	47

LIST OF ILLUSTRATIONS

Figure	Page
3.1	The chaotic attractor of Chua's circuit system in the xy -plane.
	14
3.2	The chaotic attractor of Chua's circuit system in the xz -plane.
	14
3.3	The chaotic attractor of Chua's circuit system in the yz -plane.
	14
3.4	The chaotic attractor of perturbed Chua's circuit system in the xy -plane.
	19
3.5	The chaotic attractor of perturbed Chua's circuit system in the xz -plane.
	20
3.6	The chaotic attractor of perturbed Chua's circuit system in the yz -plane.
	20
3.7	The stabilization of the equilibrium point E_0 of the system (3.2). The control law $u_1 = -11.4x$, $u_2 = -0.1y$, $u_3 = -0.55z$ is activated at $t = 10$
	24
3.8	The stabilization of the equilibrium point E_1 of the system (3.2). The control law $u_1 = -8.75(x - 0.71573)$, $u_2 = -0.1(y - 0.00251)$, $u_3 = -0.55(z + 0.71322)$ is activated at $t = 10$
	24
3.9	The stabilization of the equilibrium point E_2 of the system (3.2). The control law $u_1 = -8.75(x + 0.69858)$, $u_2 = -0.1(y - 0.00239)$, $u_3 = -0.55(z + 0.70098)$ is activated at $t = 10$
	25
3.10	The time response of the states x , y and z of the controlled system (3.16), where $\bar{x} = 0$, $\bar{y} = 0$ and $\bar{z} = 0$
	29

3.11	The time response of the states x, y and z of the controlled system (3.16), where $\bar{x} = 0.71573$, $\bar{y} = 0.00251$ and $\bar{z} = -0.71322$. . .	29
3.12	The time response of the states x, y and z of the controlled system (3.16), where $\bar{x} = -0.69858$, $\bar{y} = 0.00239$ and $\bar{z} = 0.70098$. . .	30
3.13	Changing of parameter g of the adaptive control.	30
3.14	Changing of parameter k of the adaptive control.	30
3.15	The states x_1, x_2 of the coupled perturbed Chua's circuit system of equations with the active control deactivated.	34
3.16	The states y_1, y_2 of the coupled perturbed Chua's circuit system of equations with the active control deactivated.	34
3.17	The states z_1, z_2 of the coupled perturbed Chua's circuit system of equations with the active control deactivated.	35
3.18	The states x_1, x_2 of the coupled perturbed Chua's circuit system of equations with the active control activated.	35
3.19	The states y_1, y_2 of the coupled perturbed Chua's circuit system of equations with the active control activated.	36
3.20	The states z_1, z_2 of the coupled perturbed Chua's circuit system of equations with the active control activated.	36
3.21	The states error (e_x, e_y, e_z) of perturbed Chua's circuit system of equations with the active control activated	37
3.22	Synchronization error (e_x, e_y, e_z) states for system (3.27) and (3.28) with time t	41
3.23	Changing parameter p_1 of system (3.28) with time t	41
3.24	Changing parameter q_1 of system (3.28) with time t	42
3.25	Changing parameter r_1 of system (3.28) with time t	42