

TABLE OF CONTENTS

	Page
ACKNOWLEDGEMENT	iii
ABSTRACT (ENGLISH)	iv
ABSTRACT (THAI)	vi
LIST OF TABLES	xii
LIST OF FIGURES	xiv
ABBREVIATIONS AND SYMBOLS	xxv
CHAPTER 1 INTRODUCTION	1
1.1 Biodegradable polymers	1
1.2 Absorbable surgical sutures	3
1.3 Property requirements for an ideal absorbable suture	4
1.4 Molecular design considerations	4
1.4.1 Main chain chemical structure	5
1.4.2 Molecular architecture	6
1.4.3 Copolymer composition and monomer sequence distribution	7
1.4.4 Molecular weight and its distribution	9
1.4.5 Morphology and crystallinity	11
1.5 Historical development of synthetic absorbable sutures	17
1.6 Mechanism of suture absorption	19
1.7 Aims of this study	21
CHAPTER 2 SYNTHESIS AND CHARACTERIZATION OF THE RANDOM AND BLOCK TERPOLYMERS	24
2.1 Introduction	24
2.2 Chemical and instruments	25
2.2.1 Chemicals	25

2.2.2	Instruments	26
2.3	Monomer preparation and purification	27
2.3.1	Synthesis of L-lactide and purification	27
2.3.2	Synthesis of glycolide and purification	30
2.3.3	Purification of ϵ -caprolactone by fractional vacuum distillation	32
2.3.4	Purification of diethylene glycol by fractional vacuum distillation	32
2.4	Terpolymer synthesis	33
2.4.1	Random terpolymer synthesis	33
2.4.2	Block terpolymer synthesis	33
2.5	Instrumental methods for polymer characterization	34
2.5.1	Gel permeation chromatography (GPC)	35
2.5.2	Dilute-solution viscometry	36
2.5.3	Infrared spectroscopy (IR)	39
2.5.4	Nuclear magnetic resonance spectrometry (NMR)	40
2.5.5	Differential scanning calorimetry (DSC)	42
2.5.6	Thermogravimetry (TG)	44
2.6	Polymer characterization	45
2.6.1	Average molecular weight determination	45
2.6.2	Intrinsic viscosity determination	47
2.6.3	Structural characterization	50
2.6.4	Identification and monomer composition determination	54
2.6.5	Monomer sequences of terpolymers	58
2.6.6	Thermal transition analysis	71
2.6.7	Thermal stability analysis	75

CHAPTER 3 FIBRE PROCESSING AND MECHANICAL

PROPERTIES OF POLYMERS	79
3.1 Introduction	79
3.2 Fibre processing	80

3.2.1 Melting-spinning	81
3.2.2 Hot-drawing	84
3.2.3 Annealing	86
3.3 Mechanical properties	87
3.4 Effect of external factors on mechanical behavior	94
3.4.1 Influence of strain rate	95
3.4.2 Influence of temperature	96
3.5 Experiment of fibre production	101
3.5.1 As-spun fibre preparation	101
3.5.2 Off-line hot-drawing and annealing	108

**CHAPTER 4 MORPHOLOGY DEVELOPMENT OF
CRYSTALLIZABLE TERPOLYMERS OF
L-LACTIDE, ϵ -CAPROLACTONE AND GLYCOLIDE** 111

4.1 Introduction	111
4.2 Instrumental methods for structural characterization	112
4.2.1 X-ray scattering techniques	112
4.2.1.1 Wide-angle X-ray scattering (WAXS)	113
4.2.1.2 Small-angle X-ray scattering (SAXS)	123
4.2.2 Microscopy	125
4.2.2.1 Optical microscopy (OM)	125
4.2.2.2 Scanning electron microscopy (SEM)	127
4.3 Polymer crystallization	128
4.3.1 Crystallization from a quiescent melt	128
4.3.2 Rate of crystallization and fraction of crystallinity	130
4.3.3 Morphology development	137
4.4 Structure of fibres	143
4.4.1 Structure of hot-drawn fibres with annealing	143
4.4.2 Structure of hot-drawn fibres without annealing	152
4.4.3 Structure of undrawn fibres	159
4.5 Discussion	160

CHAPTER 5 FIBRE STRUCTURE-PROPERTY-PROCESSING	
RELATIONSHIPS	163
5.1 Introduction	163
5.2 Thermal property analysis by DSC	164
5.3 WAXD analysis of fibres	169
5.3.1 Azimuthal intensity distribution analysis	174
5.3.2 Orientation parameter calculation	177
5.3.3 Fraction of oriented crystalline	178
5.4 SAXS analysis of fibres	185
5.5 Surface analysis by SEM	189
5.6 Tensile properties	190
5.7 Discussion	196
CHAPTER 6 MAIN CONCLUSIONS	204
6.1 Molecular design and polymer products	204
6.2 Fibre characterization	206
6.3 Morphology development	207
SUGGESTIONS FOR FURTHER WORK	210
REFERENCES	211
APPENDICES	221
APPENDIX A Theory of purity analysis	222
APPENDIX B Supporting papers	225
VITA	268

LIST OF TABLES

Table	Page
1.1 Medical applications for synthetic biodegradable polymers	2
1.2 Effect of crystallinity on physical appearance	17
1.3 The chemical structures of some commercial synthetic absorbable sutures	18
2.1 Chemicals used in this research project	25
2.2 Instruments used in this research project	26
2.3 Definitions of dilute-solution viscosity terms	37
2.4 Vibrational peak assignments and frequencies in the homopolymer and terpolymer products infrared spectra	53
2.5 Peak assignments and corresponding chemical shifts in ¹ H-NMR spectra of the random and block terpolymers	55
2.6 Peak assignments and peak area integrations in ¹ H-NMR spectra for the random and block terpolymers	57
2.7 Chemical shifts, peak intensities and monomer sequences in the ¹ H-NMR spectra of the random and block terpolymers	61
2.8 Peak assignments and corresponding chemical shifts in ¹³ C-NMR spectra of the random and block terpolymers	63
2.9 Chemical shifts along with their intensities of the terpolymer sequences in the ¹³ C-NMR spectra of random and block terpolymers in the carbonyl atom regions	65
2.10 The sequence distribution of the random and block terpolymers	69
2.11 DSC transition temperatures and heats of melting of the homopolymers and terpolymers	74
2.12 TG thermal degradation range for the homopolymers and terpolymer products	78

Table	Page
3.1 The processing conditions used for melt spinning of poly(L-lactide), random and block terpolymers	106
3.2 Average draw ratio and draw rate for off-line hot-drawing at various temperatures	109
3.3 Drawing and annealing conditions for post-spinning treatment of poly(L-lactide) , random and block terpolymer fibres	110
4.1 Rate of crystallization of the random and block terpolymers at various temperatures and final fraction of crystallinity.	135
5.1 DSC thermal transitions, heats of crystallization and melting for the random terpolymer fibres processed under different conditions	168
5.2 DSC thermal transitions, heats of crystallization and melting for the block terpolymer fibres processed under different conditions	168
5.3 Peak width and peak positions of the scattering intensity profiles in the equatorial and meridional sections of the random terpolymer fibres shown in Fig. 5.5(b)	173
5.4 Peak width and peak positions of the scattering intensity profiles in the equatorial and meridional sections of the block terpolymer fibres shown in Fig. 5.6(b)	173
5.5 List of orientation parameter and fraction of oriented crystalline in the random and block terpolymer fibres	184
5.6 Long period of lamellar stacks calculated from the peak position along the meridional scan of SAXS patterns in Fig. 5.14(b) and 5.15(b)	188
5.7 Tensile properties of PDSII, as-spun and fibres of the random and block terpolymers drawn under various conditions	195
5.8 Summary of all results from combination techniques for as-spun and hot-drawn fibres under various drawn conditions	200

LIST OF FIGURES

Figure		Page
1.1	The physical form of a braided multifilament and a monofilament suture	4
1.2	Schematic representation of (a) linear (b) branched and (c) cross-linked or network polymers	7
1.3	Homopolymer and different types of copolymers. Unit A : o and Unit B : •	8
1.4	Molar mass dependence of the equilibrium melting point of oligo- and polyethylene	10
1.5	The relationship of polymer properties to molecular weight	10
1.6	Fringed-micelle model of the crystalline-amorphous structure of polymer	12
1.7	Single crystals of polyethylene	13
1.8	Schematic representation of flat lamellae of polymer single crystals	13
1.9	Schematics illustrations of possible chain morphology in a single polymer chain. L_c = Thickness of crystalline lamellae; L_a = Thickness of amorphous cover layers; d = X-ray long periodicity (a) Regular lamellae with sharp folds and crystal defects by chain ends and dislocations (b) Loose fold with adjacent re-entry (c) Switchboard model with random re-entry of chains	13
1.10	Schematic representation of folded chain lamellae tied together by interlamellar amorphous chains	14
1.11	Spherulites growing in poly(ethylene oxide) from the melt	15
1.12	Fully-developed spherulite grown from the melt, comprising chain folded lamellae (magnified section). Most rapid growth occurs in the direction of the spherulite radius R	15

Figure	Page
1.13 Schematic model of Shish-kebab morphology	16
1.14 The various physical and chemical processes involved in suture absorption	21
2.1 Apparatus used in the two-stage preparation of L-lactide : (a) L-lactide acid polycondensation to low molecular weight PLLA (b) Thermal decomposition of low molecular weight PLLA to L-lactide	28
2.2 DSC curve of purified L-lactide	29
2.3 Van't Hoff plot of the purity analysis data for the purified L-lactide (F = mole fraction of sample which has melted)	29
2.4 DSC curve of purified glycolide	31
2.5 Van't Hoff plot of the purity analysis data for the purified glycolide (F = mole fraction of sample which has melted)	31
2.6 Vacuum distillation apparatus used for the purification of ϵ -caprolactone	32
2.7 Illustration of the separation of polymer molecules of different sizes in size-exclusion chromatography	36
2.8 Diagrams of (a) an Ostwald U-tube viscometer, (b) a Ubbelohde suspended-level viscometer, and (c) a modified Ubbelohde viscometer with a large reservoir bulb for dilutions	37
2.9 The position of different infrared absorption bands used in the analysis of polymers	40
2.10 Approximate chemical shifts for protons in various functional groups relative to TMS	41
2.11 Approximate chemical shifts for ^{13}C -NMR in various functional groups relative to TMS	42
2.12 DSC thermogram of polymer	43
2.13 A typical non-isothermal TG thermogram for a polymer	45

Figure	Page
2.14 GPC curve of the random terpolymer	46
2.15 GPC curve of the block terpolymer	47
2.16 Reduced and inherent viscosity-concentration plots for the random terpolymer in chloroform as solvent at 30°C	48
2.17 Reduced and inherent viscosity-concentration plots for the prepolymer, P(LL-co-CL), in chloroform as solvent at 30°C	49
2.18 Reduced and inherent viscosity-concentration plots for the block terpolymer in chloroform as solvent at 30°C	49
2.19 Reference infrared spectrum of poly(L-lactide)	50
2.20 Reference infrared spectrum of poly(ε-caprolactone)	51
2.21 Reference infrared spectrum of poly(glycolide)	51
2.22 Infrared spectrum of the random terpolymer	52
2.23 Infrared spectrum of the block terpolymer	52
2.24 250 MHz ¹ H-NMR spectrum of the random terpolymer	54
2.25 250 MHz ¹ H-NMR spectrum of the block terpolymer	55
2.26 The expanded ¹ H-NMR spectrum of the random terpolymer in the range of 5.3 - 4.0 ppm	56
2.27 The expanded ¹ H-NMR spectrum of the block terpolymer in the range of 5.3 - 4.0 ppm	57
2.28 ¹ H-NMR spectra of the random terpolymer	60
2.29 ¹ H-NMR spectra of the block terpolymer	60
2.30 100 MHz ¹³ C-NMR spectrum of the random terpolymer in CDCl ₃ as solvent at 294 K	62
2.31 100 MHz ¹³ C-NMR spectrum of the block terpolymer in CDCl ₃ as solvent at 294K	62
2.32 Expanded carbonyl region of the ¹³ C-NMR spectrum of the random terpolymer	64
2.33 Expanded carbonyl region of the ¹³ C-NMR spectrum of the block terpolymer	65
2.34 DSC thermogram of poly(L-lactide)	71
2.35 DSC thermogram of poly(ε-caprolactone)	72

Figure	Page
2.36 DSC thermogram of poly(glycolide)	72
2.37 DSC thermogram of the random terpolymer	73
2.38 DSC thermogram of the block terpolymer	73
2.39 TG thermogram of poly(L-lactide)	76
2.40 TG thermogram of poly(ϵ -caprolactone)	76
2.41 TG thermogram of poly(glycolide)	77
2.42 TG thermogram of the random terpolymer	77
2.43 TG thermogram of the block terpolymer	78
3.1 Schematic representation of melt spinning system	82
3.2 Some cross-sections of holes in spinnerettes (left) and resulting cross-sections of fibres (right)	83
3.3 Schematic representation of molecular and crystal orientation in (a) as-spun (b) annealed and (c) drawn fibre.	84
3.4 Schematic diagram of a drawing process	85
3.5 Schematic representation of crystallization in fibre under annealing process	87
3.6 (a) Schematic illustration of how a tensile load produces an elongation and positive linear strain. Dashed lines represent the shape before deformation; solid lines, after deformation. (b) Schematic illustration of how a compressive load produces contraction and a negative linear strain (c) Schematic representation of shear strain, γ where $\gamma = \tan\theta$	88
3.7 A typical stress-strain curve for solid amorphous or semi-crystalline polymers	89
3.8 Schematic stress-strain diagrams showing (a) linear elastic deformation for loading and unloading cycles and (b) non-linear elastic behavior and how secant and tangent moduli are determined	91
3.9 Deformation occurred by (a) bending and stretching of interatomic bond (b) straightening out of a coiled portion in a molecular chain (c) intermolecular slippage	92

Figure	Page
3.10 Typical stress-strain curves	93
3.11 Schematic representations of tensile stress-strain behavior for brittle and ductile materials loaded to fracture	94
3.12 Typical tensile behavior of unplasticized PVC	95
3.13 Load-extension curves for a typical polymer sample tested at four different temperatures, increasing from (a) to (d), showing different types of mechanical behaviour (a) brittle fracture (b) ductile failure (c) necking and cold-drawing and (d) homogeneous deformation (quasi-rubber-like behaviour)	97
3.14 Effect of temperature on tensile stress-strain curves of cellulose acetate	97
3.15 Schematic represent of the stress-strain behavior of a semi-crystalline polymer. The shape of tensile specimens at several stages is indicated	99
3.16 Illustration of the change in spherulite morphology during cold-drawing corresponding to Fig. 3.15	100
3.17 Steps in deformation of semi-crystalline polymers	101
3.18 Illustration of the small-scale melt spinning apparatus	102
3.19 Photograph of the various accessories used in the small-scale melt spinning apparatus	103
3.20 The assembled extrusion cylinder ready for melt spinning	104
3.21 Schematic diagram of the compression, melting and metering zones showing the (a) piston (b) cylinder (c) band heater (d) heating block (e) stainless steel filter mesh (f) thermocouple (g) spinnerette and (h) extruded monofilament fibre	104
4.1 Diffraction of scattering radiation from a series of parallel planes of atoms	113
4.2 Schematic arrangements in wide-angle X-ray diffractometers and cameras	115
4.3 An X-ray diffraction pattern obtained from an isotropic, semi-crystalline polymer of poly(3-hydroxybutyrate)	115

Figure	Page
4.4 An X-ray diffraction pattern obtained from a highly stretch poly(α,α' -dimethylpropiolactone) fibre	116
4.5 X-ray diffractometer scan of unoriented cotton cellulose showing separation into crystalline and amorphous contribution	116
4.6 Anisotropic units with a preferred orientation about an extension axis	117
4.7 A section through a polar probability plot of a uniaxial orientation distribution	118
4.8 The orientation distribution function, $D(\alpha)$, which represents the level of preferred orientation in Fig.4.6 and 4.7	118
4.9 Typical SAXS patterns from fibres. (a) two point pattern and (b) four-point pattern	124
4.10 Arrangement of the crystals and amorphous regions	124
4.11 (a) A schematic plot of a SAXS pattern with a meridional slice passing through the peak positions	115
(b) A curve fitting profile to the intensity scan along a meridional slice as indicated by an arrow in (a)	125
4.12 Schematic representation of incident-light-polarizing microscope	126
4.13 Schematic diagram of part of the electron optical column of an SEM	128
4.14 Illustration of the geometry of the 3-circle X-ray diffractometer used in this experiment	129
4.15 Plots of the experimental wide-angle X-ray scattering intensity $I(Q)$ recorded for samples of poly(L-lactide), the random and block terpolymers crystallized from a quiescent melt	130
4.16 (a) X-ray scattering intensity variation at $ Q = 1.18 \text{ \AA}^{-1}$ as a function of time of the random terpolymer heated at 50°C	119
(b) fraction of crystallinity as a function of time calculated from (a) (see text); its slope at the inflection point indicates the rate of crystallization.	133

Figure	Page
4.17 Curve fitting to separate crystalline and amorphous scattering intensities for the random terpolymer completely crystallized at 50°C (see text)	134
4.18 (a) A plot of the rate of crystallization as a function of the isothermal crystallization temperature for the random terpolymer (▲, dashed-line) and the block terpolymer (●, full line) (b) a plot of the final fraction of crystallinity in samples of the random terpolymer (▲, dashed-line) and the block terpolymer (●, full line) as a function of the isothermal crystallization temperature.	136
4.19 Polarizing optical micrographs of thin films at room temperature after crystallization at (a) 130°C, poly(L-lactide); (b) 110°C random terpolymer and (c) 120°C block terpolymer showing well defined spherulites which for (b) and (c) are strongly banded.	138
4.20 Polarizing optical micrographs of poly(L-lactide) crystallizing at 130°C at different times from the melt	139
4.21 Polarizing optical micrographs of the random terpolymer crystallizing at 110°C at different times from the melt	140
4.22 Polarizing optical micrographs of the block terpolymer crystallizing at 120°C at different times from the melt	141
4.23 Plots of radius of growing spherulites as a function of time for thin films of the random (at 110°C) and block (at 120°C) terpolymers after quenching from the melt	142
4.24 A plot of the radial growth of spherulites against the molecular weight (M_n) for ▲ random terpolymer, ● block terpolymer and △ poly(L-lactide) prepared in this work together with data for poly(L-lactide) taken from Ref [104] (○) and Ref [105] (□). The growth rates were measured at a constant degree of under cooling of ~ 40°C. The line represents a fit to the poly(L-lactide) data on the basis of a simple power law relationship between growth rate and molecular weight.	142
4.25 Specimen for scattering measurement	144

Figure	Page	
4.26	X-ray scattering intensity maps $I(Q, \alpha)$ for the annealed fibres of (a) poly(L-lactide), (b) random terpolymer and (c) block terpolymer. In each case the fibre axis is vertical. The grey scale representation is arranged to that white represents the highest intensity. Note that the grey scale has been truncated to allow the details within the pattern to be observed. The relative strength of the strong equatorial feature at $ Q \sim 1.2 \text{ \AA}^{-1}$ can be judged from the equatorial section. The accompanying line plots show the equatorial ($\alpha=0^\circ$, full line) and the meridional section ($\alpha=90^\circ$, broken line)	147
4.27	Cross-sections of the intensity maps shown in Fig. 4.26 taken at constant Z values corresponding to the layer line number indicated in the figures ; (a) poly(L-lactide) (b) random terpolymer (c) block terpolymer	148
4.28	Small-angle X-ray scattering patterns recorded for as-spun fibres of (a) the random and (b) block terpolymers	150
4.29	Small-angle X-ray scattering patterns recorded for the same annealed fibres as in Fig. 4.26 i.e. (a) annealed random terpolymer and (b) annealed block terpolymer. In each case the fibre axis is vertical. The dark square in the centre is the shadow of the beam stop. In Fig. 4.29(b), the scattering is much weaker than in Fig. 4.29(a) and some scattering from the collimation system can be seen around the beam stop in the form of short spikes.	150
4.30	X-ray scattering intensity maps $I(Q, \alpha)$ for the unannealed fibres of (a) random and (b) block terpolymers. In each case the fibre axis is vertical. The grey scale representation is arranged to that white represents the highest intensity. Note that the grey scale has been truncated to allow the details within the pattern to be observed. The relative strength of the strong equatorial feature at $ Q \sim 1.2 \text{ \AA}^{-1}$ can be judged from the equatorial section. The accompanying line plots show the equatorial ($\alpha=0^\circ$, full line) and	

Figure	Page
	156
4.31	157
4.32	158
4.33	159
5.1	166
5.2	166
5.3	167
5.4	167
5.5	171
5.6	171

Figure	Page
profiles in equatorial and meridional sections of the block terpolymer fibres at various conditions of processing which corresponding to (a)	172
5.7 Azimuthal profiles of as-spun and drawn fibres of the random terpolymer at Q corresponding to the equatorial peak shown in Fig. 5.5	175
5.8 Azimuthal profiles of as-spun and drawn fibres of the block terpolymer at Q corresponding to the equatorial peak shown in Fig. 5.6	176
5.9 Plot of azimuthal peak width against draw ratio for the random and block terpolymer fibres	176
5.10 Profiles of the first five spherical harmonic components calculated from the scattering data of each pattern of the random terpolymer fibre in Fig. 5.5	180
5.11 Profiles of the first five spherical harmonic components calculated from the scattering data of each pattern of the block terpolymer fibre in Fig. 5.6	181
5.12 Profiles of a spherical harmonic components as a function of Q for the random terpolymer fibre (a) I_2 (b) kI_8 and (c) $(I_2 - kI_8)$ where k is the refined constant obtained from curve fitting (see text)	182
5.13 Profiles of a spherical harmonic components as a function of Q for the block terpolymer fibre (a) I_2 (b) kI_8 and (c) $(I_2 - kI_8)$ where k is the refined constant obtained from curve fitting (see text)	183
5.14 (a) SAXS patterns of the random terpolymer fibres drawn at various condition (b) Meridian scans corresponding to the SAXS patterns in (a)	186
5.15 (a) SAXS patterns of the block terpolymer fibres drawn at various condition (b) Meridian scans corresponding to the SAXS patterns in (a)	187
5.16 SEM micrographs of lateral surface of the hot-drawn fibre of (a) random and (b) block terpolymers	189

Figure	Page
5.17 SEM micrographs of fractured surfaces in different views of the hot-drawn fibre. (Left) the random terpolymer fibre drawn at 70°C, draw ratio = 7.7 with the rate of 6900%/min and (Right) the block terpolymer fibre drawn at 80°C, draw ratio = 9.4 with the rate of 4480%/min	190
5.18 (a) A Lloyds LRX+ Universal Testing Machine (b) The bollard grips showing the fibre sample mounted for tensile testing	191
5.19 Stress-strain curves of the as-spun and fibres of the random terpolymer drawn under various conditions	192
5.20 Stress-strain curves of the as-spun and fibres of the block terpolymer drawn under various conditions	193
5.21 Comparison of the stress-strain curve of PDSII to those of the random and block terpolymer fibres.	194
5.22 Plot of ultimate stress at break against draw ratio for the random and block terpolymer fibres	201
5.23 Plot of modulus against draw ratio for the random and block temperature fibres	201
5.24 Plot a log(max draw rate) against draw temperature for the random terpolymer fibre	202
5.25 Plot a log(max draw rate) against draw temperature for the block terpolymer fibre	202
5.26 (a) SEM micrographs of Monocryl and PDSII sutures after degradation for 3 and 18 weeks, respectively. (b) Stress-strain curves of Monocryl and PDSII sutures	203

ABBREVIATIONS AND SYMBOLS

g	gram
ml	millilitre
°C	degree Celcius
Fig.	Figure
min	minute
mg	milligram
Å	angstrom
M	molar
µl	microlitre
g/dl	gram per decilitre
MHz	megahertz
K	Kelvin
ppm	part per million
J/g	joules per gram
WAXS	wide-angle X-ray scattering
WAXD	wide-angle X-ray diffraction
SAXS	small-angle X-ray scattering