

REFERENCES

- [1] Kelly J.R., Nishimura I., Campbell S.D., Ceramics in dentistry: Historical roots and current perspectives. *J. Prosthet. Dent.* 1996; 75: 18-32.
- [2] O'Brien W.J., *Dental materials and their selection*. 2nd ed. Quintessence Publishing Co. Inc., Chicago, pp. 287-302, 1997.
- [3] McLean J.W., *The science and art of dental ceramics Vol. I: The nature of dental ceramics and their clinical used*. Quintessence Publishing Co. Inc., Chicago, 1979.
- [4] Cheung K.C., Darvell B.W., Sintering of dental porcelain: Effect of time and temperature on appearance and porosity. *Dent. Mater.* 2002; 18: 163-73.
- [5] Denry I.L., Recent advances in ceramics for dentistry. *Crit. Rev. Oral. Biol. Med.* 1996; 7: 134-43.
- [6] Quinn J.B., Sundar V., Lloyd I.K., Influence of microstructure and chemistry on the fracture toughness of dental ceramics. *Dent. Mater.* 2003; 19: 603-11.
- [7] Rizkalla A.S., Jones D.W., Mechanical properties of commercial high strength ceramic core materials. *Dent. Mater.* 2004; 20: 207-12.
- [8] Zinelis S., Tsetsekou A., Papadopoulos T., Thermal expansion and microstructural analysis of experimental metal-ceramic titanium alloys. *J. Prosthet. Dent.* 2003; 90: 332-38.
- [9] Fischer H., Mark R., Fracture toughness of dental ceramics: Comparison of bending and indentation method. *Dent. Mater.* 2002; 18: 12-9.

- [10] Bernardo E., Scarinci G., Sintering behavior and mechanical properties of Al₂O₃ platelet-reinforced glass matrix composites obtained by powder technology. *Ceram. Int.* 2004; 30: 785-91.
- [11] Guazzato M., Albakry M., Ringer S.P., Swain M.V., Strength fracture toughness and microstructure of a selection of all-ceramic materials. Part I. *Dent. Mater.* 2004; 20: 441-48.
- [12] McLean J.W., A higher strength of porcelain for crown and bridge work. *Br. Dent. J.* 1965; 119: 268-72.
- [13] Suryanarayana C., Structure and properties of nanocrystalline materials. *Bull. Mater. Sci.* 1994; 17: 307-10.
- [14] Gao L., Jin X., Kawaoka H., Sekino T., Niihara K., Microstructure and mechanical properties of SiC-mullite nanocomposite prepared by spark plasma sintering. *Mater. Sci. Eng. A.* 2002; 334: 262-66.
- [15] Hirvonen A., Nowak R., Yamamoto Y., Sekino T., Niihara K., Fabrication, structure, mechanical and thermal properties of zirconia-based ceramic nanocomposites. *J. Eur. Ceram. Soc.* 2006; 26: 1497-505.
- [16] Choa Y.H., Yang J.K., Kim B.H., Jeong Y.K., Lee J.S., Nakayama T., Sekino T., Niihara K., Preparation and characterization of metal/ceramic nanoporous nanocomposite powders. *J. Mag. Mat.* 2003; 266: 12-9.
- [17] Ostertag C.P., Influence of fiber and grain bridging on crack profiles in SiC fiber-reinforced alumina-matrix composites. *Mater. Sci. Eng. A.* 1999; 260: 124-31.
- [18] Davidson D.L., Fatigue and fracture toughness of aluminium alloys reinforced with SiC and alumina particles. *Composites.* 1993; 24: 248-55.

- [19] Maity S., Sarkar B.K., Phase analysis and role of microstructure in the development of high strength porcelains. *Ceram. Int.* 1998; 24: 259-64.
- [20] Yuan Z.Y., Su B.L., Titanium oxide nanotubes, nanofibers and nanowires, *Colloid. Surface. A.* 2004; 241: 173-83.
- [21] Craig R.G., Powers J.M., *Restorative dental materials*. 11th ed. CV Mosby Co. Inc., St. Louis, pp. 551-571, 2002.
- [22] Boccaccini A.R., Winkler V., Fracture surface roughness and toughness of Al₂O₃-platelet reinforced glass matrix composites. *Composites A.* 2002; 33: 125-31.
- [23] Shelley N., *A Celebration of Twentieth-Century House wares Technology and Culture*. Vol. 40. America at Home, pp. 180-182, 1999.
- [24] Anusavice K.J., DeHoff P.H., Hojatie B., Gray A., Influence of tempering and contraction mismatch on crack development in ceramic surfaces. *J. Dent. Res.* 1989; 68: 1182-7.
- [25] Duret F., Blouin J.L., Duret B., CAD-CAM in dentistry. *J. Am. Dent. Assoc.* 1988; 117: 715-20.
- [26] Rucker L.M., Richter W., MacEntee M., Richardson A., Porcelain and resin veneers clinically evaluated: 2-year results. *J. Am. Dent. Assoc.* 1990; 121: 594-6.
- [27] Ibrahim D.M., El-Meliogy E.A., Mica leucite dental porcelain, *British Ceramic Transactions*. Vol. 100. pp. 260-264, 2001.
- [28] Artitudes. 1990. "A Gallery of Fine American Crafts and Jewelry." [Online]. Available <http://www.artitudesgallery.com/JudithWeberPg.htm> (19 August 2007).
- [29] Giordano R.A., Dental ceramic restorative systems. *Compend. Contin. Educ. Dent.* 1996; 17: 779-802.

- [30] Jones D.W., Development of dental ceramics. *Dent. Clin. North Am.* 1985; 29: 621-44.
- [31] Hermansson L., Carlsson. R., On the crystallization of the glassy phases in whitewares. *Trans. Br. Ceram. Soc.* 1978; 77: 32-5.
- [32] Paul, F.C., Xauxiliary fluxes in ceramic bodies. *J. Am. Ceram. Soc.* 1932; 15: 17-27.
- [33] Rouf M.A., Hermansson L., Carlsson R., Crystallization of glasses in the primary phase field of leucite in the potassium oxide-aluminum oxidesilicon dioxide system. *Trans. Br. Ceram. Soc.* 1978; 77: 36-9.
- [34] Pich'e P.W., O'Brien W.J., Groh C.L., Boenke K.M., Leucite content of selected dental porcelains. *J. Biomed. Mater. Res.* 1994; 28: 603-9.
- [35] Meneses D.D., Malki M., Echegut P., Optical and structural properties of calcium silicate glasses. *J. Non-Cryst. Sol.* 2006; 352: 5301-8.
- [36] Tu Y., Tersoff J. Structure and energetics of the Si- SiO₂ interface. *Phys. Rev. Lett.* 2000; 84: 4393-66.
- [37] Zachariasen W.H., The atomic arrangement in glass. *J. Am. Chem. Soc.* 1932; 54: 3841-51.
- [38] Orlowski H.J., Koenig C.J, Thermal expansion of silicate fluxes in the crystalline and glassy states. *J. Am. Ceram. Soc.* 1941; 24: 80-4.
- [39] Mackert J.R., Butts M.B., Fairhurst C.W., The effect of the leucite transformation on dental porcelain expansion. *Dent. Mater.* 1986; 2: 32-6.
- [40] *Pilkington Group Limited.* 2007. “*Chemistry of glass.*” [Online]. Available <http://www.pilkington.com/about+pilkington/education/chemistry+of+glass.htm> (20 August 2007).

- [41] Elliott S.R., *Physics of amorphous materials*. Longman Group Ltd, London, 1983.
- [42] Watson H.L., Some properties of fused quartz and other forms of silicon-dioxide. *J. Am. Ceram. Soc.* 1926; 9: 511-34.
- [43] Fairhurst C.W., Anusavice K.J., Hashinger D.T., Ringle R.D., Twiggs S.W., Thermal expansion of dental alloys and porcelains. *J. Biomed. Mater. Res.* 1980; 14: 435-46.
- [44] Desouki Sh.El., Shaisha E.E., Shaltout I., Mady H.A., A new concept about the static structure and alkali non-bridging oxygen dependence of the mixed alkali effect in bismuthate glasses. *Int. J. Pure Appl. Phys.* 2007; 3: 10–21.
- [45] Bernard H.W., Ruud G.C., Peter A.V., *Glass: Ullmann's encyclopedia of industrial chemistry*. John Wiley & Sons, Inc., New York, 2000.
- [46] Dong J.K., Luthy H., Wohlwend A., Scharer P., Heat-pressed ceramics: technology and strength. *Int. J. Prosthodont.* 1992; 5: 9-16.
- [47] Chaim R., Baum L., Brandon D.G., Mechanical properties and microstructure of whisker-reinforced alumina-30 vol% glass matrix composite. *J. Am. Ceram. Soc.* 1989; 72: 1636-42.
- [48] Szarska S., Jungner H., Staniewicz B.B., Wiatr M., Characteristics of defect formation in aluminium oxide reinforced bioactive glass, Radiation Measurements. In Press, Corrected Proof, Available online 21 February 2007.
- [49] Shareef M.Y., Van N.R., Messer P.F., Piddock V., The effect of microstructural features on the biaxial flexural strength of leucite reinforced glass ceramics. *J. Mater. Sci. Mater. Med.* 1994; 5: 113-8.

- [50] Osaka A., Ono M., Takahashi K., Aluminum oxide anomaly and structure model of alkali aluminosilicate glasses. *J. Am. Ceram. Soc.* 1987; 70: 242-245.
- [51] Grossman D.G., Machinable glass ceramics based upon tetrasilicic mica. *J. Am. Ceram. Soc.* 1972; 55: 446-9.
- [52] MacCulloch W.T., Advances in dental ceramics. *Br. Dent. J.* 1968; 124: 361-5.
- [53] Smith T.B., Kelly J.R., Tesk J.A., In vitro fracture behavior of ceramic and metal-ceramic restorations. *J. Prosthodont.* 1994; 3: 138-44.
- [54] White S.N., Miklus V.G., McLaren E.A., Lang L.A., Caputo A.A., Flexural strength of a layered zirconia and porcelain dental all-ceramic system. *J. Prosthet. Dent.*, 2005; 94: 125-31.
- [55] Kelly J.R., Campbell S.D., Bowen H.K., Fracture-surface analysis of dental ceramics. *J. Prosthet. Dent.* 1989; 62: 536-41.
- [56] Grossman D.G., Cast glass ceramics. *Dent. Clin. North Am.* 1985; 29: 719-23.
- [57] McLean J.W., Hughs T.H., The reinforcement of dental porcelain with ceramic oxides. *Br. Dent. J.* 1965; 119: 251-67.
- [58] Sozi R.B., Riley E.J., Shrink-free ceramic. *Dent. Clin. North Am.* 1985; 29: 707-17.
- [59] Anusavice K.J., Gray A.E., Influence of framework design, contraction mismatch, and thermal history on porcelain checking in fixed partial dentures. *Dent. Mater.* 1989; 5: 58-63.
- [60] Fairhurst C.W., Lockwood P.E., Ringle R.D., Thompson W.O., The effect of glaze on porcelain strength. *Dent. Mater.* 1992; 8: 203-7.
- [61] Mayo M.J., Hague D.C., Chen D.J., Processing nanocrystalline ceramics for application in superplasticity. *Mater. Sci. Eng. A.* 1993; 166: 145-59.

- [62] Fang Y., Agrawal D.K., Roy D.M., Roy R., Fabrication of transparent hydroxyapatite ceramics by ambient-pressure sintering. *Mater. Lett.* 1995; 23: 147-51.
- [63] Lu L., Ueda K.-I., Yagi H., Yanagitani T., Akiyama Y., Kaminskii A.A., Neodymium doped yttrium aluminum garnet ($\text{Y}_3\text{Al}_5\text{O}_{12}$) nanocrystalline ceramics-a new generation of solid state laser and optical materials. *J. Alloys Compd.* 2002; 341: 220-5.
- [64] Cheong D.S., Hwang K.T., Kim C.S., Fabrication, mechanical properties and microstructure analysis of $\text{Si}_3\text{N}_4/\text{SiC}$ nanocomposite. Composites Part A: App. Sci. Manufac. 1999; 30: 425-7.
- [65] Kuntz J.D., Zhan G.D., Mukherjee A.K., *Improved fracture toughness in advanced nanocrystalline ceramic composites*. Chem. Eng. & Mater. Sci. University of California-Davis, United States, 2004.
- [66] Kuntz, J., Zhan, G.-D., Wan, J., Garay, J. and Mukherjee, A.K., Spark-plasma-sintered $\text{BaTiO}_3/\text{Al}_2\text{O}_3$ nanocomposites, *Mater. Sci. Eng. A.* 2003; 356: 443-6.
- [67] Zhan G.D., Kuntz J.D., Wan J., Garay J.E., Mukherjee A.K., A novel processing route to develop a dense nanocrystalline alumina matrix (< 100nm) nanocomposite material. *J. Am. Ceram. Soc.* 2003; 86; 200-2.
- [68] Zhan G.D., Kuntz J.D., Wan J., Mukherjee A.K., Single-wall carbon nanotubes as attractive toughening agents in alumina-based nanocomposites. *Nat. Mater.* 2003; 2: 38-42.
- [69] Xu C., Huang C., Ai X. Toughening and strengthening of advanced ceramics with rare earth additives. *Ceram. Int.* 2006; 32: 423-9.

- [70] Meguid S.A., Mechanics and mechanisms of toughening of advanced ceramics. *J. Mater. Proc. Tech.* 1996; 56: 978-89.
- [71] Kuntz J.D., Wan J., Zhan G.D., Mukherjee A.K., in *Proc. TMS Annu. Meet. on Ultrafine grained materials II*. The Minerals, Metals and Materials Society, Warrendale, PA, pp. 225, 2002.
- [72] Kelly P.M., Francis Rose L.R., The martensitic transformation in ceramics-its role in transformation toughening. *Prog. Mater. Sci.* 2002; 47: 463-557.
- [73] Bhaduri S., Bhaduri S.B., Enhanced low temperature toughness of Al_2O_3 - ZrO_2 nano/nano composites. *Nanostruct. Mater.* 1997; 8: 755-63.
- [74] Evans A.G., Perspective on the development of high-toughness ceramics. *J. Am. Ceram. Soc.* 1990; 73: 187-206.
- [75] Reimanis I.E., A review of issues in the fracture of interfacial ceramics and ceramic composites. *Mater. Sci. Eng. A.* 1997; 237: 159-67.
- [76] Ruhle M., Evans A.G., McMeeking R.M., Charalambides P.G., Hutchinson J.W., Microcrack toughening in alumina/zirconia. *Acta. Metall.* 1987; 35: 2701-10.
- [77] Gu W.H., Faber K.T., Steinbrech R.W., Microcracking and R-curve behavior in SiC - TiB_2 composites. *Acta. Metall. Mater.* 1992; 40: 3121-8.
- [78] Niihara K., A. Nakahira, and T. Sekino, in *Nanophase and Nanocomposite Materials*. Mater. Res. Soc. Symp. Proc. 286, Pittsburgh, PA, pp. 405, 1993.
- [79] Niihara K., Nakahira A., Sasaki G., Hirabayashi M., in *Proc. MRS Int. Meet. Adv. Mater.* Vol. 4, Materials Research Society, Pittsburgh, PA, pp. 129, 1989.

- [80] Niihara K., Nakahira A., in *Proc. Satellite Symp. 2, Adv. Structural Inorganic Composites.* 7th Int. Meet. on Modern Ceramics Technologies, Elsevier, Amsterdam, pp. 637, 1991.
- [81] Levin A., Kaplan W.D., Brandon D.G., Layyous A.A., Effect of SiC submicrometer particle size and content on fracture toughness of Alumina-SiC "Nanocomposites". *J. Am. Ceram. Soc.* 1995; 78: 254-6.
- [82] Ray A., Tiwari A.N., Compaction and sintering behavior of glass-alumina composite. *Mater. Chem. Phys.* 2001; 67: 220-5.
- [83] Choy K.L., Duplock P., Rogers P.S., Davies J.C., Pirzada M.T., The mechanical behaviour of glass and glass-ceramic matrix composites. *Mater. Sci. Eng. A.* 2000; 278: 187-94.
- [84] Chen R.Z., Tuan W.H., Pressureless sintering of Al₂O₃/Ni nanocomposites. *J. Eur. Ceram. Soc.* 1999; 19: 463-8.
- [85] Wagner W.C., Chu T.M., Biaxial flexural strength and indentation fracture toughness of three new dental core ceramics. *J. Prosthet. Dent.* 1996; 76: 140-4.
- [86] Tulyaganov D.U., Ribeiro M.J., Labrincha J.A., Development of glass-ceramics by sintering and crystallization of fine powders of calcium-magnesium-aluminosilicate glass. *Ceram. Int.* 2002; 28: 515-20.
- [87] Ohji T., Young-Keun J., Yong-Ho C., Niihara K., Strengthening and toughening mechanisms of ceramic nanocomposites. *J. Am. Ceram. Soc.* 1998; 81: 1453-60.
- [88] Tan H., Yang W., Toughening mechanisms of nanocomposite ceramics. *Mech. Mater.* 1998; 30: 111-23.

- [89] Ji Y., Yeomans J.A., Processing and mechanical properties of Al_2O_3 -5 vol.% Cr nanocomposites. *J. Eur. Ceram. Soc.* 2002; 22: 1927-36.
- [90] Oh S.T., Sekino T., Niihara K., Fabrication and mechanical properties of 5 vol% copper dispersed alumina nanocomposite. *J. Eur. Ceram. Soc.* 1998; 18: 31-7.
- [91] Sekino T., Nakajima T., Ueda S., Niihara K., Reduction and sintering of a nickel-dispersed-alumina composite and its properties. *J. Am. Ceram. Soc.* 1997; 80: 1139-48.
- [92] Sekino T., Niihara K., Microstructural characteristics and mechanical properties for Al_2O_3 /metal nanocomposites. *Nanostruct. Mater.* 1995; 6: 663-6.
- [93] Albakry M., Guazzato M., Swain M.V., Fracture toughness and hardness evaluation of three pressable all-ceramic dental materials. *J. Dent.* 2003; 31: 181-8.
- [94] Mishra R.S., Lesher C.E., Mukherjee A.K., in *Materials Science Forum*, Vols. 225-227, Part 1, Trans Tech, Zurich, Switzerland, pp. 617, 1996.
- [95] Mishra R.S., Lesher C.E., Mukherjee A.K., High-pressure sintering of nanocrystalline γ - Al_2O_3 . *J. Am. Ceram. Soc.* 1996; 79: 2989-92.
- [96] Liao S.C., Chen Y.J., Kear B.H., Mayo W.E., High pressure/low temperature sintering of nanocrystalline alumina. *Nanostruct. Mater.* 1998; 10: 1063-79.
- [97] Wan J., Gasch M.J., Kuntz J.D., Mishra R., Mukherjee A.K., in *Structure and mechanical properties of nanophase materials: Theory and computer simulation vs. experiment*. Mater. Res. Soc. Symp. Proc. 634, Warrendale, PA, pp. B7.2.1, 2001.

- [98] Wan J., Gasch M.J., Mukherjee A.K., Silicon carbonitride ceramics produced by of polymer ceramic powder. *J. Mater. Res.* 2000; 15: 1657-60.
- [99] Zhan G.D., Kuntz J.D., Wan J., Garay J.E., Mukherjee A.K., in *Ultrafine grained materials II: Proc. TMS Annu. Meet.* The Minerals Metals & Materials Society, Warrendale, PA, pp. 219, 2002.
- [100] Zhan G.D., Kuntz J.D., Wan J., Garay J.E., Mukherjee A.K., Alumina-based nanocomposites consolidated by spark plasma sintering, *Scripta. Mater.* 2002; 47: 737-41.
- [101] Hernandez T., Bautista M.C., The role of the synthesis route to obtain densified TiO₂-doped alumina ceramics. *J. Eur. Ceram. Soc.* 2005; 25: 663-72.
- [102] Bueno S., Moreno R., Baudín C., Reaction sintered Al₂O₃/Al₂TiO₅ microcrack-free composites obtained by colloidal filtration. *J. Eur. Ceram. Soc.* 2004; 24: 2785-91.
- [103] Vestal C.R., Zhang Z.J., Normal micelle synthesis and characterization of MgAl₂O₄ spinel nanoparticles. *J. Solid. State. Chem.* 2003; 175: 59-62.
- [104] Mazzoni A.D., Sainz M.A., Caballero A., Aglietti E.F., Formation and sintering of spinels (MgAl₂O₄) in reducing atmospheres. *Mater. Chem. Phys.* 2002; 78: 30-7.
- [105] Xiao-ping L., Jie-mo T., Yun-long Z., Ling W., Strength and fracture toughness of MgO-modified glass infiltrated alumina for CAD/CAM. *Dent. Mater.* 2002; 18: 216-20.

- [106] Valenzuela M.A., Jacobs J.P., Bosch P., Reijne S., Zapata B., Brongersma H.H., The influence of the preparation method on the surface structure of ZnAl₂O₄. *Appl. Catal. A-Gen.* 1997; 148: 315-24.
- [107] Elam J.W., Sechrist Z.A., George S.M., ZnO/Al₂O₃ nanolaminates fabricated by atomic layer deposition: growth and surface roughness measurements. *Thin. Solid. Films.* 2002; 414: 43-55.
- [108] Duan X., Yuan D., Sun Z., Sun H., Xu D., Lv M., Synthesis and characterization of ZnAl₂O₄/SiO₂ nanocomposites by sol-gel method. *J. Cryst. Growth.* 2003; 252: 4-8.
- [109] Jamaluddin O., Zainal A.A., Study on changing the coefficient of thermal expansion (CTE) of dental porcelain. *Med. J. Malaysia.* 2004; 59: 143-4.
- [110] Hahn H., Microstructure and properties of nanostructured oxides, *Nanostruct. Mater.* 1993; 2: 251-65.
- [111] Pechenik A., Piermarini G.J., Danforth S.C., Fabrication of transparent silicon nitride from nanosize particles. *J. Am. Ceram. Soc.*, 1992; 75: 3283-8.
- [112] Pechenik A., Piermarini G.J., Danforth S.C., Low temperature densification of silicon nitride nanoglasses. *Nanostruct. Mater.*, 1993; 2: 479-86.
- [113] Gallas M.R., Hockey B., Pechenik A., Piermarini G.J., Fabrication of transparent γ -Al₂O₃ from nanosize particles. *J. Am. Ceram. Soc.*, 1994; 77: 2107-12.
- [114] Kolbeck C., Rosentritt M., Handel G., Fracture strength of artificially aged 3-unit adhesive fixed partial dentures made of fiber-reinforced composites and ceramics: an in vitro study. *Quintessence Int.* 2006; 37: 731-5.

- [115] Reidy D.J., Holmes J.D., Morris M.A., The critical size mechanism of anatase to rutile transformation for TiO₂ and doped-TiO₂. *J. Eur. Ceram. Soc.* 2006; 26: 1527-34.
- [116] Chu R., Yan J., Lian S., Wang Y., Yan F., Chen D., Shape-controlled synthesis of nanocrystalline titania at low temperature. *Solid. State. Commun.* 2004; 130: 789-92.
- [117] Huang W., Tang X., Felner I., Koltypin Y., Gedanken A., Preparation and characterization of Fe_xO_y-TiO₂ via sonochemical synthesis. *Mater. Res. Bull.* 2002; 37: 1721-35.
- [118] Pesl J., Eric R.H., High temperature carbothermic reduction of Fe₂O₃-TiO₂-M_xO_y oxide mixtures. *Miner. Eng.* 2002; 15: 971-84.
- [119] Pal B., Sharon M., Nogami G., Preparation and characterization of TiO₂/Fe₂O₃ binary mixed oxides and its photocatalytic properties. *Mater. Chem. Phys.* 1999; 59: 254-61.
- [120] Kalinkin A.M., Kalinkina E.V., Makarov V.N., Mechanical activation of natural titanite and its influence on the mineral decomposition. *Int. J. Miner. Process.* 2003; 69: 143-55.
- [121] Aboshi H., Takahashi T., Komuro T., Component analysis of dental porcelain for assisting dental identification. *J. Forensic Odontostomatol.* 2006; 24: 36-41.
- [122] International Organization for standardization. ISO 6872: 1995(E): Dental ceramics, 2nd ed. Geneva, Switzerland 1995.
- [123] Anusavice K.J., Hojjatie B., Effect of thermal tempering on strength and crack propagation behavior of feldspathic porcelains. *J. Dent. Res.* 1991; 70: 1009-13.

- [124] American society for testing of materials, Designation C 20-00 Standard test methods for apparent porosity, water absorption, apparent specific gravity, and bulk density of burned factory brick and shapes by boiling water. In: Annual Book of ASTM Standards 15.01, Philadelphia: ASTM (2000)
- [125] American society for testing of materials, Designation C 1259-01 Standard test method for dynamic Young's modulus, shear modulus, and Poisson's ratio for advanced ceramics by impulse excitation of vibration. In: Annual Book of ASTM Standards 15.01, Philadelphia: ASTM (2001)
- [126] American Society for Testing of Materials, Designation C 1327-99 Standard test method for Vickers indentation hardness of advanced ceramics. In: Annual Book of ASTM Standards 15.01, Philadelphia: ASTM (1999)
- [127] Anstis G.R., Chantikul P., Lawn B.R., Marshall B.D., A critical evaluation of indentation techniques for measuring fracture toughness: I, Direct crack measurements. *J. Am. Ceram. Soc.* 1981; 64: 533-8.
- [128] Chantikul P., Anstis G.R., Lawn B.R., Marshall B.D., A critical evaluation of indentation techniques for measuring fracture toughness: II, strength method. *J. Am. Ceram. Soc.* 1981; 64: 539-43.
- [129] Weibull W. A statistical distribution function of wide application. *J. Applied Mechanism.* 1951; 9: 293-7.
- [130] Abernethy R.B., *The new Weibull handbook*. North Palm Beach, FL, 2000.
- [131] Thompson G.A., Abernethy R.B., Kelly J.R., Determining Weibull two-parameter estimates by different methods. *J. Dent. Res.* 2001; 80: 199-203.

- [132] Cattell M.J., Chadwick T.C., Knowles J.C., Clarke R.L., Lynch E., Flexural strength optimization of a leucite reinforced glass ceramic. *Dent. Mater.* 2001; 17: 21-33.
- [133] Harada R., Sugiyama N., Ishida H., Al₂O₃-strengthened feldspathic porcelain bodies; Effect of the amount and particle size of alumina. *Ceram. Eng. Sci. Proc.* 1996; 17: 88-98.
- [134] Cesar P.F., Yoshimura H.N., Miranda Junior W.G., Okada C.Y., Correlation between fracture toughness and leucite content in dental porcelains. *J. Dent.* 2005; 33: 721-9.
- [135] Seghi R.R., Denry I.L., Rosenstiel S.F., Relative fracture toughness and hardness of new dental ceramics. *J. Prosthet. Dent.* 1995; 74: 145-50.
- [136] Johnson S.M., Pask, J.A., Role of impurities on formation of mullite from kaolinite and Al₂O₃-SiO₂ mixtures. *Am. Ceram. Soc. Bull.* 1982; 61: 838-42.
- [137] Klug F.J., Prochazka S., Doremus R.H., Al₂O₃-SiO₂ system in the mullite region. *J. Am. Ceram. Soc.* 1987; 70: 750-9.
- [138] Rado P., The strength case of hard porcelain. *Trans. Br. Ceram. Soc.* 1971; 71: 131-9.
- [139] Tanimoto Y., Nemoto K., Effect of sintering temperature on flexural properties of alumina fiber-reinforced, alumina-based ceramics prepared by tape casting technique. *J. Prosthodont.* 2006; 15: 345-52.
- [140] Tanimoto Y., Nemoto K., Development of Al₂O₃ fiber-reinforced Al₂O₃-based ceramics. *Dent. Mater J.* 2004; 23: 297-304.

- [141] Cai K.F., He X.R., Zhang L.C., Fabrication, properties and sintering of ZnO nanopowder *Materials Letters, In Press, Uncorrected Proof, Available online 10 August 2007,*
- [142] Li J.Y., Dai H., Zhong X.H., Zhang Y.F., Ma X.F., Meng J., Cao X.Q., Effect of the addition of YAG ($\text{Y}_3\text{Al}_5\text{O}_{12}$) nanopowder on the mechanical properties of lanthanum zirconate. *Mater. Sci. Eng. A.*, 2007; 460-461: 504-8.
- [143] Rusnah M., Andanastuti M., Idris B., The influence of sintering temperature on the porosity and strength of porous hydroxyapatite ceramics. *Med. J. Malaysia*. 2004; 59: 158-9.
- [144] Hojjatie B., Anusavice K.J., Effects of initial temperature and tempering medium on thermal tempering of dental porcelains. *J. Dent. Res.* 1993; 72: 566-71.
- [145] Twiggs S.W., Mackert J.R., Oxford A.L., Ergle J.W., Lockwood P.E., Isothermal phase transformations of a dental porcelain. *Dent. Mater.* 2005; 21: 580-5.
- [146] Isgro G., Wang H., Kleverlaan C.J., Feilzer A.J., The effects of thermal mismatch and fabrication procedures on the deflection of layered all-ceramic discs. *Dent. Mater.* 2005; 21: 649-55.
- [147] Hojjatie B., Anusavice K.J., Effects of initial temperature and tempering medium on thermal tempering of dental porcelains. *J. Dent. Res.* 1993; 72: 566-71.
- [148] DeHoff P.H., Vontivillu S.B., Wang Z., Anusavice K.J., Stress relaxation behavior of dental porcelains at high temperatures. *Dent. Mater.* 1994; 10: 178-84.

- [149] Studart A.R., Filser F., Kocher P., Luthy H., Gauckler L.J., Mechanical and fracture behavior of veneer-framework composites for all-ceramic dental bridges. *Dent. Mater.* 2007; 23: 115-23.
- [150] Peters M.C., de Vree J.H., Brekelmans W.A., Distributed crack analysis of ceramic inlays. *J. Dent. Res.* 1993; 72: 1537-42.
- [151] Mackert J.R., Rueggeberg F.A., Lockwood P.E., Evans A.L., Thompson W.O., Isothermal anneal effect on microcrack density around leucite particles in dental porcelain. *J. Dent. Res.* 1994; 73: 1221-7.
- [152] Denry I.L., Holloway J.A., Tarr L.A., Effect of heat treatment on microcrack healing behavior of a machinable dental ceramic. *J. Biomed. Mater. Res.* 1999; 48: 791-6.
- [153] Mackert J.R., Twiggs S.W., Russell C.M., Williams A.L., Evidence of a critical leucite particle size for microcracking in dental porcelains. *J. Dent. Res.* 2001; 80: 1574-9.
- [154] Xu C., Effects of particle size and matrix grain size and volume fraction of particles on the toughening of ceramic composite by thermal residual stress *Ceram. Inter.* 2005; 31: 537-42.
- [155] Lenz J., Thies M., Wollwage P., Schweizerhof K., A note on the temperature dependence of the flexural strength of a porcelain. *Dent. Mater.* 2002; 18: 558-60.
- [156] Kon M., O'Brien W.J., Rasmussen S.T., Asaoka K., Mechanical properties of glass-only porcelains prepared by the use of two feldspathic frits with different thermal properties. *J. Dent. Res.* 2001; 80(8): 1758-63.

- [157] Yilmaz H., Aydin C., Gul B.E., Flexural strength and fracture toughness of dental core ceramics. *J. Prosthet. Dent.* 2007; 98: 120-8.
- [158] Wen M.Y., Mueller H.J., Chai J., Wozniak W.T., Comparative mechanical property characterization of 3 all-ceramic core materials. *Int. J. Prosthodont.* 1999; 12(6): 534-41.
- [159] Cattell M.J., Chadwick T.C., Knowles J.C., Clarke R.L., Samarawickrama D.Y., The nucleation and crystallization of fine grained leucite glass-ceramics for dental applications. *Dent. Mater.* 2006; 22: 925-33.
- [160] Powder Diffraction File No. 15-0047. International Centre for Diffraction Data, Newton Square, PA, 2000.
- [161] Powder Diffraction File No. 10-0173. International Centre for Diffraction Data, Newton Square, PA, 2000.
- [162] Feret F.R., Roy D., Boulanger C., Determination of alpha and beta alumina in ceramic alumina by X-ray diffraction *Spectrochimica Acta. Part B: Atomic Spectroscopy*. 2000; 55: 1051-61.
- [163] Powder Diffraction File No. 21-1152. International Centre for Diffraction Data, Newton Square, PA, 2000.
- [164] Zawrah M.F., Hamaad H., Meky S., Synthesis and characterization of nano $MgAl_2O_4$ spinel by the co-precipitated method. *Ceram. Inter.* 2007; 33: 969-78.
- [165] Powder Diffraction File No. 05-0669. International Centre for Diffraction Data, Newton Square, PA, 2000.
- [166] Areán C.O., Sintes B.S., Palomino G.T., Carbonell C.M., Platero E.E., Parra Soto J.B., Preparation and characterization of spinel-type high surface area

- Al₂O₃-ZnAl₂O₄ mixed metal oxides by an alkoxide route. *Micropor. Mater.* 1997; 8: 187-92.
- [167] Chen I.W., Wang X.H., Sintering dense nanocrystalline ceramics without final-stage grain growth. *Nature*. 2000; 404: 168-71.
- [168] Chong A.C., Miller F., Buxton M., Friis E.A., Fracture toughness and fatigue crack propagation rate of short fiber reinforced epoxy composites for analogue cortical bone. *J. Biomech. Eng.* 2007; 129: 487.
- [169] Mackert J.R., Williams A.L., Microcracks in dental porcelain and their behavior during multiple firing. *J. Dent. Res.* 1996; 75: 1484-90.
- [170] Anusavice K.J., Lee R.B., Effect of firing temperature and water exposure on crack propagation in unglazed porcelain. *J. Dent. Res.* 1989; 68: 1075-81.
- [171] Powder Diffraction File No. 21-1276. International Centre for Diffraction Data, Newton Square, PA, 2000.
- [172] Kloužková A., Mrázová M., Kohoutková M., Synthesis of partially stabilized leucite. *J. Phys. Chem. Solids.* 2007; 68: 1207-10.
- [173] Diebold U., The surface science of titanium dioxide. *Surface Sci. Reports.* 2003; 48: 221-9.
- [174] Kwon C.H., Kim J.H., Jung I.S., Shin H., Yoon K.H., Preparation and characterization of TiO₂-SiO₂ nano-composite thin films. *Ceram. Inter.* 2003; 29: 851-6.
- [175] Cesar P.F., Yoshimura H.N., Miranda W.G., Miyazaki C.L., Muta L.M., Rodrigues L.E., Relationship between fracture toughness and flexural strength in dental porcelains. *J. Biomed. Mater. Res. B.* 2006; 78: 265-73.

- [176] Sakar-Deliormanli A., Guden M., Microhardness and fracture toughness of dental materials by indentation method. *J. Biomed. Mater. Res. B.* 2006; 76: 257-64.
- [177] Lenz J., Kessel S., Thermal stresses in metal-ceramic specimens for the ISO crack initiation test (three-point flexure bond test). *Dent. Mater.* 1998; 14: 277-80.
- [178] Powder Diffraction File No. 41-1432. International Centre for Diffraction Data, Newton Square, PA, 2000.
- [179] Ambrico J.M., Begley M.R., The role of initial flaw size, elastic compliance and plasticity in channel cracking of thin films. *Thin Solid Films.* 2002; 419: 144-53.
- [180] Yan J., Karlsson A.M., Chen X., On internal cone cracks induced by conical indentation in brittle materials. *Eng. Fracture Mech.* 2007; 74: 2535-46.
- [181] Ayyar A., Chawla N., Microstructure-based modeling of crack growth in particle reinforced composites. *Comp. Sci.Tech.* 2006; 66: 1980-94.
- [182] Jayaseelan D.D., Ueno S., Ohji T., Kanzaki S., Thermo-mechanical stability of porous alumina: effect of sintering parameters. *Sci. Tech. Adv. Mater.* 2004; 5: 387-92.
- [183] Zeng T., Dong X., Mao C., Zhou Z., Yang H., Effects of pore shape and porosity on the properties of porous PZT 95/5 ceramics. *J. Eur. Ceram. Soc.* 2007; 27: 2025-9.