TABLE OF CONTENTS

	Page
ACKNOWLEDGEMENTS	iii
ABSTRACT (ENGLISH)	v
ABSTRACT (THAI)	vi
LIST OF TABLES	х
LIST OF FIGURES	xiii
ABBREVIATIONS AND SYMBOLS	xx
CHAPTER 1 INTRODUCTION	1
1.1 Overview	1
1.2 Objectives	4
CHAPTER 2 LITERATURE REVIEW	5
2.1 Dental Porcelains	5
2.1.1 Chemical compositions	7
opyright ^{2.1.2} Structures hiang Mai Univers	sit 9/
2.1.3 Mechanical Properties	15
2.2 Ceramic Nanocomposites	22
2.2.1 Ductile-Phase Toughening	23
2.2.2 Fiber Toughening	23

		Page
	2.2.3 Transformation Toughening	25
	2.2.4 Microcrack Toughening	26
	2.3 Alumina-Reinforced Ceramic Nanocomposites	31
	2.4 Titanate-Reinforced Ceramic Nanocomposites	34
CHAPTER 3	EXPERIMENTAL PROCEDURE	36
	3.1 Sample Preparation	36
	3.1.1 Powder Preparation	36
	3.1.1.1 Preparation of Dental Porcelain Powders	36
	3.1.1.2 Preparation of Metal Oxides Modified	
	porcelain Powders	39
	3.1.2 Ceramic Fabrication	44
	3.2 Sample Characterization	51
	3.2.1 Phase Analysis	51
	3.2.2 Microstructural Analysis	51
	3.2.3 Densification Analysis	53
	3.2.4 Mechanical Properties Measurements	54
	3.2.4.1 Uniaxial Flexural Strength	54
	3.2.4.2 Hardness and Elastic Modulus	56
	3.2.4.3 Indentation Fracture Toughness	57
	3.3 Statistical Analysis	59

viii

		Page
CHAPTER 4	RESULTS AND DISCUSSION (PART I):	
	AI - OXIDES REINFORCED DENTAL PORCELAINS	61
	4.1 Dental Porcelain Ceramics	61
	4.2 Al ₂ O ₃ Reinforced Porcelain Ceramic Nanocomposites	65
	4.3 Al ₂ O ₃ -M _x O _y Reinforced Porcelain Ceramic	
	Nanocomposites	84
CHAPTER 5	RESULTS AND DISCUSSION (PART II):	
	Ti - OXIDES REINFORCED DENTAL PORCELAINS	106
	5.1 TiO ₂ Reinforced Porcelain Ceramic Nanocomposites	106
	5.2 TiO ₂ -Fe ₂ O ₃ Reinforced Porcelain Ceramic	
	Nanocomposites	123
CHAPTER 6	CONCLUSIONS AND SUGGESTIONS	
	FOR FURTURE WORKS	142
	6.1 Conclusions	142
	6.2 Suggestions for Further Work	143
REFERENCI		145
APPENDIX		e ₁₆₅
VITA		187

LIST OF TABLES

Table		Page
2.1	Chemical compositions of porcelain materials.	7
2.2	Chemical composition analysis of some commercial dental porcelains.	8
2.3	Strength and Fracture Toughness of Alumina-Based Nanocomposites.	28
3.1	Specifications of the raw materials used in this study.	37
3.2	Three groups of dental porcelain powders prepared in this work.	38
3.3	Designed chemical composition of Al-oxides modified porcelains	
	powders.	42
3.4	Designed chemical composition of Ti-oxides modified porcelains	
	powders.	43
3.5	Sintering conditions for the production of dental porcelain ceramics	
	at 950 °C.	48
3.6	Sintering conditions for the production of Al-oxides modified	
	porcelain systems with constant heating rate of 55 °C/min.	49
3.7	Sintering conditions for the production of Ti-oxides modified	
	porcelain systems with constant heating rate of 55 °C/min.	50
4.1	Average (and standard deviation) of physical and mechanical	
	properties of various dental porcelains.	63

Х

Table		Page
4.2	Average (and standard deviation) of the physical properties of Al ₂ O ₃ -	
	reinforced porcelain ceramics.	73
4.3	Average (and standard deviation) of the mechanical properties of	
	Al ₂ O ₃ -reinforced porcelain ceramics.	74
4.4	Summary of one-way ANOVA of Al ₂ O ₃ -reinforced porcelain ceramics.	75
4.5	Results of the Weibull regression analysis of Al ₂ O ₃ -reinforced porcelain	
	ceramics.	77
4.6	XRD analysis of Al_2O_3 - M_xO_y reinforced porcelain ceramics.	85
4.7	Detected crystalline phase specification.	85
4.8	Average (and standard deviation) of the physical properties of Al ₂ O ₃ -	
	M _x O _y reinforced porcelain ceramics.	94
4.9	Average (and standard deviation) of the mechanical properties of	
	Al_2O_3 - M_xO_y reinforced porcelain ceramics.	95
4.10	Summary of one-way ANOVA of Al ₂ O ₃ -M _x O _y reinforced porcelain	
	ceramics.	96
4.11	Results of the Weibull regression analysis of Al_2O_3 - M_xO_y reinforced	
	porcelain ceramics.	98
5.1 DDyr	Average (and standard deviation) of the physical properties of TiO ₂ - reinforced porcelain ceramics.	113
5.2	Average (and standard deviation) of the mechanical properties of	
	TiO ₂ -reinforced porcelain ceramics.	114
5.3	Summary of one-way ANOVA of TiO ₂ -reinforced porcelain ceramics.	115

Table		Page
5.4	Results of the Weibull regression analysis of TiO2-reinforced	
	porcelain ceramics.	117
5.5	Average (and standard deviation) of the physical properties of TiO ₂ -	
	Fe ₂ O ₃ reinforced porcelain ceramics.	130
5.6	Average (and standard deviation) of the mechanical properties of	
	TiO ₂ -Fe ₂ O ₃ reinforced porcelain ceramics.	131
5.7	Summary of one-way ANOVA of TiO ₂ -Fe ₂ O ₃ reinforced porcelain	
	ceramics.	132
5.8	Results of the Weibull regression analysis of TiO ₂ -Fe ₂ O ₃ reinforced	
	porcelain ceramics.	134

ลิขสิทธิ์มหาวิทยาลัยเชียงใหม่ Copyright[©] by Chiang Mai University All rights reserved

LIST OF FIGURES

Figure		Page
1.1	Applications of dental porcelain-based ceramics: (a) inlay, (b) all	
	ceramic jacket crown and (c) veneering metal bridgework.	2
1.2	Cracks of dental porcelain-based ceramics in clinical applications.	3
2.1	Examples of porcelains used in (a) the art decoration and (b) the	
	construction of ceramic crown and bridge.	6
2.2	Structural units of SiO ₄ tetrahedra: (a) diagram of silicate unit with	
	each SiO tetrahedra sharing an oxygen atom, (b) a silicate unit	
	which the silicon atom (Si) is surrounded by four oxygen atoms	
	(oxygen polyhedra) and (c) linked silicate units which form the	
	network in glass.	10
2.3	Two-dimensional presentation of an oxide M_2O_3 in (a) the	
	crystalline form and (b) the glass form.	11
2.4	Reaction between sodium oxide and silica tetrahedral. The sodium	
	oxide contributes one of the non-bridging oxygen ions which	
	interrupt the continuity of the silica network.	- 12
2.5	Two-dimensional representation of the structure of sodium silicate	
	glass.	13

xiii

Figure

- 2.6 Aluminium in a silicate network (The structure is shown in a simplified form; the true structure is three-dimensional, the AlO₄ and SiO₄ groups having tetrahedral configurations.). The alkali metal ion (M^+) such a sodium maintains electroneutrality.
- 2.7 Microcracks in the surface of dental porcelain (arrows) showing a change in direction due to fault in the surface. This is typical of the flaw system which may be present in the surface of porcelain denture.
- 2.8 Methods of strengthening dental porcelain: (a) enameling of metals,(b) enameling of high strength crystalline ceramics and (c) production of pre-stressed surface layers in dental porcelain via ion-exchange.
- 2.9 Diagram illustrating the fracture path in an alumina-glass composite where the thermal expansion of the glass is higher than the alumina.
- 2.10 Diagram of the fracture path occurring in an alumina-glass composite where the coefficients of expansion match. The crack will then pass indiscriminately through both glass and crystalline phases.
 2.11 Schematic illustrations of toughening mechanisms in ceramic-matrix composites: (a) ductile-phase toughening, (b) fiber toughening, (c) transformation toughening, and (d) microcrack toughening.
 - (a) Niihara's classification of nanocomposite types, based on matrix grain size and second-phase particle size. (b) A new classification, in which the matrix phase is continuously nanocrystalline while the second phase varies, leading to four nanocomposite types.

15

16

18

20

21

24

29

Figure		Page
3.1	Typical processing route for dental porcelain powders.	38
3.2	The processing flow chart for the modified porcelain powders.	40
3.3	Micrographs of some key raw materials used in this study: α -Al ₂ O ₃	
	(a) 1-10 μ m, (b) 0.1-1 μ m and (c) 0.1-0.5 μ m; (d) γ -Al ₂ O ₃ (10-100	
	nm), (e) MgO, (f) ZnO, (g) Fe_2O_3 , (h) irregular-shaped TiO_2 and (i)	
	whiskered TiO ₂ .	41
3.4	Fabrication process for dental porcelain ceramics.	45
3.5	Industrial shaping process of dental porcelain by slip casting	
	technique: (1) pouring slip into the metal mold, (2) excess moisture	
	removing, (3) - (4) surface flattening, (5) unpacking and (6) green	
	specimen.	46
3.6	Vacuum furnace (for reducing sample porosity after sintering process).	47
3.7	Schematic diagram of the firing schedule used; x: Heating rate, y:	
	Firing temperature and z: Dwell time.	47
3.8	X-ray diffractometer.	52
3.9	Scanning electron microscope, equipped with EDX analyzer.	52
3.10	Mercury volumenometer.	54
3.11	Diagram of uniaxial flexural strength test shows rectangular-shaped	
	specimen loaded from above by steel bar and supported from below	
	by adjustable half-round steel plates.	55
3.12	Universal testing machine.	55
3.13	Vickers microhardness testing machine.	56

Figure		Page
3.14	Illustration of Vickers indentation and cracks formed around	
	indentation. Dimensions of indentation and cracks to calculate	
	indentation fracture toughness.	57
3.15	Vickers microhardness testing machine.	58
4.1	SEM micrograph of dental porcelain ceramics.	64
4.2	Enlarge zone (b) demonstrating the formation of nanorod-mullite	
	phase in the glassy matrix phase.	64
4.3	SEM micrographs of Al_2O_3 (1-10 µm, platelet, α -phase) reinforced	
	porcelain ceramics; (a) D13 and (b) D14 .	66
4.4	SEM micrographs of Al ₂ O ₃ (0.1-0.5 μ m, irregular-shaped, α -phase)	
	reinforced porcelain ceramics; (a) D15 and (b) D17 .	67
4.5	SEM micrographs of Al_2O_3 (a mixture of 1-10 μ m platelet, 0.1-1	
	μ m irregular and 0.1-0.5 μ m irregular; α -phase) reinforced porcelain	
	ceramics; (a) D18 and (b) D19 .	68
4.6	SEM micrographs of Al_2O_3 (10-100 nm, fibrous-shaped, γ -phase)	
	reinforced porcelain ceramics; (a) D20 and (b) D21 .	69
4.7	Impression of a Vickers indenter producing symmetric cracks,	
	where the cracks are propagating along the glassy phase of the	
	matrix. The crack patterns are propagating normally to the	
	orientation of the crystalline reinforced phase.	70

	Page
SEM micrographs of (a) D14 , (b) D17 , (c) D19 and (d) D21 ;	
bridging I a branch of the intergranular crack is propagating	
through a glassy phase, ⁽²⁾ transgranular cracking through the grain	
of crystalline reinforced phase and ③ microcracks are visible in the	
glassy matrix and at the interface between particles and glass.	71
Weibull plots of uniaxial flexure strength data for Al ₂ O ₃ -reinforced	
porcelain ceramics.	78
The cumulative Weibull plots of probability of failure data for	
Al ₂ O ₃ -reinforced porcelain ceramics.	78
X-ray diffraction patterns of (a) pure dental porcelain ceramic (D11)	
and $Al_2O_3-M_xO_y$ reinforced porcelain ceramics; (b) D22, (c) D23	
and (d) D24 .	86
X-ray diffraction patterns of Al ₂ O ₃ -M _x O _y reinforced porcelain	
ceramics; (a) D25 , (b) D26 and (c) D27 .	87
SEM micrographs of Al ₂ O ₃ - M _x O _y (TiO ₂ , MgO) reinforced porcelain	
ceramics; (a) D22 , (b) D23 and (c) D24 .	89
SEM micrographs of Al_2O_3 (10-100 nm, fibrous-shaped, γ -phase) -	
ZnO reinforced porcelain ceramics; (a) D25 , (b) D26 and (c) D27 .	90
Optical micrograph of asymmetric cracks from the corners of an	
indentation of composite materials in this section with propagating	
of cracks along the glassy matrix phase and retarded (non-directly	
line) with the crystalline reinforced phase (arrows).	91
	 SEM micrographs of (a) D14, (b) D17, (c) D19 and (d) D21; bridging ① a branch of the intergranular crack is propagating through a glassy phase, ② transgranular cracking through the grain of crystalline reinforced phase and ③ microcracks are visible in the glassy matrix and at the interface between particles and glass. Weibull plots of uniaxial flexure strength data for Al₂O₃-reinforced porcelain ceramics. The cumulative Weibull plots of probability of failure data for Al₂O₃-reinforced porcelain ceramics. X-ray diffraction patterns of (a) pure dental porcelain ceramic (D11) and Al₂O₃-M_xO_y reinforced porcelain ceramics; (b) D22, (c) D23 and (d) D24. X-ray diffraction patterns of Al₂O₃-M_xO_y reinforced porcelain ceramics; (a) D25, (b) D26 and (c) D27. SEM micrographs of Al₂O₃ (10-100 nm, fibrous-shaped, γ-phase) - ZnO reinforced porcelain ceramics; (a) D23, (10-100 nm, fibrous-shaped, γ-phase) - ZnO reinforced porcelain ceramics; (a) D25, (b) D23 and (c) D24. SEM micrographs of Al₂O₃ (10-100 nm, fibrous-shaped, γ-phase) - ZnO reinforced porcelain ceramics; (a) D25, (b) D26 and (c) D27. Optical micrograph of asymmetric cracks from the corners of an indentation of composite materials in this section with propagating of cracks along the glassy matrix phase and retarded (non-directly line) with the crystalline reinforced phase (arrows).

Figure		Page
4.16	SEM micrographs of (a) D22 , (b) D23 , (c) D24 and (d) D27 ;	
	bridging 1 a branch of the intergranular crack is propagating	
	through a glassy phase, ⁽²⁾ transgranular cracking through the grain	
	of crystalline reinforced phase and ③ microcracks are visible in the	
	glassy matrix and at the interface between particles and glass.	92
4.17	Weibull plots of flexure strength data for Al ₂ O ₃ -M _x O _y reinforced	
	porcelain ceramics.	99
4.18	The cumulative Weibull plots of probability of failure data for	
	Al ₂ O ₃ -M _x O _y reinforced porcelain ceramics.	99
4.19	The comparative all flexural strength and porosity data of (a) Al_2O_3	
	and (b) Al_2O_3 - M_xO_y reinforced porcelain ceramics.	105
5.1	X-ray diffraction patterns of (a) dental porcelain ceramic (D11) and	
	TiO ₂ reinforced porcelain ceramics; (b) D28 , (c) D29 and (d) D30 .	107
5.2	SEM micrographs of TiO ₂ (0.2-0.5 μ m, irregular-shaped) reinforced	
	porcelain ceramics; (a) D28, (b) D29 and (c) D30.	109
5.3	SEM micrographs of TiO ₂ (50-200 nm, whisker-shaped) reinforced	
	porcelain ceramics; (a) D31, (b) D32 and (c) D33.	110
5.4	SEM micrographs of (a) the crack patterns generated by Vickers	
	indentations which are propagating along the glassy phase of the	
	matrix and made non-directly line (arrows), (b) D34 and (c) D36;	
	bridging $ extsf{D}$ intergranular cracks, $ ilde{ extsf{Q}}$ transgranular crack and $ ilde{ extsf{3}}$	
	microcracks.	111

xviii

Figure		Page
5.5	Weibull plots of uniaxial flexure strength data for TiO ₂ -reinforced	
	porcelain ceramics.	118
5.6	The cumulative Weibull plots of probability of failure data for TiO ₂ -	
	reinforced porcelain ceramics.	118
5.7	X-ray diffraction patterns of (a) dental porcelain ceramic (D11) and	
	TiO_2 -Fe ₂ O ₃ reinforced porcelain ceramics; (b) D34 , (c) D35 and (d)	
	D36.	124
5.8	SEM micrographs of TiO ₂ (0.2-0.5 μ m, irregular-shaped) and Fe ₂ O ₃	
	reinforced porcelain ceramics; (a) D34, (b) D35 and (c) D36.	126
5.9	SEM micrographs of TiO ₂ (50-200 nm, whisker-shaped) and Fe_2O_3	
	reinforced porcelain ceramics; (a) D37 , (b) D38 and (c) D39 .	127
5.10	SEM micrographs of (a) the crack patterns generated by Vickers	
	indentations which are propagating along the glassy phase of the	
	matrix and made non-directly line (arrows), (b) D37 and (c) D39;	
	bridging $ extsf{0}$ intergranular cracks, $ extsf{0}$ transgranular cracks and $ extsf{3}$	
	microcracks	128
5.11	Weibull plots of uniaxial flexure strength data for TiO_2 -Fe ₂ O ₃	
5.12	reinforced porcelain ceramics. The cumulative Weibull plots of probability of failure data for TiO_2 -	135
	Fe ₂ O ₃ reinforced porcelain ceramics.	135
5.13	The comparative all flexural strength and porosity data of (a) TiO_2	
	and (b) TiO_2 -Fe ₂ O ₃ reinforced porcelain ceramics.	141

ABBREVIATIONS AND SYMBOLS

ANOVA	Analysis of Variance
ASTM	American Society for Testing Materials
cm	centimeter
EDX	Energy Dispersive X-ray Spectrometry
g	gram
GPa	gigapascal
g/cm ³	gram per cubic centimeter
ISO	International Organization for Standardization
JCPDS	Joint Committee for Powder Diffraction Standards
К	Kelvin
<i>K</i> _{IC}	fracture toughness
kV	kilovolt
m	meter
m	Weibull moduli
mA	miliampare
mmyrig	millimeter by Chiang Mai University
MPa	megapascal
Ν	Newton
nm	nanometer
pm	picometer

XX



ลิขสิทธิ์มหาวิทยาลัยเชียงใหม่ Copyright[©] by Chiang Mai University All rights reserved