

TABLES OF CONTENTS

	Page
ACKNOWLEDGEMENTS	iii
ABSTRACT (ENGLISH)	v
ABSTRACT (THAI)	vii
LIST OF TABLES	xiii
LIST OF FIGURES	xiv
CHAPTER 1 INTRODUCTION	1
1.1 Overview	1
1.2 Objective of this work	2
CHAPTER 2 LITERATURE REVIEWS	
2.1 Electrical properties of materials	3
2.1.1 Conduction and carrier	3
2.1.2 Metals and insulators	4
2.1.3 Semiconductor	5
2.1.4 Intrinsic semiconductor	7
2.1.5 Extrinsic semiconductor	8
2.1.6 p-n junction	11
2.1.7 Metal-semiconductor contact	13
2.2 Optical properties of materials	17
2.2.1 Refraction	19

	Page
2.2.2 Reflection	19
2.2.3 Transmission	20
2.2.4 Absorption	20
2.2.5 Scattering	21
2.2.6 Emission	21
2.3 Transparent conducting oxide films	23
2.4 Photocatalytic activity of semiconductor	24
2.4.1 Definition of pH	28
2.4.2 Metal doping semiconductor photocatalyst	30
2.4.3 Coupled Ssemiconductor photocatalyst	31
2.5 Solar irradiation on earth	32
2.6 Zinc oxide	35
2.7 Titanium dioxide	37
2.8 Surface tension (γ)	39
2.9 Enhance field factor (β)	41
2.10 Literature review	43
CHAPTER 3 EXPERIMENTAL PROCEDURES	46
3.1 Chemical substances	46
3.2 Instruments	47
3.3 Sample preparation	48
3.4 Sample characterization	56

	Page
CHAPTER 4 RESULTS AND DISCUSSION	70
4.1 Vertical tips alignment sparking	70
4.1.1 Effect of electrode polarity	70
4.1.2 Effect of tip shape	71
4.1.3 Effect of sparking voltage	73
4.2 Horizontal tips alignment sparking ZnO nanoparticles thin films	75
4.2.1 Surface morphology as imaged by AFM	76
4.2.2 Surface morphology and cross-section as imaged by SEM	77
4.2.3 X-ray diffraction of sparking ZnO	80
4.2.4 UV-vis spectroscopy	81
4.2.5 Raman spectroscopy	88
4.2.6 Ionoluminescence	90
4.2.7 Electrical resistivity	93
4.2.8 Effect of pressure on the size of nanoparticle	94
4.3 ZnO-TiO ₂ coupled nanoparticle thin film	96
4.3.1 Surface morphology and cross-section as imaged by SEM	97
4.3.2 X-ray diffraction	101
4.3.3 Raman spectroscopy	103
4.3.4 Ionoluminescence	104

	Page
4.3.5 UV-vis spectroscopy	105
4.3.6 Photocatalytic activity	107
4.4 Sparking ZnO using square wave pulse	109
4.4.1 Surface morphology and cross-section as imaged by SEM	109
4.4.2 I-V curve characteristic	110
4.5 Nucleation mechanism of sparking process	112
CHAPTER 5 CONCLUSION AND SUGGESTION	116
5.1 ZnO nanoparticle thin films	116
5.2 ZnO-TiO ₂ coupled nanoparticle thin films	117
5.3 Sparking ZnO using square wave pulse	118
REFERENCE	119
APPENDIX	126
VITA	147

LIST OF TABLES

Table	Page
4.1 The Tauc' plot for estimated band gap of ZnO films as shown in fig. 4.14, using $\alpha = \frac{1}{t} \ln \frac{(1-R)}{T}$ where t is film thickness, R is reflection and T is transmittance.	85
4.2 The Tauc's plot for estimation of the energy gaps of the films as shown in fig. 4.15, $\alpha = \frac{(1-C)^2}{C}$, where $C = 10^{-A}$, A is absorbance.	86
4.3 The Tauc's plot for estimation of the energy gaps of the films as shown in fig. 4.16, $\alpha = \ln \frac{1}{T}$, where T is the transmittance.	87
4.4 The band gaps of ZnO samples estimated from different absorption coefficients (α): t is the film thickness (nm), R is the reflectance, T is the transmittance, C is the reflection coefficient ($C = 10^{-A}$) and A is the absorbance.	88

LIST OF FIGURES

Figure	Page
2.1 Band gap of materials (a) in conductor the conduction band and the valance band overlap slightly (b) in semiconductor the conduction band and the valance band are separated (c) in insulator the conduction band and the valance band are widely separate.	6
2.2 (a) The atoms of Si have four valence electrons which are bound together to form tetrahedral crystals, where each atom has four nearest neighbours, and thermal energy can create few electron hole pairs resulting in weak conduction and (b) energy gap (E_g) with Fermi level at the middle.	8
2.3 (a) Schematic diagram shows n-type silicon (doped with phosphorous), and (b) energy level diagram of p-type semiconductor.	9
2.4 (a) Schematic diagram shows p-type silicon (doped with boron), and (b) energy level diagram of p-type semiconductor.	10
2.5 Formation of the p-n junction which shows (a) holes and electrons diffuse across junction, (b) depletion layer, and (c) energy band diagram for a p-n junction at thermal equilibrium.	11
2.6 Semiconductor devices e.g. (a) diode, (b) transistor, and (c) Light Emitting Diode (LEDs)	13

Figure	Page
2.7 Energy band of the metal and n-type semiconductor, $\Phi_M > \Phi_S$, before (a) and after (b) contact is made.	14
2.8 Metal-semiconductor contact with two polarities: (a) reverse bias and (b) forward bias. The number of electron that flow in both directions and the net current is indicated by the range of the arrows. The potential barriers are marked by heavy lines	15
2.9 (a) Characteristic of rectifier (b) Voltage versus time curves to demonstrate behaviour of and alternating current and a current for which the negative voltage has been eliminated	16
2.10 Ohmic contact between metal and n-type semiconductor ($\Phi_M < \Phi_S$), (a) metal and semiconductor are separate (b) metal and semiconductor are in the contact and (c) current voltage characteristic	17
2.11 The electromagnetic spectrum	18
2.12 Diagram of reflection, refraction and transmission of light (refractive index, $n_2 > n_1$).	19
2.13 Upon irradiation of semiconductor photocatalyst by ultra band gap light, the semiconductor undergoes photo-excitation. The electron and the hole that result can follow one of several pathways: (a) electron–hole recombination on the surface; (b) electron–hole recombination in the bulk reaction of the semiconductor; (c) electron acceptor A is reduced by photogenerated electrons; and (d) electron donor D is oxidised by photogenerated holes.	26

Figure	Page
2.14 Energy structures of various photoconductors	28
2.15 Semiconductor photocatalyst particle with adding noble metal for trapped electron.	30
2.16 Design of semiconductor-metal nanocomposites using couple Geometry	31
2.17 The proposed mechanism of photocatalytic ZnO-TiO ₂ composite.	32
2.18 The solar radiation spectrum for direct light at both the top of the Earth's atmosphere and at sea level	33
2.19 Angle of the sunlight	34
2.20 Hexagonal wurtzite structure of ZnO. O atoms are shown as large white spheres, Zn atoms as smaller black spheres. One unit cell is outlined for clarity.	36
2.21 Unit cell of rutile (a) and (b) anatase phase of TiO ₂ , the red circles are titanium and the white circles are oxygen. Both forms are tetragonal with lattice constants a and c of 0.4594 nm and 0.2958 nm for rutile and 0.3785 nm and 0.9514 nm for anatase.	39
2.22 Diagram of force on molecules of liquid.	40
2.23 Geometry of an individual emitter in diode system. L height of emitter, r radius of curvature; Θ -tip semi-angle for cone form.	42
3.1 Optical microscope images of (a) the conical tip, (b) the sharp tip and (c) the dull tip.	48
3.2 Schematic diagram of vertical tip alignment sparking.	49

Figure	Page
3.3 Capacitor discharge sparking apparatus: 1 Power supply, 2 Capacitor 0.1 μF , 3 vertical slider, 4 Switch and 5 substrate base.	50
3.4 Schematic diagram of the double tip sparking apparatus	51
3.5 Capacitor discharge sparking apparatus: 1 Power supply, 2 Capacitor 0.035 μF , 3 Switch, and 4 substrate	52
3.6 Schematic diagram of square wave pulse sparking	54
3.7 Square wave pulse sparking apparatus: 1 voltage amplifier, 2 function generator, 3 oscilloscope, 4 pump and 5 vacuum chamber	55
3.8 Square wave pulse of 100 Hz, 50% duty cycle.	55
3.9 Principle of the AFM	57
3.10 Nanoscope IIIa 5.12r3 software	58
3.11 Nanoscope IIIa 5.12r3 software for estimate the height and diameter of the nanoparticles.	58
3.12 Atomic Force Microscope	59
3.13 Field Emission Scanning Electron Microscope	60
3.14 X-ray Diffraction	61
3.15 X-ray Diffractrometer	62
3.16 UV-visible spectrophotometer	63
3.17 Schematic diagram of the absorption transitions between direct parabolic bands	64
3.18 Raman scattering	66
3.19 Raman spectrometer	67

Figure	Page
3.20 Tandetron accelerator	68
3.21 Schematic representation of an I-V curve measurement	69
4.1 Optical microscope images of (a) the anode tip and (b) the cathode tip after the sparking occurred.	71
4.2 AFM images of ZnO NPs prepared by sparking once at 4 kV from (a) the conical tip (b) the sharp tip and (c) the dull tip.	72
4.3 The mean heights and the mean diameters of ZnO NDs prepared by sparking once from the different tip shapes at 4 kV.	73
4.4 AFM images of ZnO NPs prepared by sparking once from sharp tip at (a) 2 kV (b) 4 kV and (c) 6 kV	74
4.5 The mean heights and the mean diameters of ZnO NDs prepared by sparking once from the sharp tip at 2, 4 and 6 kV.	75
4.6 AFM images of ZnO thin films (a) the as-deposited sample and the samples annealed at (b) 400 °C, (c) 600 °C, and (d) 800 °C.	76
4.7 The grain size and the surface roughness as functions of the annealing temperature.	77
4.8 SEM images of as-deposited ZnO nanoparticles thin films	78
4.9 SEM cross section images of the ZnO films sparking number of (a) 50 times, (b) 100 times, (c) 150 times and (d) 200 times.	79
4.10 The thickness of the ZnO thin films as a function of the sparking numbers.	80

Figure	Page
4.11 XRD spectra of ZnO thin films of (a) the as-deposited sample and the samples annealed at (b) 400 °C, (c) 600 °C, and (d) 800 °C.	81
4.12 Optical transmittance spectra of ZnO thin films of (a) the as-deposited sample and the samples annealed at (b) 400 °C, (c) 600 °C, and (d) 800 °C.	82
4.13 Optical absorption spectra of ZnO thin films of (a) the as-deposited sample and the samples annealed at (b) 400 °C, (c) 600 °C, and (d) 800 °C.	83
4.14 The Tauc's plot for estimation of the energy gaps of the films, $\alpha = \frac{1}{t} \ln \frac{(1-R)}{T}$, where t is film thickness, R is reflectance and T is the transmittance.	84
4.15 The Tauc's plot for estimation of the energy gaps of the films, $\alpha = \frac{(1-C)^2}{C}$, where C = 10 ^{-A} , A is absorbance.	86
4.16 The Tauc's plot for estimation of the energy gaps of the films, $\alpha = \ln T$, where T is the transmittance.	87
4.17 Raman spectra of ZnO thin films of ZnO thin films of (a) the as-deposited sample and the samples annealed at (b) 400 °C, (c) 600 °C, and (d) 800 °C.	89
4.18 Ionoluminescence spectra of ZnO thin films of (a) the as-deposited sample and the samples annealed at (b) 400 °C, (c) 600 °C, and (d) 800 °C.	90

Figure	Page
4.19 Scheme of the UV emission and the three visible radiative emission processes.	92
4.20 Schematic diagram showing the effects of non-radiative centres and the various filling levels of radiative centres on the intensity and peak wavelength of green emission. In the energy diagram, dark filled areas represent the population of electrons contributing to radiative green emission, and the lengths of the down arrows represent energy of green emission.	93
4.21 The electrical resistivity and the intensity of orange-red emission of the ZnO films, as functions of the annealing temperature.	94
4.22 AFM images of ZnO nanoparticles thin films prepared at pressure (a) 160 torr, (b) 360 torr, (c) 560 torr and (d) 760 torr.	95
4.23 The nanoparticle size of the ZnO samples as a function of the sparking pressure.	96
4.24 (a) SEM images of the as-deposited ZnO-TiO ₂ thin films and, (b) and (c) are EDS mapping of zinc and titanium, of (a), respectively.	98
4.25 EDX spectra of (a) cathode titanium and (b) anode titanium.	99
4.26 SEM cross section images of the ZnO-TiO ₂ films sparking number of (a) 100 times, (b) 200 times, (c) 300 times and (d) 400 times.	100
4.27 The thickness of the ZnO-TiO ₂ thin films as a function of the sparking numbers.	101

Figure	Page
4.28 XRD patterns of the as-deposited and the annealed at 600 °C ZnO-TiO ₂ films.	102
4.29 Raman spectra of the as-deposited and the annealed at 600 °C ZnO-TiO ₂ nanocomposited thin films.	103
4.30 IL spectrum of the as-deposited and the annealed ZnO-TiO ₂ films	104
4.31 UV-vis transmittance spectrum of the annealed ZnO-TiO ₂ films.	105
4.32 UV-vis absorbance spectrum of the annealed ZnO-TiO ₂ films.	106
4.33 The plot of $(\alpha hv)^2$ versus $h\nu$ for estimation of the energy gap	107
4.34 UV-vis adsorption spectra of pure 10 μ M methylene blue solution and the solution with dipping ZnO, TiO ₂ and ZnO-TiO ₂ film under sunlight irradiation for 75 min.	108
4.35 (a) SEM image of square wave pulse sparking ZnO and (b) cross-section of fig. (a).	110
4.36 I-V curve of sparking ZnO based electroluminescence device as a function of annealing time.	111
4.37 Schematic diagram of the nucleation mechanism of ZnO nanoparticle deposited by the sparking method.	114
4.38 Voltage distribution as function of distance into spark	115