

REFERENCES

- [1] O. C. Montero-Hernandez and P. N. Enjeti, "Ride-Through for Critical Loads," *Industry Applications*, Vol. 8, No. 6, pp. 45-53, November/December 2002.
- [2] R. Zhang, D. Boroyevich, V. H. Prasad, H. Mao, F. C. Lee, and S. Dubovsky, "A three-phase inverter with a neutral leg with space vector modulation," *IEEE Proceedings of Power Electronics Specialists Conference*, pp.857-863, 1997.
- [3] V. H. Prasad, D. Boroyevich, and R. Zhang, "Analysis and comparison of space vector modulation schemes for four-leg voltage source inverter," *IEEE Proceedings of Power Electronics Specialists Conference*, pp.864-871, 1997.
- [4] C. Zhan, V. K. Ramachandaramurthy, A. Arulampalam, C. Fitzer, S. Kromlidis, M. Barnes, and N. Jenkins, "Dynamic Voltage Restorer Based on Voltage-Space-Vector PWM Control," *IEEE Trans. on Industry Applications*, vol. 37, pp.1855-1863, Nov./Dec. 2001.
- [5] C. Zhan, A. Arulampalam, and N. Jenkins, "Four-Wire Dynamic Voltage Restorer Based on a Three-Dimensional Voltage Space Vector PWM Algorithm," *IEEE Trans. on Power Electronics*, vol. 18, pp.1093-1102, July 2003.
- [6] G.F. Reed, M. Takeda, and I. Iyoda, "Improved Power Quality Solutions Using Advanced Solid-State Switching and Static Compensation Technologies," in *Proc. IEEE Power Engineering Society 1999 Winter Meeting*, vol. 2, pp. 1132-1137, 1999.
- [7] S. M. Schoenung, W. R. Meier, R. L. Fagaly, M. Heiberger, R. B. Stephens, J. A. Leuer and R. A. Guzman, "Design, Performance, and Cost Characteristics of High Temperature Superconducting Magnetic Energy Storage," *IEEE Trans. on Energy Conversion*, vol. 8, pp.33-39, Mar. 1996.
- [8] W. Allen, "A Hybrid Static/Rotary UPS System," *IEEE Trans. on Industry Applications*, vol. 28, pp.541-545, May/June 1992.
- [9] S. Samineni, B.K. Johnson, H.L. Hess, and J.D. Law, "Modeling and analysis of a flywheel energy storage system for voltage sag correction," *IEEE Inter. Conf. on Electric Machines and Drives Conference (IEMDC'03)*, June 2003.
- [10] A. V. Jouanne, P. N. Enjeti, and B. Banerjee, "Assessment of Ride-Through Alternatives for Adjustable-Speed Drives," *IEEE Trans. on Industry Applications*, vol. 35, pp.908-916, July/Aug. 1999.
- [11] M. A. Perales, M. M. Prats, R. Portillo, J. L. Mora J. I. Leon and L. G. Franquelo, "Three-Dimensional Space Vector Modulation in abc Coordinates for Four-Leg Voltage Source Converters," *IEEE Power Electronics Letters*, vol. 1, No 4, Dec 2003.
- [12] Rui Wu, Donghua Chen, Shaojun Xie "A Three-Dimensional Space Vector Modulation Algorithm in ABC Coordinate Implemented by a FPGA," *Industrial Electronics Society, IECON 2005, 31st Annual Confererence of IEEE*, 6-6 Nov. 2005.
- [13] European standard EN 50160 ICS 29.020, November 1994.

- [14] Recommended practice for monitoring electric power quality. IEEE Std. 1159-1995.
- [15] D.S. Dorr, "Point of utilization power quality study results," *IEEE Trans. Ind. Applicat.*, vol.31, no. 4, pp. 658-666, July 1995.
- [16] M. H. J. Bollen, *Understanding Power Quality Problems*, New York: IEEE Press, 2000.
- [17] S. W. Middelekauff and E. R. Collins Jr., "System and Customer Impact: Considerations for Series Custom Power Devices," *IEEE Trans. Power Deliv.*, Vol.13, pp. 278-282, Jan.1998.
- [18] Pohjanheimo, P. and Lehtonen, E. (2002). "Equipment Sensitivity to Voltage Sags – Test Results for Contactors, Pcs and Gas Discharge Lamps," *International Conference on Harmonics and Quality of Power*, 2002. Rio de Janeiro, Brazil.
- [19] M. H. J. Bollen and L. D. Zhang, "Analysis of Voltage Tolerance of AC Adjustable-Speed Drives for Three-Phase Balanced and Unbalanced Sags," Paper 4, Session 1 a *IEEE Industrial & Commercial Power Systems Technical Conference*, Sparks-NV, USA, May 1999.
- [20] A. von Jouanne, P. N. Enjeti and B. Banerjee, "Assesment of ride-through alternatives for adjustable speed drive," *IEEE Trans. Ind. Applicat.*, vol. 35, pp. 908-916, July/Aug. 1999.
- [21] A. van Zyl and R. Spee, "Short term energy storage for ASD ride-through," in *Conf. Rec. IEEE-IAS Annu. Meeting*, vol. 2, Oct. 1998, pp. 1162-1167.
- [22] D. G. Fink and H. W. Beaty, *Standard Handbook for Electrical Engineers, Section II*, New York:McGraw-Hill, 1993.
- [23] Maxwell Technologies Systems Division DC Bus Ride-Through System, Maxwell Technologies, San Diego, CA, Produc Brochure, Oct. 1998.
- [24] PRI Inc. and PRI Development Co., Pridtronics Brochure, Ver. 7.8 , Oct 7, 1997 <http://www.trinityflywheel.com>
- [25] S. M. Schoenung, "Power Conditioning Technology Assessment for the Power Quality Park," *Electric Power Research Institute*, Palo Alto, CA. EPRI Final Report WO-4897-04, Apr. 1997.
- [26] Piller website, 2008. [Online]. Availabel : www.piller.com
- [27] Active Power website, 2008. [Online]. Available: www.activepower.com
- [28] R. S. Weissbach, G. G. Karady, and R. G. Farmer, "Dynamic voltage compensation on distribution feeders using flywheel energy storage," *IEEE Trans. Power Delivery*, vol. 14-2, pp. 465-471, April 1999.
- [29] C. J. Melhorn, A. Braz, P. Hofman, R. J. Mauro, "An evaluation of energy storage techniques for improving ride-through capability for sensitive customers on underground netwokds," *IEEE Trans. Ind. Applicat.*, vol. 33, pp. 1083-1095, Jul-Aug. 1997.
- [30] J. Lamoreee, L. Tang, C. DeWinkel, and P. Vinett, "Description of a micro-smes system for protection of critical customer facilities," *IEEE Transactions on Power*

Delivery, vol. 9, No. 2, pp. 984-992, April 1994.

- [31] V. Karasik, K. Dixon, C. Weber, B. Batchelder, G. Campbell, and P. Ribeiro, "SMES for power utility applications: a review of technical and cost considerations," *IEEE Trans. Applied Superconductivity*, vol. 921, pp. 541-546, June 1999.
- [32] American Superconductor website, 2008. [Online]. Available: www.amsuper.com
- [33] O. Montero-Hernandez, P. N. Enjeti, "A fast detection algorithm suitable for mitigation of numerous power quality disturbances," in *Conf. Rec. IEEE-IAS Annu. Meeting*, 2001, pp. 2661-2666.
- [34] S. Kim, P. N. Enjeti, "Control strategies for active power filter in three-phase four-wire systems," in *Proc. IEEE APEC 2000*. pp. 420-426.
- [35] W. E. Brumsickel, R. S. Schneider, G. A. Luckjiff, D. M. Divan, and M. F. McGranahan, "Dynamic sag correctors: Cost Effective industrial power line conditioning," in *Conf. Rec. IEEE-IAS Annu. Meeting*, 1999, vol. 2. pp. 1339-1344.
- [36] P. T. Cheng, R. Lasseter, D. Divan, "Dynamic Series Voltage Restoration for Sensitive Loads in Unbalanced Power Svstems." US Patent No. 5.883.769. 1999.
- [37] G. F. Reed, M. Takeda, and I. Iyoda, "Improved power quality solutions using advanced solid-state switching and static compensation technologies," in *Conf. Rec. IEEE-PES Winter Meeting*, 1999, volt.2, pp. 1132-1137.
- [38] G. V. Venkataramanan, B. Johnson, "A pulse width modulated power line conditioner for sensitive load centers," *IEEE Transactions on Power Delivery*, vol. 12, NO. 2, pp. 844-849, April 1997.
- [39] A. V. Jouanne, P. N. Enjeti, and B. Banerjee, "Assessment of Ride-Through Alternatives for Adjustable-Speed Drives," *IEEE Trans. on Industry Applications*, vol. 35, pp.908-916, July/Aug. 1999.
- [40] C.Zhan, C. Fitzer, V.K. Ramachandaramurthy, A. Arulampalam, M. Barnes, N. Jenkins "Software Phase-Locked Loop applied to Dynamic Voltage Restorer(DVR)," *IEEE Power Engineering Society Winter Meeting* , Vol. 3, 29 Jan – 1 Feb 2001.
- [41] Dogan Ibrahim, *Microcontroller Based Temperature Monitoring and Control*, Newnes, 2002.
- [42] Salem M. Ali, Marian P. Kazmierkowski, "PWM Voltage and Current Control of Four-Leg VSI," *IEEE ISIE 1998*, Vol.1, pp. 196-201, 7-10 July 1998.
- [43] Said El-Barbari, W. Hofmann, "Digital control of a four leg inverter for standalone photovoltaic systems with unbalanced load," *IEEE IECON 2000*, Vol. 1 pp. 729-734, 22-28 Oct. 2000.