

TABLE OF CONTENTS

	Page
ACKNOWLEDGEMENTS	iii
ABSTRACT (THAI)	v
ABSTRACT (ENGLISH)	vii
LIST OF TABLES	xv
LIST OF FIGURES	xvi
 CHAPTER 1 INTRODUCTION	1
1.1 Overview	1
1.2 Objectives of this work	4
1.3 Methodology and Analyses	4
 CHAPTER 2 BACKGROUND AND LITERATURE REVIEW	7
2.1 Piezoelectric ceramics	7
2.1.1 Background and basis for piezoelectricity theory	7
2.1.2 Piezoelectricity in ferroelectric ceramics	8
2.1.3 Hysteresis loops	12
2.1.4 Poling	16
2.1.5 Lead zirconate titanate, PZT	18
2.2 Organic ferroelectric materials	24
2.2.1 Polyvinylidene fluoride films	25

2.2.2 Structure and piezoelectricity of PVDF	25
2.3 Portland cement	32
2.3.1 Portland cement: general	32
2.3.2 Compound composition of anhydrous Portland cement	33
2.3.3 The hydration of Portland cement	34
2.3.4 Rate of hydration	37
2.3.5 Volume change during hydration	38
2.3.6 Summary of the hydration of Portland cement	39
2.3.7 Aggregate and the aggregate/cement bond	40
2.3.8 Aggregate particle characteristics	41
2.4 Carbon graphite	42
2.5 Composite materials	44
2.5.1 Properties of composite materials	47
2.5.2 Connectivity	49
2.5.3 Piezoelectric composites	51
2.5.4 Percolation in composites	53
2.6 Requirement and background of piezoelectric-cement based composites	55

CHAPTER 3 EXPERIMENTAL PROCEDURE 75

3.1 Materials and Fabrication	75
3.1.1 Piezoelectric ceramics fabrication	75
3.1.2 Lead zirconate titanate, PZT	78
3.1.3 Composite fabrications	79
3.1.4 Electrode making	82

3.2 Poling process	82
3.3 Physical and Microstructure characterization	83
3.3.1 X-ray diffractometry	83
3.3.2 Scanning electron microscopy, SEM	84
3.3.3 Piezoresponse Force microscopy, PFM	85
3.4 Electrical properties measurements	88
3.4.1 Dielectric measurement	88
3.4.2 Ferroelectric measurement	89
3.4.3 Piezoelectric measurement	90
CHAPTER 4 RESULTS AND DISCUSSION	92
Part I: 0-3 connectivity cement-based piezoelectric ceramic composite	92
4.1 Phase formation	92
4.2 Dielectric properties	93
4.2.1 Effect of piezoelectric ceramic content	93
4.2.2 Effect of particle size of piezoelectric ceramic	97
4.3 Piezoelectric properties	98
4.3.1 The degree of poling	98
4.3.2 Effect of PZT content on piezoelectric properties	101
4.3.3 Effect of PZT particle size on piezoelectric properties	103
4.3.4 Effect of hydration ages on piezoelectric properties	105
4.4 Ferroelectric properties	108
4.4.1 Ferroelectric hysteresis behavior in 0-3 ceramic-cement composites:	108
Effects of frequency and electric field	

4.4.2 Effects of PZT content on ferroelectric hysteresis behavior of 0–3 PZT-Portland cement composites	111
4.5 Interfacial morphology and Microstructure	113
4.5.1 SEM micrograph	113
4.5.2 Domain configurations using PFM	116
4.6 Summary	121
Part II: Effect of third phase on microstructure and properties of PZT-PC composites	124
4.7 Dielectric properties	125
4.7.1 Dielectric properties of PZT-PC composites with added carbon graphite	125
4.7.2 Dielectric properties of PZT-PC composites with added PVDF	128
4.8 Piezoelectric properties	130
4.8.1 Piezoelectric properties of PZT-PC composites with added carbon graphite	130
4.8.2 Piezoelectric properties of PZT-PC composites with added PVDF	131
4.8.3 Effect of hydration ages on piezoelectric properties	135
4.9 Ferroelectric properties	138
4.9.1 Ferroelectric properties of PZT-PC composites with added carbon graphite	138
4.9.2 Ferroelectric properties of PZT-PC composites with added PVDF	139
4.10 Interfacial morphology and Microstructure	141

4.10.1 Microstructure of PZT-PC composites with added PVDF	141
4.11 Summary	149
CHAPTER 5 CONCLUTIONS AND SUGGESTIONS FOR FURTHER WORK	151
5.1 Conclusions	151
5.2 Suggestions for further work	153
REFERENCES	155
VITA	167

LIST OF TABLES

Table	Page
2.1 Piezoelectric and pyroelectric coefficients of polymer films at room temperature	25
2.2 Typical oxide and compound compositions of Portland cements	34
2.3 Depth of hydration product (μm) on 30-55 μm grains	37
2.4 Examples of product properties	49
2.5 The basic properties of the PZT ceramics, cement paste and concrete	58
2.6 Properties of composites	64
2.7 Piezoelectric parameter of the 0-3 nano-PZT/cement composites	65
2.8 The electromechanical coupling properties of the composites	68
3.1 Specifications of the starting materials used in this study	76
3.2 Composition of ceramic- cements composites	80
3.3 Composition of ceramic- cements composites with third phase adding	80
3.4 Poling condition of the ceramic-cement composites	83
5.1 Electrical properties of cement piezoelectric composites	153

LIST OF FIGURES

Figures	Page
1.1 Flow chart of preparation and characterization of cement-based PZT composites	6
2.1 Piezoelectric effects in ferroelectric ceramics	10
2.2 Typical hysteresis loops from various ferroelectric ceramics: (a) BaTiO ₃ capacitor, (b) soft (easily switchable) PZT, (c) PLZT relaxor, and (d) PSZT antiferroelectric material	13
2.3 Hysteresis loops and longitudinal strain curves for (a) ferroelectric memory ceramic and (b) SFE nonmemory relaxor ceramic	15
2.4 Schematic drawing of the poling process for piezoelectric ceramics	17
2.5 Morphotropic phase boundary in the Pb(Zr,Ti)O ₃ system	18
2.6 Composition dependence of dielectric constant and electromechanical coupling factor in PZT ceramic	20
2.7 P–E loops with increasing peak field strengths at 50 Hz for a ceramic Ferroelectric	22
2.8 (a) variations, at room temperature of piezoelectric coefficient d_{ij} and (b) remanent polarization P_r with composition of PZT near the morphotropic phase boundary	23

2.9	Schematic illustration showing random stacks of amorphous and crystal lamellae in PVDF polymer. Figure (a) represents the morphology after the film is melt cast; (b) is after orientation of the film by mechanically stretching to several times its original length; (c) is after depositing metal electrodes and poling through the film thickness	27
2.10	Elementary cell of the PVDF crystal structure in phase β	29
2.11	Projections of four crystal structures of PVDF viewed along the molecular axes. Dipole moments are shown by arrows. Large circles represent fluorine atoms, small circles represent carbon atom; hydrogen atom are not shown	30
2.12	Schematic picture of a liquid-crystal stack showing the chain and dipole directions in the crystals	31
2.13	The strength developed by Portland cement compounds	35
2.14	The interface between the aggregate and cement paste	40
2.15	The structure of graphite	43
2.16	Chart illustrating design considerations for optimizing the performance of solid state devices. The task of the materials engineer is to find the materials, processing methods, and connectivity patterns which maximize the figure of merit	46
2.17	Connectivity patterns in a diphasic composite system	50
2.18	The series (a) and parallel (b) model used in estimating the piezoelectric effect of diphasic solid	52

2.19	Site percolation on the square lattice: The small circles represent the occupied sites for three different concentrations. Nearest-neighbor cluster sites are connected by lines representing the bonds. Filled circles are used for finite clusters, while open circles mark the large infinite cluster	54
2.20	Aging influence on piezoelectric factor (d_{33}) for cement-based piezoelectric composites and ceramic/polymer composites	65
2.21	The piezoelectric strain factor (d_{33}) of the composites as a function of the poling field E	66
2.22	The piezoelectric strain factor (d_{33}) of the composites as a function of the poling time t	66
2.23	The piezoelectric strain factor (d_{33}) of the composites as a function of the poling temperature T	67
2.24	Dependence of the piezoelectric constants on the content of PZT	67
2.25	Effect of PLN particle size on piezoelectric properties of the composites; (a) Pieoelectric strain factor (d_{33}), and (b) Pieoelectric voltage factor (g_{33})	68
2.26	The interfacial bonding of the PZT ceramic particle and the cement matrix	69
2.27	The influence of ages on the piezoelectric strain factor (d_{33}) constant of the composites	69
2.28	Variation of piezoelectric strain constant (d_{33}) (a), and piezoelectric voltage constant (g_{33}) (b), of the composites with carbon black content	70

2.29	Variation of dielectric constant (a), and dielectric loss (b), of the composites with carbon black content	71
2.30	Dependence of the piezoelectric strain factor (d_{33}) of the carbon black /PZT/cement composites on the poling field (a), and on the poling duration	72
2.31	Variations of piezoelectric strain factor (d_{33}) of the composites with the aging time	73
2.32	Dependence of (a); the dielectric constant (ϵ_r) and dielectric loss ($\tan \delta$) and (b); the piezoelectric strain factor (d_{33}) and piezoelectric voltage factor (g_{33}) of the carbon black/PZT/cement composites on the carbon content	74
3.1	Mixing and calcination processes for powder and ceramic preparation	77
3.2	Two-stage processing route for PZT powders and ceramic	78
3.3	The model for fabricating cement-based piezoelectric ceramic composites samples	81
3.4	The curing chamber	81
3.5	X-ray diffractometer (Philips Model X-pert)	84
3.6	Scanning electron microscope (SEM, JEOL JSM-840A, Japan)	85
3.7	The schematic of piezoresponse force microscopy	87
3.8	Piezoresponse force microscope (SPA 400, Seiko Inc., Japan)	88
3.9	The experiment set up for dielectric properties measurements at room temperature	89
3.10	Schematic circuit of Sawyer-Tower Bridge for the observation of P-E characteristics in ferroelectrics	90

3.11	The d_{33} meter model PM25	91
4.1	XRD pattern of PZT-PC composites	93
4.2	Effect of ceramic piezoelectric content on (a) dielectric constant and (b) dielectric loss	94
4.3	Model of composite (a) Series model; (b) Parallel model; (c) Cube model	96
4.4	Relative dielectric constant versus ceramic content	96
4.5	Effect of particle size of ceramic piezoelectric on (a) dielectric constant and (b) dielectric loss	97
4.6	Relationship between the d_{33} and the poling temperature	99
4.7	The effect of poling time on the piezoelectric coefficient (d_{33})	100
4.8	The effect of PZT content on the piezoelectric coefficient (d_{33})	103
4.9	The effect of PZT particle size on the piezoelectric coefficient	104
4.10	The effect of hydration age on the piezoelectric coefficient (d_{33}) of composite for (a) 10 days; (b) 90 days of 30,40,50%PZT; (c) 90 days of 60,70,80,90%PZT; (d) 1 year	106-107
4.11	Effects of electric field (a); and frequency (b); on the ferroelectric (P - E) hysteresis loops of PZT-PC composites (with fixed f of 60 Hz)	110
4.12	Effects of PZT content on the ferroelectric (P - E) hysteresis loops of PZT-PC composites (with fixed f of 20 Hz) of external electric field amplitude at 20kV/cm	112
4.13	SEM micrographs at interfacial zone of PZT-PC composites; (a) magnification 20 $\times$ and 50 $\times$, (b) magnification 500 $\times$ and 1500 $\times$ and (c) magnification 1000 $\times$ and 2000 $\times$	114

4.14 SEM micrographs of PZT-PC composites (a) magnification $\times 500$ and (b) magnification $\times 1,500$	115
4.15 The topography image (a) and the corresponding piezoresponse image (b) for scanning area of $10 \times 10 \mu\text{m}^2$ of Portland cement (PC)	116
4.16 The topography image (a) and the corresponding piezoresponse image (b) for scanning area of $10 \times 10 \mu\text{m}^2$ of Lead zirconate titanate (PZT)	117
4.17 The topography image (a) and the corresponding piezoresponse image (b) for scanning area of $60 \times 60 \mu\text{m}^2$ at interfacial zone of PZT-PC composites	118
4.18 The topography image (a) and the corresponding piezoresponse image (b) for scanning area of $30 \times 30 \mu\text{m}^2$ at interfacial zone of PZT-PC composites	119
4.19 The topography image (a) and the corresponding piezoresponse image (b) for scanning area of $10 \times 10 \mu\text{m}^2$ at interfacial zone of PZT-PC composites	119
4.20 Effect of carbon addition on dielectric properties of PZT-PC composites; (a) dielectric constant; (b) dielectric loss	126
4.21 Model of electrical transport of PZT-PC composites with added carbon	127
4.22 Effect of PVDF addition on dielectric properties of PZT-PC composites; (a) dielectric constant; (b) dielectric loss	129
4.23 The piezoelectric charge coefficient (d_{33}) of PC-PZT composites with various PVDF and carbon graphite additions	130

4.24	The poling period of PC-PZT composites with various PVDF and carbon graphite additions	132
4.25	The dielectric permittivity (ϵ_{33}) of PC-PZT composites with various PVDF and carbon graphite additions	133
4.26	The piezoelectric voltage coefficient (g_{33}) of PC-PZT composites with various PVDF and carbon graphite additions	133
4.27	The effect of hydration age on the piezoelectric charge coefficient (d_{33}) of composite for 30 days of PVDF addition	135
4.28	The effect of hydration age on the piezoelectric voltage coefficient (g_{33}) of composite for 30 days of PVDF addition	136
4.29	The effect of hydration age on the dielectric permittivity (ϵ_{33}) of composite for 30 days of PVDF addition	136
4.30	Effects of carbon graphite content on the ferroelectric (P - E) hysteresis loops of PZT-PC composites (with fixed f of 50 Hz) of external electric field amplitude at 20kV/cm	139
4.31	Effects of PVDF content on the ferroelectric (P - E) hysteresis loops of PZT-PC composites (with fixed f of 50 Hz) of external electric field amplitude at 20kV/cm	140
4.32	SEM micrographs of PVDF powder (a) magnification $\times 3,000$, (b) magnification $\times 10,000$, (c) magnification $\times 20,000$ and (d) EDX spectrum	142
4.33	The topography image for scanning area of (a) $70 \times 70 \mu\text{m}^2$, (b) $30 \times 30 \mu\text{m}^2$, (c) $10 \times 10 \mu\text{m}^2$ of PVDF	143

4.34	The topography image (a) and the corresponding piezoresponse Image, (b) for scanning area of $30 \times 30 \mu\text{m}^2$ at interfacial zone of PZT-PC composites	144
4.35	The topography image (a) and the corresponding piezoresponse image, (b) for scanning area of $10 \times 10 \mu\text{m}^2$ at interfacial zone of PZT-PC composites	145
4.36	SEM micrographs of PZT-PVDF-PC composites (a) magnification $\times 5,500$, (b) magnification $\times 10,000$, (c) magnification $\times 20,000$ and (d) EDX spectrum	146
4.37	The topography image for scanning area of $30 \times 30 \mu\text{m}^2$ (a), (b and c), of PZT-PVDF-PC composite	147
4.38	The corresponding piezoresponse image for scanning area of $30 \times 30 \mu\text{m}^2$ (a), $10 \times 10 \mu\text{m}^2$ (b and c) of PZT-PVDF-PC composite	148