

## TABLE OF CONTENTS

	Page
<b>ACKNOWLEDGEMENTS</b>	iii
<b>ABSTRACT (ENGLISH)</b>	v
<b>ABSTRACT (THAI)</b>	viii
<b>TABLE OF CONTENTS</b>	xi
<b>LIST OF TABLES</b>	xvii
<b>LIST OF FIGURES</b>	xix
<b>ABBREVIATIONS AND SYMBOLS</b>	xxi
 <b>CHAPTER 1 INTRODUCTION</b>	
1.1 Flow Injection Analysis (FIA)	1
1.1.1 Principles of the FIA	1
1.1.2 Dispersion of Sample Zone	2
1.1.3 FIA Instrumentation	6
1.2 Separation Methods in Flow Injection Analysis	9
1.2.1 Gas diffusion method	10
1.3 Chemiluminescence Detection	13
1.3.1 Chemiluminescence Principle	13
1.3.2 Measurement of CL	17
1.4 Photocatalysis	20
1.5 Nanoparticles	21
1.6 Nitrate and Nitrite	23

1.6.1	Physical and Chemical Properties	23
1.6.2	Source and Uses	23
1.6.3	Toxicity and Limiting Contamination	24
1.6.4	Determination of Nitrate and Nitrite	26
1.7	Objectives of the Study	28

## CHAPTER 2 EXPERIMENTAL

2.1	Instruments and Apparatus	29
2.2	Chemicals	31
2.3	Preparation of Standard and Reagents Solutions	33
2.3.1	Nitrate stock solution ( $0.1000 \text{ mol L}^{-1}$ )	33
2.3.2	Nitrite stock solution ( $0.1000 \text{ mol L}^{-1}$ )	33
2.3.3	Luminol stock solution ( $2.0000 \times 10^{-3} \text{ mol L}^{-1}$ )	33
2.3.4	Sulfuric acid solution ( $0.15 \text{ mol L}^{-1}$ )	33
2.3.5	Hydrogen peroxide stock solution ( $100.00 \text{ mmol L}^{-1}$ )	34
2.3.6	EDTA stock solution ( $10.0000 \text{ mmol L}^{-1}$ )	34
2.3.7	Sodium hydroxide stock solution ( $2.00 \text{ mol L}^{-1}$ )	34
2.3.8	Phosphate buffer solution (pH 8.0)	34
2.4	Flow Injection Chemiluminescence Flow Design	35
2.4.1	Preliminary investigation of the flow injection chemiluminescence for determination of nitrate and nitrite	35
2.4.2	A gas diffusion flow injection chemiluminescence (GDFI-CL) for determination of nitrate and nitrite	36

2.5	Procedure	38
2.5.1	Flow injection chemiluminescence (FI-CL) system	38
2.5.1.1	Optimization of the FI-CL system by univariate method	39
2.5.2	Gas diffusion flow injection chemiluminescence (GDFI-CL) system for determination of nitrite	40
2.5.2.1	Optimization of the GDFI-CL system by univariate method	41
2.5.2.2	Linearity of calibration graph	41
2.5.2.3	Precision	41
2.5.2.4	Detection limit	42
2.5.2.5	Accuracy of the proposed method	42
2.5.2.6	Interference studies	42
2.5.3	Gas diffusion flow injection chemiluminescence (GDFI-CL) system with on-line photoreduction for determination of nitrate using zinc oxide nanoparticles as catalyst	43
2.5.3.1	Linearity of calibration graph	44
2.5.3.2	Precision	44
2.5.3.3	Detection limit	44
2.5.3.4	Accuracy of the proposed method	44
2.6	Validation Method	45
2.6.1	AOAC Colorimetric method for determination of nitrite in food samples	45

2.6.2	AOAC Xylenol method for determination of nitrate in food samples	46
2.6.3	Student T- test	47
2.7	Analytical recovery	48

### **CHAPTER 3 RESULTS AND DISCUSSION**

3.1	Preliminary investigation of the flow injection chemiluminescence for determination of nitrate and nitrite	49
3.1.1	Manifold Design	49
3.1.2	Optimization of the FI-CL system by univariate method	51
3.1.2.1	Effect of photomultiplier tube (PMT) voltage	51
3.1.2.2	Effect of sulfuric acid concentration	53
3.1.2.3	Effect of hydrogen peroxide concentration	55
3.1.2.4	Effect of EDTA concentration	56
3.1.2.5	Effect of luminol concentration	58
3.1.2.6	Effect of sodium hydroxide concentration	59
3.1.2.7	Effect of sample injection volume	61
3.1.2.8	Effect of reaction coil length	62
3.1.2.9	Effect of flow rate	64
3.1.3	Summary of the optimum conditions	65
3.2	Gas diffusion flow injection chemiluminescence system for determination of nitrite	67
3.2.1	Manifold Design	67

3.2.2	Optimization of the GDFI-CL Manifold	69
3.2.3	Analytical characteristics of the method	70
3.2.3.1	Linearity	70
3.2.3.2	Precision of the flow injection system	71
3.2.3.3	Detection limit	72
3.2.3.4	Interference studies	74
3.2.3.5	Determination of nitrite in food samples	80
3.3	Gas diffusion flow injection chemiluminescence system	83
	for determination of nitrate in food sample with	
	the on-line photoreduction of nitrate ions to nitrite ions	
3.3.1	Manifold design	84
3.3.2	Comparison of the FICL grams obtained with and	86
	without ZnO nanoparticles	
3.3.3	Optimization of the GDFI-CL Manifold	86
3.3.3.1	Effect of zinc oxide concentration	87
3.3.3.2	Effect of time for photoreduction	88
3.3.4	Summary of the optimum conditions	90
3.3.5	Analytical characteristics of the method	91
3.3.5.1	Linearity	91
3.3.5.2	Precision of the flow injection system	92
3.3.5.3	Detection limit	93
3.3.5.4	Determination of nitrate in food samples	95

<b>CHAPTER 4 CONCLUSIONS AND SUGGESTION</b>	<b>100</b>
<b>FOR FURTHER WORK</b>	
<b>REFERENCES</b>	<b>104</b>
<b>APPENDIX</b>	<b>108</b>
<b>CURRICULUM VITAE</b>	<b>111</b>
<b>THE RELEVANCE OF THE RESEARCH WORK IN THAILAND</b>	<b>113</b>

## LIST OF TABLES

Table		Page
1.1	Chemical toxicity values for non-cancer effect of nitrate and nitrite	25
1.2	Nature of trouble and approximate level of nitrate	26
2.1	Preliminary experimental conditions of FI-CL for studying optimum PMT voltage	39
2.2	The studied range for the FIA parameters	40
3.1	Effect of photomultiplier tube (PMT) applied voltage	52
3.2	Effect of sulfuric acid concentration	54
3.3	Effect of hydrogen peroxide concentration	55
3.4	Effect of EDTA concentration	57
3.5	Effect of luminol concentration	58
3.6	Effect of sodium hydroxide concentration	60
3.7	Effect of sample injection volume	61
3.8	Effect of reaction coil length	63
3.9	Effect of flow rate	64
3.10	The optimum conditions for determination of nitrite	66
3.11	The optimum conditions of GDFI-CL system for determination of nitrite	69
3.12	CL intensity for calibration curve	71
3.13	Precision verification using standard $1 \times 10^{-7}$ mol L <sup>-1</sup> nitrite	72
3.14	The blank signal resulting from 12 injections	73



3.15	Interference studies for $1 \times 10^{-7}$ mol L <sup>-1</sup> nitrite standard solution by GDFI-CL method	75
3.16	Summary of interference effects of some ions on the response obtained Interference studies from $1 \times 10^{-7}$ mol L <sup>-1</sup> standard nitrite by GDFI-CL method	79
3.17	Determination of nitrite in food samples by GDFI-CL method	81
3.18	Recoveries of nitrite in the presence of food samples	81
3.19	Comparative determination of nitrite in food samples by proposed GDFI-CL method and UV-Vis method	82
3.20	Comparison of the CL intensity obtained with and without ZnO nanoparticles	86
3.21	Effect of zinc oxide concentration	88
3.22	Effect of time taken for photoreduction	90
3.23	The optimum conditions for determination of nitrate	91
3.24	Precision verification using standard $7 \times 10^{-3}$ mol L <sup>-1</sup> nitrate	94
3.25	The blank signal resulting from 12 injections	95
3.26	Determination of nitrate in food samples by on-line photoreduction GDFI-CL method	97
3.27	Recoveries of nitrite in the presence of food samples	98
3.28	Comparative determination of nitrate in food samples by proposed GD-FIA method and UV-Vis.	99




## LIST OF FIGURES

Figure		Page
1.1	The Schematic diagram of the basic FIA system showing the various components	2
1.2	General types of transport in closed tubes and the recorded profiles at the detector	3
1.3	Effects of convection and diffusion on concentration profiles of analyses at the detector	4
1.4	Dispersed sample zone in flow system	4
1.5	Relationship between the rollers of a peristaltic pump and the pump tubes	7
1.6	Gas diffusion unit	12
1.7	Temporal variation of the CL intensity	17
1.8	Schematic configuration of a basic flow injection chemiluminescence (FI-CL) manifold	18
1.9	Typical CL signal showing CL intensity as a function of time.	19
1.10	Flow cell: a) Spiral flat coil cell. (b) Spiral flat coil flow cell	20
2.1	The FI-CL manifold for nitrite determination	35
2.2	The GDFI-CL manifold for nitrite determination	37
2.3	The GDFI-CL manifold for nitrate determination	38
3.1	The FI-CL manifold for nitrite determination	50
3.2	Effect of PMT voltage on CL signal-to-noise ratio	53
3.3	Effect of H <sub>2</sub> SO <sub>4</sub> concentration on the signal-to noise ratio	54

3.4	Effect of $\text{H}_2\text{O}_2$ concentration on the signal-to noise ratio	56
3.5	Effect of EDTA concentration on the signal-to noise ratio	57
3.6	Effect of luminol concentration on the signal-to noise ratio	59
3.7	Effect of hydrogen peroxide concentration on the signal-to noise ratio	60
3.8	Effect of sample injection volume on the signal-to noise ratio	62
3.9	Effect of reaction coil length on the signal-to noise ratio	63
3.10	Effect of flow rate on the signal-to noise ratio	65
3.11	The GDFI-CL manifold for nitrite determination	68
3.12	The chemiluminescence reaction of nitrite	68
3.13	GDFI-gram determination of nitrite	70
3.14	The calibration curve of GDFI-CL determination of nitrite	71
3.15	The GDFI-CL manifold for nitrate determination	85
3.16	The chemiluminescence reaction of nitrate	85
3.17	FICL gram of enhancement in chemiluminescence intensity using ZnO	87
3.18	Effect of Zinc oxide concentration on signal-to noise ratio	89
3.19	Effect of time for photoreduction on signal-to noise ratio	90
3.20	GDFI-gram of nitrate on the CL intensity	92
3.21	The calibration curve of nitrate on the CL intensity	93

## ABBREVIATIONS AND SYMBOLS

CL	chemiluminescence
EDTA	ethylenediaminetetraacetic acid
FIA	flow injection analysis
FI-CL	flow injection chemiluminescence
GD	gas diffusion unit
GD-FI	gas diffusion flow injection
GDFI-CL	gas diffusion flow injection chemiluminescence
PMT	photomultiplier tube
h	hour
i.d.	inner diameter
in.	inch
L	liter
LOD	limit of detection
LOQ	limit of quantitation
mg	milligram
mg kg <sup>-1</sup>	milligram per kilogram
mg L <sup>-1</sup>	milligram per liter
min	minute
mL	milliliter
mm	millimeter
mol L <sup>-1</sup>	mole per liter

The background of the page features a large, faint watermark of the Chiang Mai University seal. The seal is circular, with an elephant in the center, a sunburst above its head, and Thai script around the top. The words "CHIANG MAI UNIVERSITY 1964" are written in English around the bottom half of the seal.

PC	personal computer
PE	polyethylene
PMT	photomultiplier tube
PTFE	polytetrafluoroethylene
RSD	relative standard deviation
s	second
SD	standard deviation
UV-VIS	ultraviolet visible spectrophotometry
v/v	volume by volume
$\bar{x}$	average
$\mu\text{L}$	microliter