

REFERENCES

Abe, M., Kobayashi, K., Honma, N., & Nakasaki, K. (2010). Microbial degradation of poly(butylene succinate) by *Fusarium solani* soil environments. *Polymer Degradation and stability*, 95, 138-143.

Abu-Zuraylx, R., Harkin Jones, E., McNally, T., Menary, G., Martin, P. & Armstrong, C. (2009). Biaxial deformation behavior and mechanical properties of a polypropylene/clay nanocomposite. *Composites Science and Technanology*, 69, 1644-1652.

ASTM D1238. Standard Test Method for Melt Flow Rates of Thermoplastics by Extrusion Plastometer.

ASTM D5338-98 (2003). Standard Test Method for Determining Aerobic Biodegradation of Plastic Materials under Controlled Composting Conditions.

ASTM D882-91. Standard Test Methods for Tensile Properties of Thin Plastic Sheeting.

ASTM D638. Standard Test Methods for Tensile Properties of Plastics.

Bhatia, A., Gupta, R.K., Bhattacharya, S.N., & Choi, H.J. (2007). Compatibility of biodegradation poly (lactic acid) (PLA) and poly(butylene succinate) (PBS) blends for packaging application. *Korea-Australia Rheology Journal*, 19(3), 125-131.

Billmeyer, F.W. (1994). *Text of Polymer Science*. New York, John Wiley & John.

Bower, D.I. (2002). *An Introduction to Polymer Physics*. New York: Cambridge University Press.

Brandrup, J., Immergut, E.H., & Grulke, E.A. (1999). Viscosity-Molecular Weight Relationships and Unperturbed Dimensions of Linear Chain Molecules. In *Polymer Handbook* (4th ed., Vol. VII, pp.44), New York, Chichester: John Wiley & Sons, Inc.

Brostow, W., Chiu, R., Kalogeras, I. M., & Vassilikou-Dova, A. (2008). Prediction of glass transition temperatures: Binary blends and copolymers. *Materials Letters*, 62(17-18), 3152-3155.

CEN (1997) Standard–Requirements for packaging recoverable in the form of composting and biodegradation–Test scheme and evaluation criteria for the final acceptance of packaging (in preparation, Draft June 1997).

Chanda, M., & Roy, R.S. (1993). *Plastics Technology Handbook* (2nd Ed.). USA: Marcel Dekker, Inc.

Chandra, R., & Rustgi, R. (1998). Biodegradable polymers. *Progress in Polymer Science*, 23, 1273-1335.

Channuan, W. (2006). *Microstructure-Property Relationships in Monofilament Fibres for Use as Absorbable Surgical Sutures*. Ph.D's thesis. Chiang Mai University, Chiang Mai, Thailand.

Chieng, B.W., Ibrahim, N.A., & Wan Yunus, W.M.Z. (2010). Effect of organo-modified montmorillonite on poly(butylene succinate)/poly(butylene adipate-co-terephthalate) nanocomposites. *Express Polymer Letters*, 4, 404-414.

Chrissafis, K., Paraskevopoulos, K.M., & Bikiaris, D.M. (2005). Thermaldegradation mechanism of poly(ethylene succinate) and poly(butylene succinate): Comparative study. *Thermochimica Acta* 435, 142-150.

Cowie, J.M. (1989). In *Encyclopedia of polymer science and engineering supplement volume* (pp.456). New York: John Wiley & Sons.

Da Silva, L., & Bretas, R.E.S. (2000). Blends of a bottle grade polyethylene terephthalate copolymer and a liquid crystalline polymer. Part I: Injection molding morphology and rheological properties. *Polymer Engineering & Science*, 40(6), 1414-1428.

Duckett, K.E., Bhat, G.S. & Suh, H. "Compostable and biodegradable compositions of a blend of natural cellulosic and thermoplastic biodegradable fibers" U.S. Pat 5783505 July 21, 1998.

Eastman Chemical Company (2008). Handling precautions for cellulose ester in formulating coatings, contains handling procedures for EastmanTM cellulose ester. *Eastman publication E-241*.

Edgar, K.J., Buchanan, C.M., Debenham, J.S., Rundquist, P.A., Seiler, B.D., Shelton, M.C., & Tindall, D. (2001). Advances in cellulose ester performance and application. *Progress in Polymer Science*, 26(9), 1605-1688.

El-Shafee, E., Gamal, R., & Fahmy, S.M. (2001). Miscibility, crystallization and phase structure of poly(3-hydroxybutyrate)/cellulose acetate butyrate blends. *European Polymer Journal*, 37, 2091-2104.

European Plastic Product Manufacturer (2009). In *FKUR plastics –made by natural*[®] [online]. Available: <http://www.fkur.de/?page=8.html> [2009, June].

Farrington, D. (2005). Poly(lactic acid) and fibers. in R.S. Black (Ed.), *Biodegradable and sustainable fibers* (pp.193), UK: University of Leeds, Woodhead Publishing Ltd.

Folkes, M.J., & Hope, P.S. (1993). *Polymer Blends and Alloys*. London, UK: Chapman & Hall.

Fujimaki, T. (1998). Processability and Properties of aliphatic polyesters, 'BIONOLLE', synthesized by polycondensation reaction. *Polymer Degradation and stability*, 59, 209-214.

Gcwabaza, T., Ray, S.S., Focke, W.W., & Maity, A. (2009). Morphology and Properties of nanostructured materials based on polypropylene/poly(butylene succinate) blend and organoclay. *European Polymer Journal*, 45, 353-367.

Ghosh, I. (1998). *Blends of Biodegradable Thermoplastics with Lignin Esters*. Virginia Polytechnic Institute and State University: Blacksburg, VA, USA.

Hale, W., Lee, J.-H., Keskkula, H., & Paul, D.R. (1999). Effect of PBT melt viscosity on the morphology and mechanical properties of compatibilized and uncompatibilized blends with ABS. *Polymer* 40, 3621-3629.

Hammer, C.F. (1978). *Polymer Blends*. vol.2, 17, 219, in D.R. Paul & S. Newman (Eds.), New York: Academic Press.

He, Y., Zhu, B., Kai, W., & Inoue, Y. (2004). Nanoscale-Confined and Fractional Crystallization of Poly(ethylene oxide) in the Interlamellar Region Poly(butylene succinate). *Macromolecules*, 37, 3337-3345.

Hunt, B.J., & James, M.I. (1993). *Polymer Characterization* (1st Ed.). London: Blackie Academic & Professional.

ISO/DIS 14855-1 (2005). Determination of the ultimate aerobic biodegradability and disintegration of plastic materials under controlled composting condition – method by analysis of evolved carbon dioxide – part 1: general method.

Jo, G., Shin, B., Lee, S., Cho, S., Jang, S., Cho, B., Hong, K., Kim, B., kang, K., & Jang, W. (2006). Mechanical Properties and Biodegradation Study on Blends of PLA and Chemically Modified Plasticized Starch. *Applied Chemistry*, 10(2), 405-408.

Kale, G., Auras, R., Singh, S.P., & Narayan, R. (2007). Biodegradability of polylactide bottles in real and simulated composting conditions. *Polymer Testing*, 26(8), 1049-1061.

Kanemura, C., Nakashima, S., & Hotta, A. (2012). Mechanical properties and chemical structure of biodegradable poly(butylene succinate) for material reprocessing. *Polymer Degradation and stability*, 97, 972-980.

Klemm, D., Shmauder, H.P., Heinze, T. (2002). Cellulose. in E.J. Vandamme, S. De Baets, & A. Steinbüchel (Eds.), *Biopolymers Polysaccharides II* (vol. 6, pp.275-319), Weinheim, Germany: Wiley-VCH.

Knaul, J.Z., Hudson, S.M., & Creber, K.A.M. (1999). Improved mechanical properties of chitosan fibers. *Journal of Applied Polymer Science*, 72(13), 1721-1732.

Kunioka, M., Ninomiya, F., & Funabashi, M. (2009). Biodegradation of Poly(butylene succinate) Power in a Controlled Compost at 58°C Evaluated by Naturally-Occurring Carbon 14 Amounts in Evolved CO₂ Based on the ISO 14855-2 Method. *International Journal of Molecular Sciences*, 10, 4267-4283.

Lee, W.B., wu, S.Z., & Song, M.S. (1996). Characterization of the orientation structure and distribution in rooled polypropylene. *Journal of Material Engineering and performance*, 5, 637-645.

Liu, L., Yu, L., Cheng, L., & Yang, X. (2009). Polymer Degradation and Stability. *Polymer Degradation and stability*, 94, 90-94.

Martin, O., & Avérous, L. (2001). Poly (lactic acid): plasticization and properties of biodegradable multiphase systems. *Polymer*, 42(14), 6209-6219.

Massey, L.K. (2004). *Film Properties of Plastics and Elastomers: A Guide to Non-Woven in Packaging Applications* (2nd Ed.). New York: William Andrew, Inc.

Miller, E. (1996). *Introduction to plastic and composites*. Mechanical properties and engineering applications., Marcel Dekker, New York.

Neblette, C.B. (1962). *Photography, its materials and processes* (6th Ed.). Princeton, NJ: Van Nostrand.

Nolan-ITU, (2002). *Environment Australia: Biodegradable Plastics-Developments and Environmental Impacts*. Melbourne: NOLAN-ITU Pty Ltd.

Okamoto, K., Ray, S.S., & Okamoto, M. (2003). New poly(butylene succinate)/layered silicate nanocomposites, II. Effect of organically modified layered silicates on structure, properties, melt rheology, and biodegradability. *Journal of polymer science Part B:Polymer Physic*, 41, 3160-3172.

Park, H.-M., Liang, H., Mohanty, A.K., Misra, M., & Drzal, L.T. (2004). Effect of Compatibilizer on Nanostructure of the Biodegradable Cellulose Acetate/Organoclay Nanocomposites. *Macromolecules*, 37, 9076-9082.

Paul, D.R. (1978). *Polymer Blends*. vol.2, 12, 35, in D.R. Paul & S. Newman (Eds.), New York: Academic Press.

Phua, Y.S., Chow, W.S., & Mohd Ishak, Z.A. (2011). The hydrolytic effect of moisture and hygrothermal aging on poly(butylene succinate)/organo-montmorillonite nanocomposites. *Polymer Degradation and stability*, 96, 802-812.

Pillin, I., Montrelay, N., & Grohens, Y. (2006). Thermo-mechanical characterization of plasticized PLA: Is the miscibility the only significant factor?. *Polymer*, 47(13), 4676-4682.

Qiu, Z., Ikehara, T., & Nishi, T. (2003). Melting behaviour of poly(butylene succinate) in miscible blends with poly(ethylene oxide). *Polymer* 44, 3095-3099.

Rabek, J.F. (1980). *Experimental Methods in Polymer Chemistry: Physical Principles and applications*. New York: John Wiley & Sons, Inc.

- Ray, S.S., Bandyopadhyay, J., & Bousmina, M. (2007). Thermal and thermomechanical properties of poly[(butylene succinate)-co-adipate] nanocomposite. *Polymer Degradation and stability*, 802-812.
- Ray, S.S., Okamoto, K., & Okamoto, M. (2008). Structure-Property Relationship in Biodegradable Poly(butylene succinate)/Layered Silicate Nanocomposites. *Macromolecules*, 36, 2355-2367.
- Robeson, L.M. (2007). *Polymer Blends: A Comprehensive Review*. USA: Hanser Publications LLC.
- Rosa, D.S., Guedes, C.G.F., Casarin, F., & Braganca, F.C. (2005). The effect of the Mw of PEG in PCL/CA blends. *Polymer Testing*, 24, 542-548.
- Rosen, S.L. (1975). *Fundamental Principles of Polymeric Materials* (2nd Ed.). New York: John Wiley & Sons, Inc.
- Sasisil, C. (2004). *Improvement of the Mechanical Properties of Chitosan Monofilament Fibres by Blending with Poly (Ethylene Oxide)*. Chiang Mai University: Chiang Mai, Thailand.
- Sawada, H., & Fujimaki, T. (1995). *Handbook of Biodegradable Polymer*. in Y. Doi (Ed.), (pp.130). Tokyo:NTS.
- Scandola, M., Ceccorulli, G., & Pizzoli, M. (1992). Miscibility of bacterial poly (3-hydroxybutyrate) with cellulose esters. *Macromolecules*, 25(24), 6441-6446.
- Sealey, J.E., Samaranayake, G., Todd, J.G., & Glasser, W.G. (1996). Novel cellulose derivatives. IV. Preparation and thermal analysis of waxy esters of cellulose. *Journal of Polymer Science Part B: Polymer Physics*, 34(9), 1613-1620.
- Seymour, R.B., & Carraher, C.E. (1984). *Structure-Property Relationships in Polymers*. New York: Plenum Press.

- Shinoda, H., Asou, Y., Kashima, T., Kato, T., Tseng, Y., & Yagi. (2003). Amphiphilic biodegradable copolymer, poly(aspartic acid-co-lactide): acceleration of degradation rate and improvement of thermal stability for poly(lactic acid), poly(butylene succinate) and poly(ϵ -caprolactone). *Polymer Degradation and stability*, 80, 241-250.
- Siracusa, V., Rocculi, P., Romani, S., & Rosa, M.D. (2008). Biodegradable polymers for food packaging: a review. *Trends in Food Science & Technology*, 19, 634-643.
- Someya, Y., Nakazato, T., Teramoto, N., & Shibata, M. . (2003). Thermal and mechanical properties of poly(butylene succinate) nanocomposites with various organo-modified montmorillonites. *Journal of Applied Polymer Science*, 91, 1463-1475.
- Tachibana, Y., Giang, N.T.T., Ninomiya, F., Funabashi, M., & Kunioka, M. (2010). Cellulose acetate butyrate as multifunctional additive for poly(butylene succinate) by melt blending : Mechanical properties, biomass carbon ratio, and control of biodegradability. *Polymer Degradation and stability*, 1-8.
- Tserki, V., Matzinos, P., Parlidou, E., Vachliotis, D., & Panayiotou, C. (2006). Biodegradable aliphatic polyesters. Part I. Properties and biodegradation of poly(butylene succinate-co-butylene adipate). *Polymer Degradation and stability*, 91, 367-376.
- Tsi, H.-Y., Tsen, W.-C., Shu, Y.-C., Chuang, F.-S., & Chen, C.-C. (2009). Compatibility and characteristics of poly (butylene succinate) propylene-co-ethylene copolymer blend. *Polymer Testing*, 28, 875-885.
- Uesaka, T., Nakane, K., Maeda, S., Ogihara, T., & Ogata, N. (2000). Structure and physical properties of poly(butylene succinate)/cellulose acetate blends. *Polymer* 41, 8449-8454.

Vaithiyalongam, S. (2001). *Preparation and characterization of cellulose acetate butyrate pseudolatex for multi-particulate controlled drug delivery*. Doctor of Philosophy. Texas Tech University, Amarillo, TX, USA.

Vega-Bundrit, J., Sibaja, J., Martin-Martinez, J.M., Nakayama, K., & Masudat, A. (2003). *New developments in polymer analysis, stabilization and degradation*. Nova Science, New York.

Wang, H., Gan, Z., Schultz, J.M., & Yan, S. (2008). A morphological study of poly(butylene succinate)/poly(butylene adipate) blends with different blend ratios and crystallization processes. *Polymer* 49, 2342-2353.

Wang, X., Zhou, J., & Li, L. (2007). Multiple melting behavior of poly(butylene succinate). *European Polymer Journal* 43, 3163-3170.

Wong, A.C.-Y., & Lam, F. (2002). Study of selected thermal characteristics of polypropylene/polyethylene binary blends using DSC and TGA. *Polymer Testing*, 21, 691-696.

Wu, S.Z., & Lee, W.B. (2002). Modeling of the elastic properties of cold-rolled polypropylene sheets. *Scripta Materialia*, 46, 587-592.