

TABLE OF CONTENTS

	Page
ACKNOWLEDGEMENTS	iii
ABSTRACT	iv
CONTENTS	viii
LIST OF TABLES	xi
LIST OF FIGURES	xii
CHAPTER 1 INTRODUCTION	1
1.1 Statement and Significance of the Problem	1
1.2 Literature Review	2
1.2.1 Fuel cell modeling	3
1.2.1.1 The effect of operating temperature to polarization of PEM fuel cell	3
1.2.1.2 The effect of other parameter to polarization of PEM fuel cell	3
1.2.2 Technology and Applications of Hybrid System	5
1.3 Objectives of Study	7
1.4 Scope of study	7
1.5 Expected Benefits	8
CHAPTER 2 THEORY	9
2.1 Fuel Cell Basic Chemistry and Thermodynamics	9
2.1.1 Heat of Reaction	10
2.1.2 Theoretical Electrical Work	11
2.1.3 Theoretical Fuel Cell Potential	12
2.1.4 Effect of Temperature to Cell Potential	13
2.1.5 Theoretical Fuel Cell Efficiency	15
2.1.6 Effect of Pressure to Cell Potential	16
2.1.7 Reaction Rate	17
2.1.8 Reaction Constants: Transfer Coefficient	18
2.1.9 Current Potential Relationship – Butler – Volmer Equation	19
2.1.10 Exchange Current Density	20
2.1.11 Voltage Losses	21
2.1.11.1 Activation Polarization	21
2.1.11.2 Internal Currents and Crossover Losses	22
2.1.11.3 Ohmic (Resistive) Losses	22
2.1.11.4 Concentration Polarization	23
2.1.11.5 Reactants Flow Rates	25
2.1.11.6 Fuel Cell Energy Balance	26

2.2 Theory of Internal Combustion Engine	27
2.2.1 Brake torque and power	27
2.2.2 Indicated work per cycle	28
2.2.3 Mechanical efficiency	29
2.2.4 Specific fuel consumption and efficiency	29
2.2.5 Air/fuel and fuel/are ratio	30
2.2.6 Volumetric efficiency	30
2.2.7 Relationships between performance parameters	31
2.3 Permanent Magnet Synchronous Generator	31
2.4 DC/DC buck converter	32
2.5 Hybrid Technology	33
2.5.1 Components of Hybrid Power System	34
CHAPTER 3 METHODOLOGY	37
3.1 Fuel cell model	37
3.1.1 Case 1: The effect of pressure to fuel cell potential	40
3.1.2 Case 2: The effect of temperature	40
3.1.3 Case 3: The effect of transfer coefficient	40
3.1.4 The effect of exchange current density	40
3.1.5 The effect of internal resistance	40
3.1.6 The effect of limiting current density	41
3.1.7 The effect of load current changed	41
3.2 Gasoline generator model	41
3.3 Experimental	43
3.3.1 Test Station of Stack Fuel Cell	43
3.3.2 The Nexa™ PEM fuel cell module	44
3.3.3 Electronic Load	49
3.3.4 Hydrogen Tank	51
3.3.5 Electrical Generator test station	51
3.3.6 Hybrid test station	52
3.3.6.1 Control unit box	53
3.3.7 Experimental procedure for Fuel Consumption of Fuel Cell	55
3.3.8 Experimental procedure for Fuel Consumption of Gasoline Generator	56
3.3.9 Experimental procedure for Fuel Consumption of Hybrid System	57
3.3.10 Experimental procedure of hybrid test station	58
3.4 Hybrid Model	59
3.4.1 DC/DC converter or Buck converter model	59
3.4.2 AC/DC inverter model	60
3.4.3 Dynamic model of the fuel cell	61
3.4.4 Fuel cell mass balance	62
3.4.4.1 Inlet flow rate	62
3.4.4.2 Outlet flow rates	63
3.4.5 Fuel cell energy balance	65
CHAPTER 4 RESULTS AND DISCUSSION	68
4.1 Results of PEMFC Model	68

4.1.1 The effect of pressure to fuel cell output voltage	69
4.1.2 The effect of temperature to fuel cell potential	69
4.1.3 The effect of transfer coefficient to fuel cell potential	70
4.1.4 The effect of exchange current density to fuel cell potential	71
4.1.5 The effect of internal resistance to fuel cell potential	72
4.1.6 The effect of limiting current density to fuel cell potential	73
4.1.7 The effect of load current changed to fuel cell potential	74
4.1.8 Sensitivity Analysis of fuel cell performance	75
4.1.9 The hydrogen flow rate at any load current	78
4.1.9.1 Simulation model of the relationship of hydrogen flow rate and load current conditions	79
4.1.10 Verification of the simulation model	80
4.1.10.1 Verification of the fuel cell model	80
4.2 The Experiment Results	81
4.2.1 The Experiment results of Fuel Cell	81
4.2.2 The Experiment Results of Hybrid System	85
4.2.2.1 Switching case 1: Fuel cell is the main power source	86
4.2.2.2 Switching case 2: Gasoline generator is the main power source	87
4.2.2.3 Hybrid case 3: Fuel cell and Gasoline generator supply to load power	89
4.2.3 The Experiment results of fuel consumption of gasoline generator	90
4.3 The Simulation Model Results of Hybrid System	91
4.3.1 The 1 st case simulation model results	91
4.3.2 The 2 nd case simulation model results	92
4.3.3 The 3 rd case simulation model results	94
4.3.4 Comparison result of hybrid system	97
4.3.5 Energy Balance	98
4.4 Operation strategy for optimal performance of the fuel cell and electric generator hybrid system	98
CHAPTER 5 CONCLUSIONS AND RECOMMENDATIONS	101
5.1 Conclusions	101
5.1.1 The Simulation Model of the Fuel Cell and Hybrid System	101
5.1.2 The Experimental of the Hybrid System	102
5.1.3 Operation strategy for optimal performance of the hybrid system	102
5.2 Recommendation for future works	103
REFERENCES	104
APPENDIX	109
LIST OF PUBLICATIONS	110
CURRICULUM VITAE	144

LIST OF TABLES

Table	Page
2.1 Change of Enthalpy, Gibbs Free Energy, and Entropy of Hydrogen/Oxygen Fuel Cell Reaction ($kJ/mol.K$) with Temperature and Resulting Theoretical Cell Potential	15
2.2 Reactants consumption and water generation (per Amp and per Cell)	26
3.1 Model parameters (Colleen, 2008)	41
3.2 The output specification of the Nexa™ fuel cell module.	44
3.3 The input specification of the Nexa™ fuel cell module	45
3.4 The interpolation value of Polarization curve from Figure 3.7	47
3.5 The hydrogen consumption with current load conditions from Figure 3.8 with running time 1 min for each current changed.	48
3.6 Design criteria for fuel cell test station	49
4.1 Range of parameters for sensitivity analysis	76
4.2 The constant value of A and B of sensitivity analysis of fuel cell potential	76
4.3 The R^2 and $RMSE$ of the hydrogen consumption rate at difference operating pressure under load conditions.	83
4.4 Relationship of fuel consumption and cost.	100

LIST OF FIGURES

Figure	Page
2.1 Schematic diagram of a PEMFC	9
2.2 Schematic of a single fuel cell assembly	10
2.3 The <i>i-v</i> curve schematic of FC	24
2.4 Schematic of principle of dynamometer's operation (John B. Heywood, 1988)	27
2.5 p-v diagrams for a two stroke engine and a four stroke engine (John B. Heywood, 1988)	28
2.6 Schematic diagram of the buck converter	33
2.7 Diagram of hybrid system with two power sources connected to electronic load	33
2.8 Concept diagram of hybrid energy systems (Praya et al, 2008)	34
2.9 Schematic of a fuel cell vehicle driveline	35
3.1 The research procedures of hybrid system	37
3.2 The schematic of a PEMFC stack module	38
3.3 Calculation procedure flowchart of the of PEM fuel model	39
3.4 Calculation procedure flowchart of gasoline generator model	43
3.5 Nexa™ Fuel cell power module	44
3.6 Nexa™ fuel cell schematic (Ballard, 2003)	45
3.7 Polarization and Power Curves of Nexa™ module (Ballard, 2003)	46
3.8 Hydrogen consumption rates of Nexa™ Fuel Cell (Ballard, 2003)	47
3.9 Connecting diagram of test station of stack cell	50
3.10 Electronic loads which assembled to fuel cell	50
3.11 Monitoring display of the fuel cell parameters	51
3.12 (a) Gasoline Generator with output is 220 VAC and (b) AC/DC inverter with output is 24 VDC	52
3.13 Connecting diagram of hybrid system	53
3.14 Wiring diagram of the hybrid system consists of (1) wiring diagram of 2 power source modules (2) the micro controller with RS485, and (3) data collector	54
3.15 Display and monitor the wiring connection of hybrid system	55
3.16 Schematic diagram of the fuel cell test hydrogen fuel consumption	56
3.17 Schematic diagram of the gasoline generator test fuel consumption	57
3.18 Schematic diagram of the hybrid system test fuel consumption	57
3.19 Buck converter operation (a) basic of buck converter topology, (b) topological mode 1: switch closed, and (c) topological mode 2: switch open	60
3.20 Single Phase Diode Bridge Rectifiers	61
3.21 Calculation procedure flowchart of hybrid system	67
4.1 Polarization curve of single cell	68
4.2 The effect of operating pressure to fuel cell output voltage	69

4.3 The effect of the operating temperature to fuel cell output voltage	70
4.4 The effect of transfer coefficient to fuel cell potential	71
4.5 The effect of exchange current density to fuel cell potential	72
4.6 The effect of internal resistance to fuel cell potential	73
4.7 The effect of limiting current density to fuel cell potential	74
4.8 The output voltage of fuel cell changed when the load current has been changed as in step waveform	75
4.9 Sensitivity analysis of parameters affect to fuel cell potential a) At low current density 0.1A b) At middle current density 0.6A, and c) At high current density 1.2A	77
4.10 Comparison of hydrogen consumption rate at any load current	80
4.11 Verification results of the numerical model and experimental of a stack fuel cell Nexa™	81
4.12 Stack cell output voltage with operating pressure of hydrogen at 1 bar under load current conditions	81
4.13 Stack cell output voltage with operating pressure of hydrogen at 1, 2 and 3 bars under load current changed	83
4.14 Temperature of stack fuel cell with operating pressure of hydrogen at 1 to 3 bars and air flow under load current conditions	84
4.15 Comparison of hydrogen consumptions with operating pressure changing from 1 to 3 bars under load current conditions	84
4.16 The relationship of purge cell voltage and the increasing of output voltage of stack fuel cell	85
4.17 The power of both fuel cell and gasoline generator with the load power conditions in the first case of fuel cell operates as the main power source and gasoline generator work as add-on power source with set point at 210 watts	86
4.18 The power of both fuel cell and gasoline generator with the load power conditions in the first case of fuel cell operates as the main power source and gasoline generator work as add-on power source	87
4.19 The power of both fuel cell and gasoline generator with the load power conditions in the case of gasoline generator operates as the main power source and fuel cell work as add-on power source with set point at 210 watts	88
4.20 The power of both fuel cell and gasoline generator with the load power conditions in the case of gasoline generator operates as the main power source and fuel cell work as add-on power source with set point at 180 watts	88
4.21 Third case of hybrid system to power load conditions: Fuel cell works as the main power source	89
4.22 Third case of hybrid system to power load conditions: Gasoline generator works as the main power.	90
4.23 Relationship between load power and fuel consumption of gasoline fuel	91
4.24 Switching case 1: Fuel cell operates at the main power source with the set point at 210 watts	92
4.25 Switching case 1: Fuel cell operates at the main power source with the set point at 210 watts and operate at 400 watts maximum	92
4.26 Switching case 2: Gasoline generator operates at the main power source with the set point at 210 watts	93

4.27 Switching case 2: Gasoline generator operates at the main power source with the set point at 210 watts and operate at 400 watts maximum	93
4.28 Hybrid case 3: Fuel cell operates at the main power source with gasoline generator supply the exceed power	94
4.29 Hybrid case 3: Fuel cell operates at the main power source with gasoline generator supply the exceed power with step load condotion	94
4.30 Hybrid case 3: Fuel cell and gasoline generator supply equally power	95
4.31 Hybrid case 3: Fuel cell and gasoline generator supply equally power with step load condition	95
4.32 Hybrid case 3: Fuel cell operates at the main power source with gasoline generator is the supported power with difference operation (a), (b), (c), and (d) with the gasoline generatore resistance is 0.00848Ω	97
4.33 Comparison Hybrid system operates at step load condition with gasoline generator resistane 0.00848Ω	98
4.34 Hydrogen consumption rate in L/hr	99