

REFERENCES

- [1] *The free encyclopedia.* (no date). "nanocomposite" [online]. Available <http://en.wikipedia.org> (18 June 2011).
- [2] N. Chisholm, H. Mahfuz, V.K. Rangari, A. Ashfaq, S. Jeelani, "Quasi-static and high strain rate response of nano-featured carbon/epoxy composites", *Comp. Struct.*, **67**(2005):115-124.
- [3] N. Chisholm, H. Mahfuz, V.K. Rangari, A. Ashfaq, S. Jeelani, "Fabrication and mechanical characterization of carbon/SiC-epoxy nanocomposites", *Comp. Struct.*, **67**(2005): 115–127.
- [4] P.K. Mallick, *Fiber-reinforced Composites: Materials, Manufacturing and Design, Revised and Expanded*, second ed., Marcel Dekker, Inc., NY, 1993.
- [5] M. Walker, R. Smith, "A computational methodology to select the best material combinations and optimally design composite sandwich panels for minimum cost", *Comp. Struct.*, **80**(2002): 1457–1460.
- [6] M.M. Schwartz, *Composite Materials, Properties, Nondestructive, Testing and Repair*, Vol. 1, Prentice-Hall, NJ, 1996.
- [7] M. Alagar, A.A. Kumar, K.P.O. Mahesh and K. Dinakaran, "Studies on thermal and morphological characteristics of E-glass/Kevlar 49 reinforced siliconized epoxy composites", *European Polymer Journal*, **36**(2000): 2449-2454.
- [8] K.L. Luthra, H.D. Park, "Chemical considerations in carbon-fiber/oxide-matrix composites", *J.Am. Ceram. Soc.*, **75**(1992): 1889-1898.

- [9] J.A. Kim, D.G. Seong, T.J. Kang and J.R. Youn, " Effects of surface modification on rheological and mechanical properties of CNT/epoxy composites ", *Carbon*, **44**(2006): 1898-1905.
- [10] P. Liu, " Modifications of carbon nanotubes with polymers ", *J. Eur. Poly.*, **41**(2005): 2693-2703.
- [11] X.L. Xie, Y.W. Mai and X.P. Zhou, " Dispersion and alignment of carbon nanotubes in polymer matrix: A review ", *Mater. Sci. Eng. R.*, **49**(2005): 89-112.
- [12] Y. Zou, Y. Feng, L. Wang and X. Liu, " Processing and properties of MWNT/HDPE composites ", *Carbon*, **42**(2004): 271-277.
- [13] K.T. Lau, M. Lu, C.K. Lam, H.Y. Cheung, F.L. Sheng and H.L. Li, "Thermal and mechanical properties of single-walled carbon nanotube bundle-reinforced epoxy nanocomposites: the role of solvent for nanotube dispersion", *Compos. Sci. and Technol.*, **65**(2004): 719-725.
- [14] C.A. Cooper, D. Ravich, D. Lips, J. Mayer and H.D. Wagner, "Distribution and alignment of carbon nanotubes and nanofibrils in a polymer matrix ", *Compos. Sci. and Technol.*, **62**(2002):1105-1112.
- [15] B. Safadi, R.Andrews, E.A. Grulke, " Multiwalled carbon nanotube polymer composites: Synthesis and characterization of thin films", *J. Appl. Polym Sci.*, **84**(2002): 2660-2669.
- [16] M. Cadek, J.N. Coleman, K.P. Ryan, V. Nicolosi, G. Bister, A. Fonseca, and et al., "Reinforcement of Polymers with Carbon Nanotubes: The Role of Nanotube Surface Area", *Nano Lett.*, **4**(2004): 353-356.

- [17] Q.G. Fu, H.J. Li, X.H. Shi, K.Z. Li, J. Wei and Z.B. Hua, "Synthesis of silicon carbide nanowires by CVD without using a metallic catalyst ", *Mater. Chem. Phys.*, **100**(2006): 108–111.
- [18] Y. Ying, Y. Gu, Z. Li, H. Gu, L. Cheng and Y. Qian, " A simple route to nanocrystalline silicon carbide ", *J. Solid State Chem.*, **177**(2004): 4163–4166.
- [19] W. Yang, H. Araki, A. Kohyama, S. Thaveethavorn, H. Suzuki and T. Noda, "Fabrication in-situ SiC nanowires/SiC matrix composite by chemical vapor infiltration process ", *Mater. Lett.*, **58**(2004): 3145–3148.
- [20] X.W. Du, X. Zhao, S.L. Jia, Y.W. Lu, J.J. Li and N.Q. Zhao, " Direct synthesis of SiC nanowires by multiple reaction VS growth ", *Mater. Sci. Eng. B.*, **136**(2007): 72–77.
- [21] J.Y. Fan, X.L. Wu and P.K. Chu, "Low-dimensional SiC nanostructures: Fabrication, luminescence, and electrical properties", *Prog. Mater. Sci.*, **51**(2006): 983–1031.
- [22] U.S. Tewari, A.P. Harsha, A.M. Häger and K. Friedrich, "Solid particle erosion of carbon fibre– and glass fibre–epoxy composites", *Compos. Sci. and Technol.*, **63**(2003): 549-557.
- [23]. M. Hussain, Y. Oku, A. Nakahira and K. Niihara, "Effects of wet ball-milling on particle dispersion and mechanical properties of particulate epoxy composites", *Mats. Lett.*, **26**(1996): 177-184185.
- [24] P. Singjai, S. Changsarn, and S. Thongtem, "Electrical resistivity of bulk multi-walled carbon nanotubes synthesized by an infusion chemical vapor deposition method", *Mat. Sci. Eng A.*, **443**(2007): 42-46.

- [25] P. M. Ajayan, L. S. Schadler and, P.V.Braun; “Nanocomposite science and technology”, first ed., wiley-VCH, (2003).
- [26] “*Carbon nanotube science and technology*” (20 April 2010) [online] Available <http://www.personal.rdg.ac.uk/~scsharip/tubes.htm> (11 June 2011)
- [27] “*Carbon nanotube*” (16 May 2012) [online] Available http://en.wikipedia.org/wiki/Carbon_nanotubes (22 May 2012)
- [28] “*Carbon Nanotubes - Applications of Carbon Nanotubes (Buckytubes)*” (17 June 2004) Available [online] <http://wwwazonano.com/details.asp?ArticleID=980> (11 June 2011)
- [29] K.W.Kolasinski, W. Nessler and A. Demeijere; “Catalytic growth of nanowires: Vapor–liquid–solid, vapor–solid–solid, solution–liquid–solid and solid–liquid–solid growth”, *Curr. Opin. Solid State Mater. Sci.*, **10**(2006): 182-191.
- [30] G. Attolini, F. Rossi, F. Fabbri, M. Bosi, G. Salviati and B. E. Watts, *Cubic SiC Nanowires: Growth, Characterization and Applications*, In Tech -Open Access Publisher, ISBN 978-953-7619-79-4.
- [31] W. Zhou, Y. Zhang, X. Niu, and G. Min, “One-Dimensional SiC Nanostructures: Synthesis and Properties” *One-Dimensional Nanostructures*, **3** (2008): 17-59.
- [32] “*Polytypism and Moissanite*” (No date) [online] Available <http://www.moissaniteitalia.com/eng/caratteristiche/politipismo.htm> (22 May 21012)
- [33] A.A. Lebedev, “Heterojunctions and super lattices based on silicon carbide: Review Semicond.”, *Sci. Technol.*, **21** (2006): R17-R34.

- [34] L.L. Snead, T. Nozawa, Y. Katoh, T.-S. Byun, S. Kondo and D.A. Petti, “Handbook of SiC properties for fuel performance modeling”, *J. Nucl. Mater.*, **371**(2007): 329-377.
- [35] J.B. Casady and R.W. Johnson “States of silicon carbide (SiC) as a wide-bandgap semiconductor for high-temperature applications: A review”, *Solid State Electron.* **39**(1996): 1409–1422.
- [36] B.J. Baliga, *Power Semiconductor Devices*. PWS-Kent, Boston, MA (1996)
- [37] M. Treu, R. Rupp, P Blaschitz, “Commercial SiC device processing: Status and requirements with respect to SiC based power devices” *Superlattice Microstruct.*, **40**(2006):380–387.
- [38] J.J. Sha, J.S. Park, Hinoki T, A. Kohyama, “Bend stress relaxation of advanced SiC-based fibers and its prediction to tensile creep”, *Mech. Mater.*, **39**(2007):175–182.
- [39] M. Mehregany and C.A. Zorman, “SiC MEMS: Opportunities and challenges for applications in harsh environments”, *Thin Solid Films*, **355–356**(1999):518–524.
- [40] D. Djenkal, D. Goeuriot and F. Thevenot, “SiC-reinforcement of an Al₂O₃–γ-Al₂O₃ composite”, *J. Eur. Ceram. Soc.* **20**(2000):2585–2590.
- [41] G. Muller, G. Krotz, and E. Niemann “SiC for sensors and high-temperature electronics. Sens”, *Actuators A: Phys*, **43**(1994):259–268.
- [42] S. Dimitrijev and P. Jamet “Advances in SiC power MOSFET”, *technology. Microelectron. Reliab*, **43**(2003):225–233.
- [43] C.M. Zetterling, *Process Technology for Silicon Carbide Devices*. EMIS Processing Series, Second Edition, INSPEC, IEE, UK (2002).

- [44] S. Iijima, “Helical microtubules of graphitic carbon”, *Nature*, **354** (1993):56–58.
- [45] S. Iijima and T. Ichihashi, “Single-shell carbon nanotubes of 1-nm diameter”. *Nature*, **363**(1993):603–605.
- [46] D. Zhou and S. Seraphin, “Production of silicon carbide whiskers from carbon nanoclusters”, *Chem. Phys. Lett.*, **222**(1994):233–238.
- [47] H.J. Dai, E.W. Wong, Y.Z. Lu, S.S. Fan and C.M. Lieber, “Synthesis and characterization of carbide nanorods” *Nature*, **375**(1995):769–772.
- [48] W.Q. Han, S.S. Fan, Q.Q. Li, W.J. Liang, B.L. Gu and D.P. Yu, “Continuous synthesis and characterization of silicon carbide nanorods” *Chem. Phys. Lett.*, **265**(1997):374–378.
- [49] C.C. Tang, S.S. Fan, H.Y. Dang, J.H. Zhao, C. Zhang, P. Li and A. Gu, “Growth of SiC nanorods prepared by carbon nanotubes-confined reaction”, *J. Cryst. Growth*, **210**(2000):595–599.
- [50] E. Muñoz, A.B. Dalton, S. Collins and A.A. Zakhidov, “Synthesis of SiC nanorods from sheets of single-walled carbon nanotubes”, *Chem. Phys. Lett.*, **395**(2002):397–402.
- [51] T. Seeger, P.K. Redlich and M. Ruhle “Synthesis of nanometer-sized SiC whiskers in the arc-discharge”, *Adv. Mater.*, **12**(2000):279–282.
- [52] Y.B. Li, S.S. Xie, X.P. Zou, D.S. Tang, Z.Q. Liu, W.Y. Zhou and G. Wang, “Large-scale synthesis of β -SiC nanorods in the arc-discharge”, *J. Cryst. Growth*, **223**(2001):125–128.

- [53] A. Thess, R. Lee, P. Nikolaev, H. Dai and P. Petit, "Crystalline ropes of metallic carbon nanotubes", *Science*, **273**(1996):483–487.
- [54] J. Liu, A.G. Rinzler, H. Dai, J.H. Hafner, P.K. Bradley, P.J. Boul and A. Lu, "Fullerene pipes", *Science*, **280**(1998):1253–1255.
- [55] Y.F. Zhang, Y.H. Tang, N. Wang, D.P. Yu, C.S. Lee, I. Belllo and S.T. Lee "Silicon nanowires prepared by laser ablation at high temperature", *Appl. Phys. Lett.*, **72**(1998):1835–1837.
- [56] Y.H. Tang, Y.F. Zhang, H.Y. Peng, N. Wang, C.S. Lee and S.T. Lee, "Si nanowires synthesized by laser ablation of mixed SiC and SiO₂ powders", *Chem. Phys. Lett.*, **314**(1999):16–20.
- [57] W.S. Shi, Y.F. Zheng, H.Y. Peng, N. Wang, C.S. Lee and S.T. Lee "Laser Ablation synthesis and optical characterization of silicon carbide nanowires", *J. Am. Ceram. Soc.*, **83**(2000): 3228–3230.
- [58] G.W. Meng, Z. Cui, L.D. Zhang and F. Phillip, "Growth and characterization of nanostructured β-SiC via carbothermal reduction of SiO₂ xerogels containing carbon nanoparticles" *J. Cryst. Growth*, **209**(2000):801–806.
- [59] C.H. Liang, G.W. Meng, L.D. Zhang, Y.C. Wu and Z. Cui, "Large-scale synthesis of β-SiC nanowires by using mesoporous silica embedded with Fe nanoparticles" *Chem. Phys. Lett.*, **329**(2000):323–328.
- [60] W.J. Xu, Y. Xu, X.Y. Sun, Y.Q. Liu, D. Wu and Y.H. Sun, "Fabrication of tower like β-like by sol-gel and carbothermal reduction processing", *New Carbon Mater.*, **21**(2006):167–170.

- [61] W. Yang, H. Araki, S. Thaveethavorn, H. Suzuki and T. Noda, "In situ synthesis and characterization of pure SiC nanowires on silicon wafer", *Appl. Surf. Sci.*, **241**(2005):236–240.
- [62] W. Yang, H. Araki, Q.L. Hu, N. Ishikawa, S. Suzuki and T. Noda, "In situ growth of SiC nanowires on RS-SiC substrates", *J. Cryst. Growth*, **264**(2004):278–283.
- [63] Y.C. Ying, Y. Gu, Z.F. Li, H.Z. Gu, L.Y. Cheng, Y.T. Qia, "A simple route to nanocrystalline silicon carbide", *J. Solid State Chem.*, **177**(2004):4163–4166.
- [64] A.G. Mamails, L.O.G. Vogtlander and A. Markopoulos, "Nanotechnology and nanostructured materials: Trends in carbon nanotubes", *Precis. Eng.* **28**(2004):16–30.
- [65] Y.F. Zhang, M.N. Gamo, C.Y. Xiao and T. Ando, "Synthesis of 3C-SiC nanowhiskers and emission of visible photoluminescence", *J. Appl. Phys.*, **91**(2002):6066–6070.
- [66] X.T. Zhou, N. Wang, H.L. Lai, Y. Peng, I. Bello and S.T. Lee, " β -SiC nanorods synthesized by hot filament chemical vapor deposition" *Appl. Phys. Lett.*, **74**(1999):3942–3944.
- [67] H.J. Chio, H.K. Seong, J.C. Lee and Y.M. Sung, "Growth and modulation of silicon carbide nanowires", *J. Cryst. Growth*, **269**(2004):472–478.
- [68] H.J. Li, Z.J. Li, A.L. Meng, K.Z. Li, X.N. Zhang and Y.P. Xu, "SiC nanowire networks", *J. Alloys Compd.* **352**(2003):279–282.
- [69] Y.J. Zhang, N.L. Wang, R.R. He, X.H. Chen and J. Zhu, "Synthesis of SiC nanorods using floating catalyst", *Solid State Commun.*, **118**(2001):595–598.

- [70] W.M. Zhou, B. Yang, Z.X. Yang, F. Zhu, L.J. Yan and Y.F. Zhang, "Large-scale synthesis and characterization of SiC nanowires by high-frequency induction heating", *Appl. Surf. Sci.*, **252**(2006):5143–5148.
- [71] X.Y. Kong and Z.L. Wang, "Spontaneous polarization-induced nanohelices, nanosprings, and nanorings of piezoelectric nanobelts", *Nano Lett.*, **3**(2003):1625–1631.
- [72] T. Jintakosol, P. Singjai, "Synthesis of silicon carbide nanowires doped with Al₂O₃", *Key Eng. Mater.*, **353-358**(2007):2171–2174.
- [73] Z.S. Wu, S.Z. Deng, N.S. Xu, J. Chen, J. Zhou and J. Chen, "Needle-shaped silicon carbide nanowires: Synthesis and filed electron emission properties", *Appl. Phys. Lett.*, **80**(2002):3829–3831.
- [74] K.W. Wong, X.T. Zhou, C.K. Au, H.L. Lai, C.S. Lee and S.T. Lee, "Filed-emission characteristics of SiC nanowires prepared by chemical-vapor deposition", *Appl. Phys. Lett.*, **75**(1999):2918–2920.
- [75] H.C. Lo, J.S. Hwang, K.H. Chen, C.H. Hsu, C.F. Chen and L.C. Chen, "SiC-capped nanotip arrays for field emission with ultra low turn-on filed", *Appl. Phys. Lett.*, **83**(2003):1420–1422.
- [76] D.H. Feng, T.Q. Jia, X.X. Li, Z.Z. Xu, J. Chen and S.Z. Deng, "Catalytic synthesis and photoluminescence of needle-shaped 3C-SiC nanowires" *Solid State Commun.*, **128**(2003):295–297.

- [77] S.Z. Deng, Z.B. Li, W.L. Wang, N.S. Xu, J. Zhou, X.G. Zheng, H.T. Xu, J. Chen and J.C. She, "Field emission study of SiC nanowires/nanorods directly grown on SiC ceramic surface", *Appl. Phys. Lett.*, **89**(2006):023118–023200.
- [78] W.M. Zhou, Y.J. Wu, E.S.W. Kong, F. Zhu, Z.Y. Hou and Y.F. Zhang, "Field emission from nonaligned SiC nanowires", *Appl. Surf. Sci.*, **253**(2006):2056–2058.
- [79] X.M. Liu and K.F. Yao, "Large-scale synthesis and photoluminescence properties of SiC/SiO_x nanocables", *Nanotechnology*, **16**(2005):2932–2935.
- [80] E.W. Wong, P.E. Sheehan and C.M. Lieber, "Nanobeam mechanics: Elasticity, strength, and toughness of nanorods and nanotubes", *Nature*, **277**(1997):1971–1975.
- [81] W. Yang., H. Araki, A.Kohyama, Y.Katoh, Q.Hu, H.Suzuki and T.Noda, "Tyranno-SA/SiC composite with SiC nanowires in the matrix by CVI process" *J. Nucl. Mater.*, **329–333**(2004):539–543.
- [82] W. Yang, H. Araki, A. Kohyama, S. Thaveethavorn, H. Suzuki and T. Noda, "Fabrication in-situ SiC nanowires/SiC matrix composite by chemical vapour infiltration process", *Mater.Lett.*, **58**(2004):3145–3148.
- [83] W. Yang, H. Araki, C.C. Tang, S. Thaveethavorn, A. Kohyama, H. Suzuki and T. Noda, "Single crystal SiC nanowires with a thin carbon coating for stronger and tougher ceramic composites", *Adv. Mater.*, **17**(2005):1519–1523.
- [84] S.R.C. Vivekchand, U. Ramamurty and C.N.R. Rao, "Mechanical properties of inorganic nanowire reinforced polymer–matrix composites", *Nanotechnology*, **17**(2006):S344–S350.

- [85] W.M. Zhou, L.J. Yan, Y Wang, and Y.F. Zhang, "SiC nanowires: A photocatalytic nanomaterial", *Appl. Phys. Lett.* **89**(2006): 013105–013107.
- [86] G. Mpourmpakis and G.E. Froudakis, "SiC nanotubes: A novel material for hydrogen storage", *Nano Lett.*, **6**(2006):1851–1853.
- [87] C.N.R. Rao , F.L. Deepak, G. Gundiah and A. Govindaraj, "Inorganic_nanowires", *Solid State Chemistry* **31**:(2003) 5–147.
- [88] N.Wang, Y.Cai, and R.Q. Zhang, "Growth of nanowires", *Mater. Sci. Eng. R.* (2008); **60**: 1–51.
- [89] R. S. Wagner, "Whisker Technology", A. P. Levitt, Ed., Wiley-Interscience, New York, (1970), 47–119.
- [90] S.T. Lee, N. Wang, Y.F. Zhang, and Y.H. Tang, "Semiconductor nanowires from oxide", *MRS Bull.*, **24**(1999): 36–42.
- [91] N. Wang, Y.H. Tang, Y.F Zhang, C.S.Lee and S.T. Lee, "Nucleation and growth of Si nanowires from silicon oxide", *Phys Rev B* **58**: (1998) 16024–6.
- [92] The free encyclopedia. (no date). "Vapor-liquid-solid method-Growth mechanism" [online]. Available <http://en.wikipedia.org> (18 June 2011).
- [93] R. S.Wagner and W. C. Ellis, "Vapor-liquid-solid mechanism of single crystal growth", *Appl. Phys. Lett.* **4** (1964): 89-90.
- [94] Y. Wu and P. Yang, "Direct Observation of Vapor-Liquid-Solid Nanowire Growth", *J. Am. Chem. Soc.*, **123**(2001): 3165-3166.
- [95] Y. Lu, J. Zhong, Todd D Steiner: Editor, Semiconductor Nanostructures for Optoelectronic Applications. Norwood, MA: Artech House, Inc. (2004), 191–192.

- [96] สุธีรัตน์ ช้างสาร, “การสังเคราะห์ท่อนาโนคาร์บอนโดยกระบวนการตกสะสม ไօสารเคมีแบบ หยดและก่อ合成”, วิทยานิพนธ์วิทยาศาสตรมหาบัณฑิต (พิสิกส์), มหาวิทยาลัยเชียงใหม่ เชียงใหม่, 2549.
- [97] W.G. Maffatt, *The Handbook of Binary Phase Diagrams*, Genium, Schenectady, New York, 1976.
- [98] M. Law, J. Goldberger, and P. Yang, *Semiconductor Nanowires and Nanotubes*, *Annu. Rev. Mater. Res.*, **34**(2004): 83–122.
- [99] B. Li, R. Wu, Y. Pan, L. Wu, G. Yang, J. Chen and Q. Zhu, “Simultaneous growth of SiC nanowires, SiC nanotubes, and SiC/SiO₂ core-shell nanocables”, *J. Alloys Compd.*, **462** (2008) 446-451.
- [100] G. Urretavizcaya and Porto J.M. López, “Growth of SiC whiskers by VLS process”, *Journal of Materials Research*, 9(1994):2981-2986.
- [101] B. Park, Y. Ryu and K. Young, “Growth and characterization of silicon carbide nanowires”, *Surface Review and Letters*, 11(2004):373-378.
- [102] E. B. Badtiev, O. S. Petrushkova, and L. A. Panteleimonov, *Vestn, “Nickel-Silicon System Alloys”*, *Moskov. Univ. Khim.*, **15** (1974), 367-368.
- [103] W. Nhuapeng, W. Thamjaree, S. Kumfu, P. Singjai and T. Tunkasiri, “Fabrication and mechanical properties of silicon carbide nanowires/epoxy resin composites”, *Curr. App. Phys.*, 8(2008): 295-299.
- [104] ASTM 638-99 Standard test method for tensile properties of plastics. *American Society for Testing Materials*, 2000