

## TABLE OF CONTENTS

	<b>Page</b>
ACKNOWLEDGEMENTS	iii
ABSTRACT (ENGLISH)	iv
ABSTRACT (THAI)	vi
LIST OF TABLES	xi
LIST OF FIGURES	xii
<b>CHAPTER 1 INTRODUCTION AND OBJECTIVE</b>	<b>1</b>
<b>1.1 Introduction</b>	<b>1</b>
<b>1.2 Objectives</b>	<b>2</b>
<b>CHAPTER 2 THEORY AND LITERATURE SURVEY</b>	<b>4</b>
<b>2.1 Composite Materials</b>	<b>4</b>
<b>2.2 Matrix Phase: Thermoset Resin</b>	<b>6</b>
<b>2.3 Reinforcement Phase</b>	<b>8</b>
2.3.1 Carbon Nanotubes (CNTs)	8
2.3.2 Silicon carbide nanowire (SiCNWs)	16
1) Structure of SiCNWs	17
2) Synthesis of SiC Nanostructures	20
3) Properties of SiCNWs	35
4) Nanowires Growth techniques	43
5) Applications	54

<b>CHAPTER 3 EXPERIMENTAL AND PROCEDURES</b>	57
<b>3.1 Synthesis of Carbon Nanotubes by Infusion CVD Method</b>	57
<b>3.2 Synthesis of Silicon Carbide Nanowires (SiCNWs) by CVD Method</b>	58
3.2.1 Without vacuum pump - assisted system	58
3.2.1 With vacuum pump – assisted system	59
<b>3.3 Fabrication of carbon nanotubes/silicon carbide nanowires/epoxy resin nanocomposites</b>	60
<b>3.4 Characterization and Measurement Methods</b>	63
3.4.1 X-ray Diffraction Analysis	63
3.4.2 Scanning Electron Microscopy (SEM)	64
3.4.3 Transmission Electron Microscopy (TEM)	65
3.4.4 Energy Dispersive Spectroscopy (EDS)	66
<b>3.5 Property Measurement of the Nanocomposites</b>	66
3.5.1 Density Measurement	66
3.5.2 Tensile Strength Measurement	67
3.5.3 Compressive Strength Measurement	69
3.5.4 Impact Strength Measurement	70
3.5.5 Wear Measurement	71
<b>CHAPTER 4 RESULTS AND DISCUSSION</b>	72
<b>4.1 Characterization of synthesis of silicon carbide nanowires (SiCNWs)</b>	72
4.1.1 Synthesis of SiCNWs without vacuum pump - assisted system	72
4.1.2 Synthesis of SiCNWs with vacuum pump - assisted system	76

4.1.2.1 Using Fe <sub>2</sub> O <sub>3</sub> as Catalyst	76
4.1.2.2 Using Ni <sub>2</sub> O <sub>3</sub> as Catalyst	85
4.1.3 Growth mechanism	94
<b>4.2 Fabrication of CNTs, SiCNWs and Epoxy Resin Nanocomposites</b>	<b>96</b>
4.2.1 The morphologies of CNTs and SiCNWs	97
4.2.2 The morphologies of nanocomposites samples	98
4.2.3 Effect of fillers on the mechanical properties of epoxy composites	99
4.2.4 Morphologies of the nanocomposites interface and dispersion of nano-fillers in epoxy matrix	111
<b>CHAPTER 5 CONCLUSIONS AND SUGGESTIONS FOR FURTHER WORKS</b>	<b>114</b>
<b>5.1 Synthesis of Silicon Carbide Nanowires and Characterization</b>	<b>114</b>
<b>5.2 Composites Processing and Characterization</b>	<b>114</b>
<b>5.3 Suggestions for Further Work</b>	<b>115</b>
<b>REFERENCES</b>	<b>117</b>
<b>APPENDICES</b>	<b>129</b>
<b>APPENDIX A</b>	<b>130</b>
<b>APPENDIX B</b>	<b>143</b>
<b>VITA</b>	<b>159</b>

## LIST OF TABLES

<b>Table</b>	<b>Page</b>
2.1 The main physical and chemical properties of the most widespread SiC polytypes	19
2.2 Density, interlayer, and flexural properties of composite with SiC nanowires and conventional composites	40
4.1 The density data for CNTs, SiCNWs and epoxy resin nanocomposites	100

## LIST OF FIGURES

Figure	Page
2.1 Transmission electron micrograph of some multiwalled nanotubes	9
2.2 The graphite plane of nanotube surface coordinates	10
2.3 Structural of carbon Nanotube (a) Armchair structure (n, n), (b) zig-zag structure (n, 0), and (c) Chiral structure (n, m)	10
2.4 The stacking sequence of 3C-, 2H-, 4H-, and 6H-SiC	18
2.5 Geometry of the reactor. (a) Reactants of SiO <sub>2</sub> /Si source covered with carbon nanotubes were put in a crucible. (b) SiO <sub>2</sub> /Si source and carbon nanotubes were put in a boat and the latter kept clear of the former along the downstream direction of gas flow in	22
2.6 SEM micrographs of a carbon nanotube sheet before (a) and SiC nanorods: after (b)–(d) thermal annealing this sheet at 1,000°C between two parallel silicon wafers. The large quasi- spherical particles in(a), with a diameter of typically above 30 nm, contain iron	23
2.7 Arc-discharge setup	24
2.8 SEM image of the powder by arc discharge	25
2.9 Laser-ablation scheme	26
2.10 Typical SEM image of SiC nanowires	26
2.11 TEM images of resulting SiC sample catalyzed by Fe	27

- 2.12 (a) TEM image of the nanowhiskers obtained by scratching the nanowhiskers from the Si substrate.(b) HR-TEM image of a thin 3C-SiC nanowhisker with an orientation of [111]. (c) A thick 3C-SiC nanowhisker with its selected area electron diffraction pattern taken by the electron beam parallel to the [011] zone axis 29
- 2.13 SEM images of vertically aligned SiCNWs grown on a Si substrate at 1,100°C for 2h under total reactor pressure of 5 Torr. The hydrogen flow rate at 775cm<sup>3</sup> min<sup>-1</sup>. Left lower inset is a TEM image of SiCNWs 30
- 2.14 High-frequency induction-heating furnace 31
- 2.15 XRD pattern of the as-synthesized products. *Inset* (b): the digital camera photo of the products 32
- 2.16 (a) SEM image of as-prepared samples grown at 1,450°C for 20 min by SiO powder and carbon fiber, (b) EDS spectrum of the nanowires, (c) TEM image of SiCNW, and (d) HRTEM image of the individual SiCNW 33
- 2.17 (a) Typical TEM images for SiC/SiO<sub>2</sub> nanosprings and (b) HRTEM image nanostructures 34
- 2.18 TEM images of (a) SiCNWs (1 wt.% doping); inset is a corresponding SAED pattern, shows a single-crystalline cubic structure with a [111] growth direction and (b) a non-uniform layer thickness of alumina coating on an individual SiCNWs (2 wt% doping) 34

2.19	The dependence of the field-emission current density $J$ on the applied electric field strength $E$ of the samples at three anode-sample distances of 100, 120, and 140 $\mu\text{m}$	36
2.20	Raman spectrum of SiCNWs by laser ablation	37
2.21	(a) PL spectra of the as-prepared SiC nanocables with core diameters of 10 nm (I) and 20 nm (II), respectively. (b) The PL spectra of the SiC nanocables with core diameter of 20 nm before (II) and after (III) annealing	38
2.22	Typical flexural stress–displacement curves and fiber pullout fracture surface (T-NFRC)	39
2.23	Tensile stress–strain curves of PVA and NW composites, showing an increase in the ultimate tensile strength and reduction in ductility with increasing NW volume fraction	41
2.24	Variation of tensile strength as function of nanowire volume fraction. The <i>solid line</i> represents the least-square fit to the equation given in the figure	41
2.25	(a) SiC photodegradation rates as a function of irradiation time during the photodegradation of acetaldehyde gas under UV irradiation and (b) $\text{CO}_2$ evolution as a function of irradiation time (light on at zero) during the photodegradation of acetaldehyde gas under UV irradiation	43
2.26	TEM micrographs of (a) Si nanowire nuclei formed on the Mo grid and (b), (c) initial growth stages of the nanowires	47

2.27	Schematic describing the nucleation and growth mechanism of SiNWs	48
	The parallel lines indicate the [112] orientation. (a) Si oxide vapor is deposited first and forms the matrix within which the Si nanoparticles are precipitated. (b) Nanoparticles in a preferred orientation grow fast and form nanowires. Nanoparticles with non-preferred orientations may form chains of nanoparticles	
2.28	CVD Growth of SiNWs using Au particle catalysts	49
2.29	In situ TEM images recorded during the process of nanowire growth.	52
	a) Au nanoclusters in solid state at 500 °C, b) alloying initiates at 800 °C, at this stage Au exists in mostly solid state, c) liquid Au/Ge alloy; d) the nucleation of Ge nanocrystal on the alloy surface, e) Ge nanocrystal elongates with further Ge condensation and eventually a wire forms f) the interface is pushed forward (or backward) to form nanowires	
2.30	a) Schematic illustration of vapor-liquid-solid nanowire growth mechanism including three stages (I) alloying, (II) nucleation, and (III) axial growth. The three stages are projected onto the conventional Au-Ge binary phase diagram, b) shows the compositional and phase evolution during the nanowire growth process	53
2.31	SEM micrograph of 3C-SiCNW obtained on a Si spring	56
	Marker is 20 $\mu\text{m}$	
3.1	Schematic diagram of the infusion CVD apparatus	58
3.2	Schematic diagram of the synthesis SiCNWs by CVD method	59
3.3	The rubber mold and sample geometry for tensile test	61
3.4	The rubber mold and sample geometry for impact test	62



3.5	X-ray Monochromater	63
3.6	Scanning electron microscopy (JEOL JSM-6335F)	64
3.7	Transmission electron microscopy	65
3.8	Density measurement	67
3.9	The universal testing machine	68
3.10	The universal testing machine for compression test	69
3.11	The apparatus of impact strength test	70
3.12	Pin-on-Disk Tribometer	71
4.1	FE-SEM images of as-products by different reaction temperatures and the diameters distribution of nanowires (a), (b) at 1,200°C, (c), (d) at 1,300 °C, and (e), (f) at 1,400 °C	73
4.2	Typical TEM images of SiCNWs formed with different temperatures; a) 1,200°C, b) 1,300°C and c) 1,400°C	75
4.3	X-ray diffraction spectra of products from different reaction temperatures at: a) 1,200°C, b) 1,300°C and c) 1,400°C. It can be indexed to be $\beta$ -SiC (JCPDS Card No. 73-1665)	76
4.4	a) Photograph of the product in alumina boat from Fe <sub>2</sub> O <sub>3</sub> catalyst b) FE-SEM image of white wool-like from a), and c) shows the corresponding EDS spectra	77
4.5	FE-SEM images of using Fe <sub>2</sub> O <sub>3</sub> as catalyst with the reaction temperature at: a) 1,300°C, b) 1,350°C and c) 1,400°C	79
4.6	Distributions of nanowires diameters using Fe <sub>2</sub> O <sub>3</sub> as catalyst with different temperature; a) 1,300°C, b) 1,350°C and c) 1,400°C	80

4.7	Typical TEM images of SiCNWs were obtained from using Fe <sub>2</sub> O <sub>3</sub> as catalyst and its SEAD patterns from varying temperatures at a) 1,300°C, b) 1,350°C, and c) 1,400°C	82
4.8	X-ray diffraction spectra of products: using Fe <sub>2</sub> O <sub>3</sub> as catalyst after heat-treated a) 1,300°C, 1,350°C and 1,400°C. It can be indexed to be β-SiC (JCPDS Card No. 73-1665)	83
4.9	HR-TEM images of SiCNWs synthesized by using Fe <sub>2</sub> O <sub>3</sub> as catalyst with varying temperatures at a) 1,300°C, b) 1,350°C and c) 1,400°C	85
4.10	SEM images of a) the cross section of white wool-like features covered as-grown powder, b) FE-SEM image of surface of the white wool-like product at 1,350°C, and c) is the corresponding EDS spectra	87
4.11	FE-SEM images of as-products by different temperatures and the distribution of nanowires diameters (a), (b) at 1,300°C, (c), (d) at 1,350 °C and (e), (f) at 1,400 °C	89
4.12	Typical TEM images of SiCNWs and its SEAD patterns from varying temperatures at a) 1,300°C, b) 1,350°C and c) 1,400°C	91
4.13	HR-TEM images of SiCNWs synthesized by varying temperatures at a) 1,300°C, b) 1,350°C and c) 1,400°C	92
4.14	X-ray diffraction spectra of products: after heat-treated a) 1,300°C, 1,350°C and 1,400°C. It can be indexed to be β-SiC (JCPDS Card No. 73-1665)	93
4.15	FT-IR spectrum of SiCNWs products synthesized at 1,350°C	94
4.16	Tensile strength of epoxy resin matrix and CNTs, SiCNWs fillers with different ratios of 0.5-8.0 vol%	96

4.17 FE-SEM images of: a) CNTs and b) SiCNWs	98
4.18 Before and after tensile test of CNTs, SiCNWs and epoxy matrix samples	98
4.19 Before and after compressive test of CNTs, SiCNWs and epoxy matrix samples	99
4.20 Before and after impact test of CNTs, SiCNWs and epoxy matrix samples	99
4.21 The tensile response of CNTs and SiCNWs loading content (vol %) on epoxy nanocomposites	101
4.22 The compressive strength of CNTs and SiCNWs loading content (vol %) on epoxy nanocomposites	102
4.23 The impact strength of CNTs and SiCNWs loading content (vol %) on epoxy nanocomposites	102
4.24 Gain in tensile strength in percentage of nanocomposites with different ratios of CNTs, SiCNWs fillers	103
4.25 Gain in compressive strength in percentage of nanocomposites with different ratios of CNTs, SiCNWs fillers	104
4.26 Gain in absorbed energy in percentage of nanocomposites with different ratios of CNTs, SiCNWs fillers	104
4.27 The wear track of nanocomposites samples with different ratios of the fillers	105
4.28 The wear rate of CNTs and SiCNWs loading content (vol %) on epoxy nanocomposites	106
4.29 Loss of wear track in percentage of nanocomposites with different ratios of CNTs, SiCNWs fillers	106
4.30 Loss of wear track in percentage of nanocomposites with different ratios of CNTs, SiCNWs fillers	107

4.31	The photographs of the wear track width of 0.05 vol% of the fillers (CNTs:SiCNWs ratio) in nanocomposites samples	108
4.32	The photographs of the wear track width of 0.1 vol% of the fillers (CNTs:SiCNWs ratio) in nanocomposites samples	109
4.33	The photographs of the wear track width of 0.2 vol% of the fillers (CNTs:SiCNWs ratio) in nanocomposites samples	110
4.34	The SEM images of the surfaces of CNTs, SiCNWs and epoxy resin nanocomposites containing 0.2 vol% of the nano-fillers: a) CNTs 100% b) SiCNWs 100% c) CNTs:SiCNWs is 25:75 and d) EDS spectrum of the 25:75 ratio (CNTs:SiCNWs)	113