TABLE OF CONTENTS

Page	
iii	
v	
vii	
xiii	
XV	
9 1	
1	
3	
3	
5	
6	
6	
8	
rve	
	Page iii v vii xiii xv 1 1 3 3 5 6 6 6 6 7 8 8 8 9

	2.1.2 90° mass analyzing magnet	9
	2.1.3 Double steering magnets	11
	2.1.4 Target chambers	11
2.2	The paraxial ray equation for axially symmetric systems	12
2.3	Beam optics	18
	2.3.1 Transformation matrix of the drift space	20
	2.3.2 Transformation matrix of the uniform field	20
	2.3.3 Transformation matrix of double-aperture lens	21
	2.3.4 Transformation matrix of Einzel lens	23
2.4	Aberration in the ion optical elements	23
	2.4.1 Spherical aberration	24
	2.4.2 Chromatic aberration or the effect of momentum dispersion	25
	2.4.3 Ellipticity astigmatism	26
	2.4.4 Diffraction	27
	2.4.5 Total aberration	27
2.5	Ion beam energy deceleration	27
	2.5.1 Ion beam energy deceleration by mechanic theory	28
	2.5.2 Ion beam energy deceleration by electrostatic theory	30
	2.5.2.1 Analytic ion beam energy deceleration without space charge	30
	2.5.2.2 Analytic ion beam energy deceleration with space charge	32
2.6	Measurement of decelerated low-energy ion beam by using a deflecting	
	electrostatic field	34
	2.6.1 The first part: considering an ion passing through an electric field	35

X

	2.6.2 The second part: considering the ion's trajectory and the deflecting	g	
	distance after passing through the electric field	36	
2.7	Measurement of beam current	38	
2.8	Fundamentals of ion implantation	39	
	2.8.1 Interaction of energetic ions with solid surface	39	
	2.8.2 Stopping cross section	40	
	2.8.3 Ion implantation rang and projected rang	41	
2.9	Interaction between energetic ions with DNA	43	
	2.9.1 DNA structure	43	
	2.9.2 Fluence	44	
	2.9.3 Breaks of DNA single strands and double strands	45	
	2.9.4 Gel electrophoresis	46	
Chap	ter 3 Simulation of Deceleration Lens System	48	
3.1	48		
3.2	Deceleration lens simulation	49	
3.3	Simulation the deceleration lens with space charge	59	
3.4	Simulation of measurement of low ion-beam energy	65	
Chap	ter 4 Experiment	72	
4.1	Designing, construction, and test of the deceleration lens	72	
4.2	Designing and construction of the deceleration lens system for ion		
	bombardment of DNA	76	
4.3	Designing and construction of the deceleration lens system for beam		
	energy measurement	77	

4.4 Installation of the deceleration lens systems4.5 Measurement of ion beam energy	80 80
4.5 Measurement of ion beam energy	80
4.6 DNA preparation	85
4.7 Bombardment of DNA	85
4.8 Gel electrophoresis for analyzing plasmid DNA forms	86
Chapter 5 Results and Discussion	89
5.1 The deceleration lens systems	89
5.2 Measurement of ultra-low-ion beam energy	89
5.3 Ultra-low ion energy bombardment of naked DNA	99
Chapter 6 Conclusions	04
6.1 Designing, construction, and installation of the deceleration lens	04
6.2 Measurement of ultra-low ion beam energy	05
6.3 Bombardment of naked DNA using ultra-low energy ion beam 1	06
References 1	07
Appendices 1	13
Appendix A Preparation the 30 kV-Vertical Bioengineering Ion Beamline 1	14
Appendix B Ion Beam Current Depend on Position of the measurement Ion	
Beam Energy	17
Curriculum Vitae 1	27
Copyright [©] by Chiang Mai Univ	e r

xii

LIST OF TABLES

xiii

Table

- 3.1 Simulation data. (a) The potentials of each electrode of each model.(b) The original, final kinetic energies and diameters of each model
- 3.2 Summary. (a) The potentials of each electrode in each model. (b) The original, final ion energies and the distance bending by theory and simulations
- 5.1 Summary of fist experiment information on the measurement of the decelerated-ion energy. (a) The potential of each electrode of the deceleration lens in the simulation and experiment. (b) Information of the measurement of the ion beam energy (diameter, distance of ion beam bending, ion beam energy, and ion beam energy measurement error)
- 5.2 Summary of the second experiment information. (a) The potential of each electrode of the deceleration lens in the simulation and experiment. (b) Information of the measurement of the ion beam energy
- 5.3 Summary of the third experiment result. (a) The potential of each electrode of the deceleration lens in the simulation and experiment.(b) Information of the measurement of the ion beam energy

71

93

94

Page

- 5.4 Summary of the fourth experiment result. (a) The potential of each electrode of the deceleration lens in the simulation and experiment.(b) Information of the measurement of the ion beam energy
- 5.5 Summary of ion beam energy and ion beam energy error calculated by simulation, theory, and measured by experiment



ลิขสิทธิ์มหาวิทยาลัยเชียงใหม่ Copyright[©] by Chiang Mai University All rights reserved

97

98

LIST OF FIGURES

Figure		Page		
2.1	Schematic drawing of CMU3 ion beam line	10		
2.2	Schematic diagram of a double-aperture lens	19		
2.3	Drift space without deflection	21		
2.4	Paraxial case of acceleration of charged particle through a uniform			
	field. For clarity, the length of r_1 and r_2 are enlarged	21		
2.5	Schematic diagram of the Einzel lens arrangement and potential			
	variation (above the lens)	22		
2.6	Schematic diagrams of typical trajectories exhibiting (a) spherical			
	aberration and (b) chromatic aberration	24		
2.7	A schematic diagram of ion beam deceleration to lower the ion energy			
	by a retarding field	28		
2.8	A schematic diagram of the method to measure the ion beam energy			
	in this work	35		
2.9	Schematic diagram of measurement of ion beam current using the			
	Faraday cup	39		
2.10	Schematic drawing of ion and solid interaction	41 		
2.11	Schematic of ion's total path length and projected range	42		

- 2.12 Schematic diagram of DNA. (a) The model of DNA double helix and (b) the scheme of the marcromolecule
- 2.13 Schematic diagram of gel electrophoresis. (A) Equipment for gel electrophoresis method. An electric field pulls DNA in different forms (relaxed, supercoiled and linear forms) to pass agarose gel from the cathode pole to the anode pole as the total charge of DNA is negative.
 (B) Result of electrophoresis showing mobility of different DNA forms
- 3.1 The features of SIMION program version 8.0 which is used for the simulations in this thesis
- 3.2 The SIMION simulated the deceleration lens which decreases the original energy of 20 keV to final energy 64 eV. (a) The electrodes and the beam optics. The electrodes are numbered with the numbers below them. (b) Equipotential surface. (c) The three-dimensional view. Blue color shows ion's trajectories and red color shows equipotential surface. The ions travel from the left to the right hand side
- 3.3 The SIMION simulated the deceleration lens with the cover.(a) Equipotential surface. (b) The three-dimensional view
- 3.4 The first simulation reduces ion beam energy from 20 keV to 64 eV.(a) A two-dimensional view with equipotential surfaces, and (b) a three-dimensional view
- 3.5 The features of (a) the Particles Define mode which definesthe properties of ion beams and (b) Adjustment Voltages mode

44

47

52

3.6	The diameters of the first model before ion beam enters and after it	
	passes through the deceleration lens. The red circles are diameters of ion	
	beam (this case diameters of ion beam before entering and after passing	
	through the deceleration lens same)	55
3.7	The second simulation reduces ion beam energy from 15 keV to 230 eV.	
	(a) A two-dimensional view with equipotential surfaces and (b) a three-	
	dimensional view	56
3.8	The third simulation reduces ion beam energy from 15 keV to 304 eV.	
	(a) A two-dimensional view with equipotential surfaces and (b) a three-	
	dimensional view	57
3.9	The fourth simulation reduces ion beam energy from 15 keV to 408 eV.	
	(a) A two-dimensional view with equipotential surfaces and (b) a three-	
	dimensional view	58
3.10	The fifth simulation reduces ion beam energy from 15 keV to 511 eV.	
	(a) A two-dimensional view with equipotential surfaces and (b) a three-	
	dimensional view	59
3.11	Mode of ion beam repulsion of the SIMION program version 8.0	63
3.12	The deceleration lens simulations vary the beam current: (a) 1 A,	
	(b) 0.1 A, (c) 0.01 A, (d) 1 mA, (e) 0.1 mA, (f) 10 µA, (g) 1 µA,	
	(h) 100 nA, and (i) 10 nA, respectively	63
2.8	Schematic diagram of the method used to measure the ion beam energy	66

3.13 The first simulation of measurement of ion beam energy.

(a) Configuration of the deceleration lens with the electric plates. (b)The ion beam bending by an electrostatic field in two-dimension view, and (c) Three-dimension view. Ions travel from the left to the right hand side. The red lines are the equipotential surfaces and the blue color is the ion's trajectories

3.14 The second simulation of measurement of ion beam energy.

(a) The ion beam bending by the electrostatic field in 2-D view,

and (b) 3-D view

- 3.15 The third simulation of measurement of ion beam energy.(a) The ion beam bending by an electrostatic field in 2-D view, and (b) 3-D view
- 3.16 The fourth simulation of measurement of ion beam energy.(a) The ion beam bending by an electrostatic field in 2-D view, and (b) 3-D view
- 4.1 The constructed deceleration lens. (a) Photograph of Al-electrodes.(b) Schematic and (c) drawing of the deceleration lens. (d) Photograph of the finished six deceleration lens
- 4.2 Schematic of the breakdown test of the deceleration lens.
 HV: high volt. G: ground potential
 4.3 Six deceleration lens supported by two power supplies, 15 and 30 kV
- 4.4 The entire deceleration lens system. (a) schematic drawing

and (b) photograph of the system for DNA bombardment

70

70

74

76

68

69

4.5	The deceleration lens system for ion beam energy measurement.	
	(a) Schematic drawing and (b) photograph of deceleration lens system	
	for measurement of ion beam energy. The inset in (b) at the right hand	
	side shows enlargement details of the ion energy measurement part	79
4.6	The deceleration lens systems installed in the beam line of the 30-kV	
	vertical bioengineering ion implanter (CMU3) in the big chamber	81
4.7	The system for measurement of ion beam energy	83
4.8	The equipment used for ion beam energy measurement	84
4.9	An example of measured ion beam profile along the beam bending	
	distance for each case. D.L.: deceleration lens. The beam profile	
	center is taken as the beam position for calculation	84
4.10	Illustration of decelerated ion beam bombardment of naked DNA.	
	(a) System for bombardment of DNA. (b) Sample holder and	
	Faraday cup	87
5.1	Test of the beam position at the deceleration lens for alignment of	
	the lens. (a) Shape of ion beam. (b) Paper was burned by ion beam	
	at the top of cover	90
3.10	Configuration of the deceleration lens with the electric plates for	
	bending ion beam	92
5.2	Result of the first experiment showing the dependence of ion beam	
	current on position and the bending distance of ion beam as 8 mm	92
COPYII5.3	The result of the second experiment, showing the ion beam current	
	depending on position and the bending distance of ion beam as 8 mm	⁹² e d

5.4	The result of the third experiment, showing the ion beam current					
	depending on position and the bending distance of ion beam as 10 mm	95				
5.5	The fourth experiment result, showing the ion beam current					
	depending on position and the bending distance of ion beam as 13 mm	95				
5.6	Gel electrophoresis result. Lanes 1 and 5 are markers. Lane 4 is					
	natural control. Lane 3 is vacuum control. Lane 2 is bombarded.					
	The DNA bands are pointed and marked by the arrows	100				
5.7	Naked DNA was bombarded by Argon ion, the fluence					
	at 1×10^{15} ions/cm ² . (a) Ion beam energy at 242 eV,					
	(b) at 304 eV, (c) 407 eV, and (d) 510 eV	101				
5.8	Light intensity of each DNA band calculated from					
	the gel electrophoresis for the DNA bombarded by argon ion beam					
	at the fluence of 10^{15} ions/cm ² using at different energy of natural					
	and vacuum controls	102				
A.1	Vacuum system for ion source, ion source, and main switch control					
	of the 30 kV- vertical bioengineering ion beamline (CMU3)	115				
A.2	Drawing of the 30-vertical bioengineering ion beamline (CMU3)	116				

ลิ<mark>ปสิทธิ์มหาวิทยาลัยเชียงใหม่</mark> Copyright[©] by Chiang Mai University All rights reserved