

REFERENCE

- [1] “Energy stat 2554-2556,” *www.energy.go.th*.
- [2] “Table of Thailand Energy Balance 2013,” *http://www.dede.go.th*.
- [3] L. Xiong and A. Manthiram, “High performance membrane-electrode assemblies with ultra-low Pt loading for proton exchange membrane fuel cells,” *Electrochimica Acta*, vol. 50, no. 16–17, pp. 3200–3204, May 2005.
- [4] M. Prasanna, E. A. Cho, T.-H. Lim, and I.-H. Oh, “Effects of MEA fabrication method on durability of polymer electrolyte membrane fuel cells,” *Electrochimica Acta*, vol. 53, no. 16, pp. 5434–5441, Jun. 2008.
- [5] A. M. Chaparro, P. Ferreira-Aparicio, M. A. Folgado, A. J. Martín, and L. Daza, “Catalyst layers for proton exchange membrane fuel cells prepared by electrospray deposition on Nafion membrane,” *J. Power Sources*, vol. 196, no. 9, pp. 4200–4208, May 2011.
- [6] C. H. Hsu and C. C. Wan, “An innovative process for PEMFC electrodes using the expansion of Nafion film,” *J. Power Sources*, vol. 115, no. 2, pp. 268–273, Apr. 2003.
- [7] Y.-G. Chun, C.-S. Kim, D.-H. Peck, and D.-R. Shin, “Performance of a polymer electrolyte membrane fuel cell with thin film catalyst electrodes,” *J. Power Sources*, vol. 71, no. 1–2, pp. 174–178, Mar. 1998.
- [8] G. Bender, T. A. Zawodzinski, and A. P. Saab, “Fabrication of high precision PEFC membrane electrode assemblies,” *J. Power Sources*, vol. 124, no. 1, pp. 114–117, Oct. 2003.
- [9] R. Benítez, A. M. Chaparro, and L. Daza, “Electrochemical characterisation of Pt/C suspensions for the reduction of oxygen,” *J. Power Sources*, vol. 151, pp. 2–10, Oct. 2005.
- [10] D. S. Hwang, C. H. Park, S. C. Yi, and Y. M. Lee, “Optimal catalyst layer structure of polymer electrolyte membrane fuel cell,” *Int. J. Hydrog. Energy*, vol. 36, no. 16, pp. 9876–9885, Aug. 2011.

- [11] Z. Wang and Y. Nagao, "Effects of Nafion impregnation using inkjet printing for membrane electrode assemblies in polymer electrolyte membrane fuel cells," *Electrochimica Acta*, vol. 129, pp. 343–347, May 2014.
- [12] M. Uchida, Y. Fukuoka, Y. Sugawara, H. Ohora, and A. Ohta, "Improved preparation process of very-low-platinum-loading electrodes for polymer electrolyte fuel cells," *J. Electrochem. Soc.*, vol. 145, no. 11, pp. 3708–3713, 1998.
- [13] S.-J. Shin, J.-K. Lee, H.-Y. Ha, S.-A. Hong, H.-S. Chun, and I.-H. Oh, "Effect of the catalytic ink preparation method on the performance of polymer electrolyte membrane fuel cells," *J. Power Sources*, vol. 106, no. 1–2, pp. 146–152, Apr. 2002.
- [14] A. Therdthianwong, P. Ekdharmasuit, and S. Therdthianwong, "Fabrication and Performance of Membrane Electrode Assembly Prepared by a Catalyst-Coated Membrane Method: Effect of Solvents Used in a Catalyst Ink Mixture," *Energy Fuels*, no. 24, pp. 1191–1196, 2010.
- [15] M. S. Saha, D. K. Paul, B. A. Peppley, and K. Karan, "Fabrication of catalyst-coated membrane by modified decal transfer technique," *Electrochem. Commun.*, vol. 12, no. 3, pp. 410–413, Mar. 2010.
- [16] B. Millington, S. Du, and B. G. Pollet, "The effect of materials on proton exchange membrane fuel cell electrode performance," *J. Power Sources*, vol. 196, no. 21, pp. 9013–9017, Nov. 2011.
- [17] T. T. Ngo, T. L. Yu, and H.-L. Lin, "Nafion-based membrane electrode assemblies prepared from catalyst inks containing alcohol/water solvent mixtures," *J. Power Sources*, vol. 238, pp. 1–10, Sep. 2013.
- [18] T. T. Ngo, T. L. Yu, and H.-L. Lin, "Influence of the composition of isopropyl alcohol/water mixture solvents in catalyst ink solutions on proton exchange membrane fuel cell performance," *J. Power Sources*, vol. 225, pp. 293–303, Mar. 2013.
- [19] S. J. Lee, S. Mukerjee, J. McBreen, Y. W. Rho, Y. T. Kho, and T. H. Lee, "Effects of Nafion impregnation on performances of PEMFC electrodes," *Electrochimica Acta*, vol. 43, no. 24, pp. 3693–3701, 1998.

- [20] E. Antolini, L. Giorgi, A. Pozio, and E. Passalacqua, "Influence of Nafion loading in the catalyst layer of gas-diffusion electrodes for PEFC," *J. Power Sources*, vol. 77, no. 2, pp. 136–142, Feb. 1999.
- [21] E. Passalacqua, F. Lufrano, G. Squadrito, A. Patti, and L. Giorgi, "Nafion content in the catalyst layer of polymer electrolyte fuel cells: effects on structure and performance," *Electrochimica Acta*, vol. 46, no. 6, pp. 799–805, Jan. 2001.
- [22] P. Gode, F. Jaouen, G. Lindbergh, A. Lundblad, and G. Sundholm, "Influence of the composition on the structure and electrochemical characteristics of the PEFC cathode," *Electrochimica Acta*, vol. 48, no. 28, pp. 4175–4187, Dec. 2003.
- [23] Z. Qi and A. Kaufman, "Low Pt loading high performance cathodes for PEM fuel cells," *J. Power Sources*, vol. 113, no. 1, pp. 37–43, Jan. 2003.
- [24] G. Sasikumar, J. W. Ihm, and H. Ryu, "Dependence of optimum Nafion content in catalyst layer on platinum loading," *J. Power Sources*, vol. 132, no. 1–2, pp. 11–17, May 2004.
- [25] D. Lee and S. Hwang, "Effect of loading and distributions of Nafion ionomer in the catalyst layer for PEMFCs," *Int. J. Hydrog. Energy*, vol. 33, no. 11, pp. 2790–2794, 2008.
- [26] A. M. Chaparro, B. Gallardo, M. A. Folgado, A. J. Martín, and L. Daza, "PEMFC electrode preparation by electrospray: Optimization of catalyst load and ionomer content," *Catal. Today*, vol. 143, no. 3–4, pp. 237–241, May 2009.
- [27] S. Martin, P. L. Garcia-Ybarra, and J. L. Castillo, "Electrospray deposition of catalyst layers with ultra-low Pt loadings for PEM fuel cells cathodes," *J. Power Sources*, vol. 195, no. 9, pp. 2443–2449, May 2010.
- [28] R. R. Passos, V. A. Paganin, and E. A. Ticianelli, "Studies of the performance of PEM fuel cell cathodes with the catalyst layer directly applied on Nafion membranes," *Electrochimica Acta*, vol. 51, no. 25, pp. 5239–5245, Jul. 2006.
- [29] L. Sun, R. Ran, G. Wang, and Z. Shao, "Fabrication and performance test of a catalyst-coated membrane from direct spray deposition," *Solid State Ion.*, vol. 179, no. 21–26, pp. 960–965, Sep. 2008.
- [30] K.-H. Kim *et al.*, "The effects of Nafion® ionomer content in PEMFC MEAs prepared by a catalyst-coated membrane (CCM) spraying method," *Int. J. Hydrog. Energy*, vol. 35, no. 5, pp. 2119–2126, Mar. 2010.

- [31] H.-N. Su, S.-J. Liao, T. Shu, and H.-L. Gao, "Performance of an ultra-low platinum loading membrane electrode assembly prepared by a novel catalyst-sprayed membrane technique," *J. Power Sources*, vol. 195, no. 3, pp. 756–761, Feb. 2010.
- [32] J. Xie, F. Xu, D. L. Wood III, K. L. More, T. A. Zawodzinski, and W. H. Smith, "Influence of ionomer content on the structure and performance of PEFC membrane electrode assemblies," *Electrochimica Acta*, vol. 55, no. 24, pp. 7404–7412, Oct. 2010.
- [33] T.-H. Huang, H.-L. Shen, T.-C. Jao, F.-B. Weng, and A. Su, "Ultra-low Pt loading for proton exchange membrane fuel cells by catalyst coating technique with ultrasonic spray coating machine," *Int. J. Hydrog. Energy*, vol. 37, no. 18, pp. 13872–13879, Sep. 2012.
- [34] S. Mu and M. Tian, "Optimization of perfluorosulfonic acid ionomer loadings in catalyst layers of proton exchange membrane fuel cells," *Electrochimica Acta*, vol. 60, pp. 437–442, 2012.
- [35] S. H. Ahn *et al.*, "Effects of platinum loading on the performance of proton exchange membrane fuel cells with high ionomer content in catalyst layers," *Int. J. Hydrog. Energy*, vol. 38, no. 23, pp. 9826–9834, Aug. 2013.
- [36] K. Punyawudho, D. A. Blom, J. W. Van Zee, and J. R. Monnier, "Comparison of different methods for determination of Pt surface site concentrations for supported Pt electrocatalysts," *Electrochimica Acta*, vol. 55, no. 19, pp. 5349–5356, Jul. 2010.
- [37] K.-H. Kim *et al.*, "Effect of Nafion® gradient in dual catalyst layer on proton exchange membrane fuel cell performance," *Int. J. Hydrog. Energy*, vol. 33, no. 11, pp. 2783–2789, Jun. 2008.
- [38] V. A. Paganin, E. A. Ticianelli, and E. R. Gonzalez, "Development and electrochemical studies of gas diffusion electrodes for polymer electrolyte fuel cells," *J. Appl. Electrochem.*, vol. 26, no. 3, pp. 297–304, Mar. 1996.
- [39] Y.-H. Cho, H.-S. Park, Y.-H. Cho, D.-S. Jung, H.-Y. Park, and Y.-E. Sung, "Effect of platinum amount in carbon supported platinum catalyst on performance of polymer electrolyte membrane fuel cell," *J. Power Sources*, vol. 172, no. 1, pp. 89–93, Oct. 2007.

- [40] T. Maiyalagan, S. Pasupathi, and B. G. Pollet, “The Effects of Cathode Parameters on the Performance of Poly(2,5-Benzimidazole)-Based Polymer Electrolyte Membrane Fuel Cell,” *Electrocatalysis*, vol. 6, no. 2, pp. 155–162, Sep. 2014.
- [41] B. Millington, V. Whipple, and B. G. Pollet, “A novel method for preparing proton exchange membrane fuel cell electrodes by the ultrasonic-spray technique,” *J. Power Sources*, vol. 196, no. 20, pp. 8500–8508, Oct. 2011.
- [42] “Catalogue, E-TEK Inc.,” p. 15, 1999.
- [43] Frano Barbir, “PEM Fuel cell: Theory and Practice,” Elsevier Academic Press, Burlington, USA., 2005.
- [44] X. Li and I. Sabir, “Review of bipolar plates in PEM fuel cells: Flow-field designs,” *Int. J. Hydrog. Energy*, vol. 30, no. 4, pp. 359–371, Mar. 2005.
- [45] S. H. Ahn *et al.*, “Effects of platinum loading on the performance of proton exchange membrane fuel cells with high ionomer content in catalyst layers,” *Int. J. Hydrog. Energy*, vol. 38, no. 23, pp. 9826–9834, Aug. 2013.
- [46] K. Punyawudho, N. Vorayos, Y. Zhang, S. Shimpalee, and J. R. Monnier, “Identification and quantification of performance losses for PEM fuel cells as determined by selective chemisorption and ESA measurements,” *Int. J. Hydrog. Energy*, vol. 39, no. 21, pp. 11110–11119, 2014.
- [47] B. G. Pollet, “A novel method for preparing PEMFC electrodes by the ultrasonic and sonoelectrochemical techniques,” *Electrochem. Commun.*, vol. 11, no. 7, pp. 1445–1448, Jul. 2009.
- [48] K. Wuttikid and K. Punyawudho, “Optical and Scanning Electron Microscopy Characterization of Catalyst Ink Droplets prepared by Ultrasonic Spray,” *Proc. 34th MST Annu. Conf.*, no. 34, p. 145, May 2017.
- [49] B. G. Pollet, “The use of ultrasound for the fabrication of fuel cell materials,” *Int. J. Hydrog. Energy*, vol. 35, no. 21, pp. 11986–12004, Nov. 2010.
- [50] V. Mehta and J. S. Cooper, “Review and analysis of PEM fuel cell design and manufacturing,” *J. Power Sources*, vol. 114, no. 1, pp. 32–53, Feb. 2003.
- [51] S. Litster and G. McLean, “PEM fuel cell electrodes,” *J. Power Sources*, vol. 130, no. 1–2, pp. 61–76, May 2004.

- [52] C. Lamy, D. J. Jones, C. Coutanceau, P. Brault, S. Martemianov, and Y. Bultel, "Do not forget the electrochemical characteristics of the membrane electrode assembly when designing a Proton Exchange Membrane Fuel Cell stack," *Electrochimica Acta*, vol. 56, no. 28, pp. 10406–10423, Dec. 2011.
- [53] Y. Wang, K. S. Chen, J. Mishler, S. C. Cho, and X. C. Adroher, "A review of polymer electrolyte membrane fuel cells: Technology, applications, and needs on fundamental research," *Appl. Energy*, vol. 88, no. 4, pp. 981–1007, Apr. 2011.
- [54] H. Li *et al.*, "A review of water flooding issues in the proton exchange membrane fuel cell," *J. Power Sources*, vol. 178, no. 1, pp. 103–117, Mar. 2008.
- [55] M. Ji and Z. Wei, "A Review of Water Management in Polymer Electrolyte Membrane Fuel Cells," *Energies*, vol. 2, no. 4, pp. 1057–1106, Dec. 2009.
- [56] M. Lee, M. Uchida, H. Yano, D. A. Tryk, H. Uchida, and M. Watanabe, "New evaluation method for the effectiveness of platinum/carbon electrocatalysts under operating conditions," *Electrochimica Acta*, vol. 55, no. 28, pp. 8504–8512, Dec. 2010.
- [57] X. Yu and S. Ye, "Recent advances in activity and durability enhancement of Pt/C catalytic cathode in PEMFC - Part II: Degradation mechanism and durability enhancement of carbon supported platinum catalyst," *J. Power Sources*, vol. 172, no. 1, pp. 145–154, Oct. 2007.
- [58] Y. Shao, G. Yin, Z. Wang, and Y. Gao, "Proton exchange membrane fuel cell from low temperature to high temperature: Material challenges," *J. Power Sources*, vol. 167, no. 2, pp. 235–242, May 2007.
- [59] S. Mu, C. Xu, Y. Gao, H. Tang, and M. Pan, "Accelerated durability tests of catalyst layers with various pore volume for catalyst coated membranes applied in PEM fuel cells," *Int. J. Hydrog. Energy*, vol. 35, no. 7, pp. 2872–2876, Apr. 2010.
- [60] M. S. Wilson and S. Gottesfeld, "Thin-film catalyst layers for polymer electrolyte fuel cell electrodes," *J. Appl. Electrochem.*, vol. 22, no. 1, pp. 1–7, Jan. 1992.
- [61] I.-W. Oh *et al.*, "Method of preparing membrane-electrode-gasket assemblies for polymer electrolyte fuel cells," US7056612 B2, 06-Jun-2006.

- [62] Y. Zhang, C. Wang, N. Wan, Z. Liu, and Z. Mao, "Study on a novel manufacturing process of membrane electrode assemblies for solid polymer electrolyte water electrolysis," *Electrochem. Commun.*, vol. 9, no. 4, pp. 667–670, Apr. 2007.
- [63] T. Frey and M. Linardi, "Effects of membrane electrode assembly preparation on the polymer electrolyte membrane fuel cell performance," *Electrochimica Acta*, vol. 50, no. 1, pp. 99–105, Nov. 2004.
- [64] R. R. Passos, V. A. Paganin, and E. A. Ticianelli, "Studies of the performance of PEM fuel cell cathodes with the catalyst layer directly applied on Nafion membranes," *Electrochimica Acta*, vol. 51, no. 25, pp. 5239–5245, Jul. 2006.
- [65] L. Sun, R. Ran, G. Wang, and Z. Shao, "Fabrication and performance test of a catalyst-coated membrane from direct spray deposition," *Solid State Ion.*, vol. 179, no. 21–26, pp. 960–965, Sep. 2008.
- [66] H.-N. Su, S.-J. Liao, T. Shu, and H.-L. Gao, "Performance of an ultra-low platinum loading membrane electrode assembly prepared by a novel catalyst-sprayed membrane technique," *J. Power Sources*, vol. 195, no. 3, pp. 756–761, Feb. 2010.
- [67] J. Xie, F. Xu, D. L. Wood III, K. L. More, T. A. Zawodzinski, and W. H. Smith, "Influence of ionomer content on the structure and performance of PEFC membrane electrode assemblies," *Electrochimica Acta*, vol. 55, no. 24, pp. 7404–7412, Oct. 2010.
- [68] M. Uchida, Y. Aoyama, N. Eda, and A. Ohta, "Investigation of the Microstructure in the Catalyst Layer and Effects of Both Perfluorosulfonate Ionomer and PTFE-Loaded Carbon on the Catalyst Layer of Polymer Electrolyte Fuel Cells," *J. Electrochem. Soc.*, vol. 142, no. 12, pp. 4143–4149, Dec. 1995.
- [69] S. Jeon *et al.*, "Effect of ionomer content and relative humidity on polymer electrolyte membrane fuel cell (PEMFC) performance of membrane-electrode assemblies (MEAs) prepared by decal transfer method," *Int. J. Hydrog. Energy*, vol. 35, no. 18, pp. 9678–9686, Sep. 2010.
- [70] K.-H. Kim *et al.*, "The effects of relative humidity on the performances of PEMFC MEAs with various Nafion® ionomer contents," *Int. J. Hydrog. Energy*, vol. 35, no. 23, pp. 13104–13110, Dec. 2010.

- [71] J. H. Jang *et al.*, “Complex Capacitance Analysis of Ionic Resistance and Interfacial Capacitance in PEMFC and DMFC Catalyst Layers,” *J. Electrochem. Soc.*, vol. 156, no. 11, pp. B1293–B1300, Nov. 2009.



ลิขสิทธิ์มหาวิทยาลัยเชียงใหม่
Copyright© by Chiang Mai University
All rights reserved